




TESTING


FITOTERM °C
FITOCLIMA °C



TEMPERATURE / HUMIDITY

REACH-IN CLIMATIC CHAMBERS FOR TEMPERATURE AND CLIMATIC TESTING





FitoTerm & FitoClima temperature and humidity testing chambers offer highly precise and reproducible conditions for climatic and temperature testing in many industries. **Common applications include:**

Environmental Testing

Electronics, Automotive, Aerospace, Building materials, Military equipment, Materials in general

Research

Quality Control

Production facilities



ARALAB

ARALAB is a company specialized in designing, developing, manufacturing and servicing of high quality Climatic Chambers.

For more than 25 years we have been perfecting ways to create and control temperature, humidity and many other environmental conditions that respond to the needs of customers all around the world.

Only the highest quality components are used to manufacture our chambers so customers can have the best equipment for their research and testing purposes.

Aralab chambers.
Your own climate.

FEATURES

The most advanced technology in climate control

Internal aerodynamic optimization to ensure uniformity of climatic conditions

Time saving features with easily configurable testing programs that can run, start and stop automatically

Highly resistant stainless steel interior for maximum durability and easy cleaning

Flexible interior with height adjustable and removable stainless steel shelves

Nonpolluting construction and cooling system

Compliant with international standards and requirements EN, IEC, DIN, ISO, NP and UNE

TEMPERATURE AND HUMIDITY CONTROL RANGES

FITOTERM Chambers – Temperature only

FITOTERM CHAMBERS	TEMPERATURE RANGE	HUMIDITY RANGE
FitoTerm E10 *	-10°C to +100°C	N/A
FitoTerm E20	-20°C to +180°C	N/A
FitoTerm E45	-45°C to +180°C	N/A
FitoTerm E75	-75°C to +180°C	N/A

FITOCLIMA Chambers – Temperature and Humidity

FITOCLIMA CHAMBERS	TEMPERATURE RANGE	HUMIDITY RANGE
FitoClima EP, EC & ECP 10 *	-10°C to +100°C	10 to 98% RH
FitoClima EP, EC & ECP 20	-20°C to +180°C	10 to 98% RH
FitoClima EP, EC & ECP 45	-45°C to +180°C	10 to 98% RH
FitoClima EP, EC & ECP 75	-75°C to +180°C	10 to 98% RH

* -10°C to +100°C temperature range only available on the 300 liters models

* EP, EC & ECP refer to the humidity sensors. EP = Electronic Psychrometric; EC = Electronic Capacitive; ECP = Electronic Capacitive + Psychrometric

TECHNICAL DATA

FITOCLIMA AND FITOTERM TESTING CHAMBERS	
Performance in CLIMATIC testing range only FITOCLIMA chambers	
TEMPERATURE RANGE	10°C to 95°C
TEMPERATURE UNIFORMITY (DEVIATION IN SPACE) ⁽¹⁾	± 0,1°C to ± 1,0°C
TEMPERATURE FLUCTUATION (DEVIATION IN TIME) ⁽¹⁾	± 0,1°C to ± 0,3°C
HUMIDITY RANGE	10% RH to 98% RH
HUMIDITY STABILITY	± 0,5% RH to ± 3% RH
Performance in TEMPERATURE testing FITOTERM and FITOCLIMA chambers	
TEMPERATURE RANGE	-75°C, -45°C or -25°C up to 180 °C
TEMPERATURE UNIFORMITY (DEVIATION IN SPACE)	± 0,5°C to ± 1,5°C
TEMPERATURE FLUCTUATION (DEVIATION IN TIME)	± 0,1°C to ± 0,5°C
TEMPERATURE RATE OF CHANGE HEATING ⁽¹⁾	From 2,5°C to 4,5°C / minute ⁽²⁾
TEMPERATURE RATE OF CHANGE COOLING ⁽¹⁾	From 2°C to 4°C / minute ⁽²⁾
Other technical data	
NOISE LEVEL	55 to 64 dBA
ELECTRICAL CONNECTION	3/N/PE AC 400V ± 10% 50Hz

Performances measured in factory with ambient temperatures between 20°C and 25°C


1) According to IEC EN 60068-3-5

2) Values will vary with FitoClima/FitoTerm model and size, compressor type and number of compressors. Temperature rate of change can be adjusted to comply with the necessary heating / cooling speed requirements. Optional accessories available for more demanding heating and cooling temperature change rates

DIMENSIONS AND DRAWINGS


FITOTERM / FITOCLIMA 300

 EXTERIOR DIMENSIONS (H x W x D) (mm)	1.830 x 980 x 1.340
 INTERIOR DIMENSIONS (H x W x D) (mm)	800 x 650 x 600





FITOTERM / FITOCLIMA 500

 EXTERIOR DIMENSIONS (H x W x D) (mm)	1.850 x 1.000 x 1.500
 INTERIOR DIMENSIONS (H x W x D) (mm)	920 x 700 x 780





FITOTERM / FITOCLIMA 1.000

	EXTERIOR DIMENSIONS (H x W x D) (mm)	2.035 x 1.287 x 1.828
	INTERIOR DIMENSIONS (H x W x D) (mm)	1.022 x 1.022 x 1.061



FITOTERM / FITOCLIMA 1.500

	EXTERIOR DIMENSIONS (H x W x D) (mm)	2.050 x 1.287 x 2.250
	INTERIOR DIMENSIONS (H x W x D) (mm)	1.022 x 1.022 x 1.500



EQUIPMENT DESCRIPTION

Temperature

Control of temperature is done by the PLC Touch Screen ClimaPlus V, high tech PID / FUZZY temperature and humidity control, developed by Aralab.

Temperature Precision (in the interior of the chamber, at 5 cm from walls, floor and top)

In Time $\leq \pm 0,5^{\circ} \text{C}$
 In Space $\leq \pm 1,5^{\circ} \text{C}$

Temperature Sensors

One (1) PT 100 Class A, located in air treatment tunnel
 Two (2) PT 100 Class A, movable sensors for flexible placing inside chamber



Heating

By tubular stainless steel electric heaters located in the air treatment tunnel

Cooling

By airtight mechanical compressor group Copeland Scroll (low noise, high efficiency) with enforced ventilation and without use of CFC's.

As an option the system can be cooled by an air / water condenser. Air is used by default and only in need of greater power is water used, thus increasing efficiency. For -75°C models water option is standard and air is optional.



Thermal security

Safety thermostat with High / Low temperature configuration, with automatic stop of all thermic systems. High / Low temperature alarms programmed in the controller, with mute function. This function won't stop the chamber and it's only used to record the occurrence and to call the attention of the users with an audible alarm.

Humidity (FitoClima chambers)

Control of humidity levels is done by the PLC Touch Screen ClimaPlus V, high tech PID / FUZZY temperature and humidity control, and developed by Aralab.

Humidity Precision (in the interior of the chamber, at 5 cm from walls, floor and top)


In Time $\leq \pm 1,0\% \text{ RH}$
 In Space $\leq \pm 2,5\% \text{ RH}$

Humidity Sensors

To measure and control humidity, Aralab has different probing technologies: Psychrometric, Capacitive, or both simultaneously. Consult Aralab for technical support on the appropriate selection.



Humidity sensors: Humidity Vs. Temperature ranges graphic



For climatic tests that require humidity and temperature ranges highlighted **in red** on the graph, a Psychrometric sensor is recommended (EP and ECP models). Please consult Aralab for help on the choice between these two models.

Humidity / Drying

Humidity: Through thermostatic bath with dew point control.

Drying: Through thermostatic bath with dew point control and additional dry coil


Security

Automatic stop function in case of water failure, with indication on the controller; High / Low Temperature alarms; High / Low humidity alarms;

Air Flow / Ventilation

Air Flow: Forced through 2 ventilators/fans (for 300 liters model, just one ventilator/fan is used) mounted at the top of the chamber.

Air Renovation: By lateral port, also for compensating pressure.



Construction

Interior: AISI 304 hermetical welded, vapor tight, stainless steel

Exterior: Zinc mild steel with epoxy coating finish (color RAL 7035)

Insulation: Rock Wool


Interior illumination: Halogen lamp 12V (only available with optional window)

Door: Double silicone joints and anti-condensation heating frames.

Cut-off panel, Security and Communications

Mounted on left lateral panel of the chamber and equipped with:

- High / Low safety thermostat
- Main Power switch
- Audible alarms
- RS232 Output




Inclusions

- 2 Stainless steel shelves
- 1 lateral left panel entry port with Ø 80 mm
- 4 / 6 height leveling casters
- Instructions manual in English (other languages upon request)
- 2 years warranty



Aralab Testing chambers details



From left to right: interior of FitoClima 300 and 1.500. Visible at the images: highly resistant AISI 304 stainless steel with height adjustable shelves, port-hole and PT100 class A temperature sensor. Fans and perforated trays and interior base allow for uniform circulation and distribution of temperature and humidity inside the chamber.



FitoClima 300 with a chilled mirror dew point hygrometer for calibration inside




Two FitoClima chambers with liquid nitrogen injection, allowing up to 10°C / minute cooling speeds

CONTROLLER



CLIMAPLUS V

- Programmable PLC exclusively developed for ARALAB chambers
- Programmable easy to use controller with Touch Screen Display (168 x 112mm)
- Resolution of 0.1°C for Temperature and 0.1% for Relative Humidity
- High performance temperature and humidity control with value correction possibility in all ranges
- Capability for creating 50 programs of 50 segments each
- Non-volatile memory
- Automatic restart of tests due to power failure, without losing data and restarting test where it was interrupted
- Real-time monitoring of all functions and control of equipment.
- Send all control settings and system software via RS232 to plant.
- Possibility of programming a delay of the beginning of test
- Monitoring and recording of all alarms
- Possibility of performing events by external commands
- Several outputs for connecting computers or other devices
- Alarms management
- Graphic representation of the tests ran
- Graphical visualization of the test in the controller.
- Possibility of running computer test programs and export them to the controller




FITOLOG SOFTWARE


The FitoLog software pack is a set of applications designed to facilitate the managing, monitoring and recording of programs and data from the FitoClima chambers. It consists of 3 applications: **FitoLog**, **FitoLogView** and **FitoProgram**.



FitoLog: Records and displays in real time all data and details related to the set-points, running variables and equipment behavior. It also retrieves information about the active components of the chamber, running processes, errors, alarms and allows the configuration of periodic or alarm triggered remote notifications (by email or SMS, depending on existing connections and accessories).



FitoLogView: It is a working tool to process the data recorded by the FitoLog program. One can view, print and export the log contents to other file types, and analyse the data in other data management software (Excel, Star Office, Access or others).



FitoProgram: This application simplifies the creation of programs and its integration on the chamber ClimaPlus controller. Up to 32 programs, each with 24 segments, can be designed and linked to create detailed environmental profiles and simulations.

Notifications, fast diagnostics and prompt troubleshooting: With **FitoLog** it is possible to gather data from each of the chambers systems, which makes it a very useful tool to diagnose any necessary maintenance. This tool works as the “black box” of the equipment, giving Aralab technicians the necessary data to remotely carry out a fast and efficient diagnostic. All that is needed is a FitoLog file.


Most common optional accessories

- Software FitoLog and FitoLogView
- Wireless and Ethernet connections for PC running FitoLog software
- Observational anti condensation windows in multi layered glass
- Water demineralizer (for FitoClima Chambers)
- Water conductivity monitor (for FitoClima Chambers)
- Additional entry ports
- Calibration certificate from accredited external laboratory
- Height leveling casters
- Faster heating / cooling temperature change rates

Other accessories are available on request. Please consult Aralab.

Window Option

The observation window is composed of a multilayered glass with optimum levels of thermal insulation. The interior and exterior glasses have a heating system that is activated in cold cycles and damp heat to prevent condensation at the surface.




Other Testing Accessories and Devices



Cable rolling device



Combined climatic and vibration test



Impact stress tests

INSTALLATION REQUIREMENTS

To ensure a correct functioning of the chamber, the following installation conditions are required:

Installation site

The place should be easily accessible, according to equipment dimensions and weight. It should have good air circulation and a room temperature between 10° and 26°C. The floor should be leveled and a minimum distance of 50cm from the walls and other equipment must be kept.

Electrical supply

Near the equipment with the specified requirements.

Humidification circuit and demineralized water (for FitoClima models)

The humidification circuit works exclusively with distilled or demineralized water. For this circuit, a water admission pressure of 1 to 6 bares and conductivity of $\leq 10\mu$ Siemens is required.

Water circuit for cooling condenser (optional for -45°C and standard for -75°C)

A cold water circuit is required for the cold system condenser. Technical characteristics:

- o Water flow: 0 to 2000 liters/hour maximum
- o Intake pressure: 3 to 6 bares
- o Water entry and exit pipe: 1"
- o Differential pressure between entry and exit: > 2,5 bares
- o Maximum temperature of water entry: 26°C
- o Adequate temperature of water entry: 18°C

Drain

At floor level and near the equipment. The draining of the humidification and cooling systems water is done by gravity. For a correct draining there should be a minimum inclination of 10° in a descending trajectory from the chambers draining pipe until the sewage system.

Features and specifications are subject to change. Aralab continuously studies ways to further develop its products to achieve better performances and overall product quality. As a result, characteristics and specifications provided in this document may be subject to changes.