

Datasheet

Art.No. 70.354.0635.1

Hood BAS GOT GI 6 M25 A1

revos BASIC 500V size 6 hood with threaded collar M25, top cable entry, single locking lever



Art.No.	70.354.0635.1
EAN	4015573650831
Order unit	1 pieces

Approvals



Technical data

General

Housing material	Aluminium
Colour	Grey
Surface	With powder coating
Degree of protection (IP)	IP54
UV resistant	Yes
Inflammability class of insulation material acc. with UL94	Other
Operating temperature range min.	-40 °C
Operating temperature range max.	120 °C

Model

DIN-size	6
Model	male
Locking mechanism	Single locking lever
Cable entry	Above
Type of cable	Thread
With cable screw gland	No
Thread size M	25
Hinged lid	No
EMC-version	No

Classification

ECLASS 8.1	27440202: Housing for industrial connectors
ETIM 6.0	: EC000437

ETIM 5.0	EC000437: Housing for industrial connectors
ETIM 4.0	EC000437: Housing for industrial connectors
ETIM 3.0	EC000437: Housing for industry plug connectors

Drawings

Varianten/ Variants

70.352.0635.5	BAS GOT 61 6 M25 A5	Kabeilverkroebung (KV), IP65 /Cable gland (CG), IP65
70.352.0635.4	BAS GOT 61 6 M20 A4	KV mit Zugentlastung, IP54 /CG with strain relief, IP54
70.352.0635.3	BAS GOT 61 6 M25 A3	KV mit Zugentlastung und Krallschutz, IP54 /CG with strain relief and knock shield, IP54
70.352.0635.2	BAS GOT 61 6 M20 A2	Zwischenstückzahn /Bushing
70.352.0635.1	BAS GOT 61 6 M20 A1	Seitendrehbohrung /Thread hole
70.352.0635.0	BAS GOT 61 6 M20 A0	Kabeilverkroebung (KV), IP54 /Cable gland (CG), IP54

Bestellnummer / Order number:

Typ / Type:

Varianten / Variants:

Wellen Daten, siehe KATALOG oder eKatalog - www.wieland-electric.com
 Additional data see CATALOG or eCatalog - eshop.wieland-electric.com

<input type="checkbox"/>	Kontakt/Material Kontakt	2013	Explosive	Name	Druck der Öffnung Nr.	Info
<input type="checkbox"/>	Isoliertes Isoliertes	18.08.	IP65	Terminale	T	70.352.0635.0 13K
<input type="checkbox"/>	Isoliertes Isoliertes	18.08.	IP65	Terminale	T	70.352.0635.0 13K
<input type="checkbox"/>	Isoliertes Isoliertes	18.08.	IP65	Terminale	T	70.352.0635.0 13K
<input type="checkbox"/>	Isoliertes Isoliertes	18.08.	IP65	Terminale	T	70.352.0635.0 13K

GEHÄUSEOBerteil
 Gehäuse 6-Kabelbohrung, 60mm-M25
 HOSE 6-size 6-cable out let top-POD/M25