

Datasheet

Art.No. 96.042.4153.0

Connector RST20I4S S1 ZR2 V GL

RST 20I5/4 connector, 4 pole, male, screw connection, application 250V/400V, 20A, for cable diameters 10-14mm, coding-color light grey, color of housing light grey



Art.No.	96.042.4153.0
EAN	4015573863194
Order unit	1 pieces

Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated voltage 2	400 V
Rated impulse voltage	4 kV
Strain relief	Yes
Pollution degree	3
Mechanical coding	Code 0
Lockable	Yes
Color of coding/ contact carrier	Light grey
Marking of poles	1, 2, 3, PE
Color of housing inclusive strain relief	Light grey

Connection Data

Cable diameter	14 mm
Cable diameter 2	10 mm
Cable diameter 3	14 mm
Cross section solid	4 mm ²
Cross section solid 2	0.75 mm ²
Connection cross section stranded max.	4 mm ²
Cross section stranded 2	0.75 mm ²
Terminations per pole	1
Connection cross section stranded min.	0.75 mm ²
Connection cross section stranded max.	4 mm ²

Model

Model	male
Connection type	Screw connection
Degree of protection (IP)	IP66/68 (3m;2h) /IP69

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	80.4 mm
Width	34.6 mm
Height	34.6 mm

Classification

ECLASS 8.1	27440605: Plug-in connector for plug-in building installation
ETIM 6.0	: EC002560
ETIM 5.0	EC002560: Plug-in connector for plug-in building installation
ETIM 4.0	EC002560: Plug-in connector for plug-in building installation

Drawings

