


Product description **Contacts: 3+PE, female panel mount connector, PG 9, with VDE, ETS, UL approval, screw**

Area **RD24 Power Series 692/693**
 Order number **09 4224 00 04**


Illustration



Scale drawing




Contact arrangement



	X	Y
1	3,18	-3,18
2	3,18	3,18
3	-3,18	3,18
PE	-3,18	-3,18

Derating curve



You can find the assembly instructions on the next page.

Technical data

General values

Connector design	female panel mount connector
Connector locking system	bolted
Termination	screw
Wire gauge (mm)	max. 2,5 mm ²
Wire gauge (AWG)	max. 14
Cable outlet	-
Upper limit temperature	100 °C
Lower limit temperature	-40 °C

Cable data

Approval 1	UL
Approval 2	ESTI+
Approval 3	VDE

Electrical values

Rated voltage	400 V
Rated impulse voltage	6000 V
Pollution degree	3
Overvoltage category	III
Insulating material group	III
Rated current (40 °C)	16 A (12 A UL)
Volume resistivity	≤ 5 mΩ
EMC compliance	Shielding is not possible
Degree of protection	IP67
Mechanical operation	> 500 Mating cycles

Material

Contact material	CuZn (Messing)
Contact plating	Ag (silver)
Contact body material	PBT


Product description

Contacts: 3+PE, female panel mount connector, PG 9, with VDE, ETS, UL approval, screw

Area
Order number

RD24 Power Series 692/693
09 4224 00 04

Assembly instructions / Panel cut-out



Product description **Contacts: 3+PE, female panel mount connector, PG 9, with VDE, ETS, UL approval, screw**

Area **RD24 Power Series 692/693**
Order number **09 4224 00 04**

Sicherheitshinweise

1. The connector must not be connected or separated under load. Non-observance and incorrect use can result in personal injury.
2. The connectors are designed for use in plant, control system and electrical equipment. The end user is responsible for checking whether the connectors are suitable for use in other applications.
6. Connectors with degree of protection IP 67 and IP 68 are not suitable for use under water. When used outdoors, the connectors must be separately protected against corrosion. For further information about IP degrees of protection refer to 'Technical support' in the Download Centre.