

Datasheet

Art.No. 71.330.1635.1

Bottom BAS GUT GL 16 M25 A1

revos BASIC 500V size 16 closed-bottom base with 2 threaded collars M25, single locking lever



Art.No.	71.330.1635.1
EAN	4015573620872
Order unit	1 pieces

Approvals



Technical data

General

Housing material	Aluminium
Colour	Grey
Surface	With powder coating
Degree of protection (IP)	Other
UV resistant	Yes
Inflammability class of insulation material acc. with UL94	Other
Operating temperature range min.	-40 °C
Operating temperature range max.	120 °C

Model

DIN-size	16
Model	Surface mounting (base)
Locking mechanism	Single locking lever
Cable entry	Two-sided
Type of cable	Thread
With cable screw gland	No
Thread size M	25
Hinged lid	No
EMC-version	No

Classification

ECLASS 8.1	27440202: Housing for industrial connectors
ETIM 6.0	: EC000437

ETIM 5.0	EC000437: Housing for industrial connectors
ETIM 4.0	EC000437: Housing for industrial connectors
ETIM 3.0	EC000437: Housing for industry plug connectors

Drawings

71.330.1635.1	BAS GUT 6L 16 M25 A1	Seiteneinbohrung / Thread hole	X
71.330.1635.0	BAS GUT 6L 16 M25 A0	Kabelverschraubung (KV) /PSC montiert / Cable gland (CG) /PSC assembled	
Bestellnummer / Order number	Typ / Type	Variante / Variant	Art. / Part no.
Weitere Daten, siehe KATALOG oder eKatalog. www.wieland-electric.com Additional data see CATALOG or eCatalog. eshop.wieland-electric.com			

Bohrbild / Cut out

Varianten/Variants

.0

Bohrbild / Cut out

71.330.1635.1	BAS GUT 6L 16 M25 A1	Seiteneinbohrung / Thread hole	X
71.330.1635.0	BAS GUT 6L 16 M25 A0	Kabelverschraubung (KV) /PSC montiert / Cable gland (CG) /PSC assembled	
Bestellnummer / Order number	Typ / Type	Variante / Variant	Art. / Part no.
Weitere Daten, siehe KATALOG oder eKatalog. www.wieland-electric.com Additional data see CATALOG or eCatalog. eshop.wieland-electric.com			

GEHAUSEUNTERTEIL

Boßgröße 16-Kabelabgung 2-M25

Housing size 16-cable outlet 2-M25