



# Datasheet

Art.No. 97.052.4253.1

Connector RST50I5S S1 ZR7 S SW

RST 50i5/4 Connector, 5 pole, male, screw connection, application 250V/400V, 50A, for cable diameters 20-32mm, coding-color black, color of housing black



Art.No.	97.052.4253.1
EAN	4049088080036
Order unit	1 pieces

# Approvals



## Technical data

#### General

Rated current	50 A
Rated voltage	250 V
Rated voltage 2	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	1, 2, 3, N, PE
Color of housing inclusive strain relief	Black

#### **Connection Data**

Cable diameter	32 mm
Cable diameter 2	20 mm
Cross section solid	6 mm²
Cross section solid 2	4 mm²
Connection cross section stranded max.	16 mm <sup>2</sup>
Cross section stranded 2	4 mm <sup>2</sup>
Terminations per pole	1

#### Model

Model	male
Connection type	Screw connection





Degree of protection (IP)	IP66/67/69

## Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continous temperature	80 °C
Surface finish	Silver-plated

## Dimensions

Length	140 mm
Width	65 mm
Height	65 mm

#### Classification

ECLASS 8.1	27440605: Plug-in connector for plug-in building installation
ETIM 6.0	: EC002560
ETIM 5.0	EC002560: Plug-in connector for plug-in building installation
ETIM 4.0	EC002560: Plug-in connector for plug-in building installation





# Drawings

