

# HAFFMANS MK-3 CPM<sup>®</sup> FILTERTESTER

## GENERAL PRODUCT INFORMATION

Effective sterile filtration, to prevent contamination, spoilage and product loss, is an essential part of your production process. The Pentair Haffmans CPM FilterTester, type MK-3, provides easy testing of CPM sterile filter elements as well as most conventional filter cartridges. When used with CPM sterile filters, the MK-3 allows for in-line testing.

### Test method

The test method employed by the MK-3 is known as the "Go/No Go" Test and provides very fast and accurate results. To simulate microorganisms, a microfog or series of smoke-like particles is generated within the FilterTester from non-toxic saturated synthetic hydrocarbons. These hydrocarbons form micro drops of 0.2 to 2.5 µm.

This fog is then applied under pressure from an integrated compressor to the filter being tested. The fine fog particles quickly penetrate even the smallest leaks in the filter providing immediate visual identification.

A filter test can be performed in less than a minute. The procedure is simple and requires no special knowledge or skills.

A digital timer is integrated in the FilterTester. After adjusting the time and operating the start/stop button the creation of the microfog starts. The integrated pump starts automatically with a delay of 5 seconds and leads the microfog under low pressure to the internal part of the filter element being tested.

After the filter test, the micro drops evaporate without leaving any trace in the filter element.

Sterilization of the filter element after the filter test is recommended.



## CUSTOMER BENEFITS

- **Cost saving**
  - On labor - the filter test, including all preparations, can be performed in less than 2 minutes
  - On utilities - no water or compressed air from an external source required
  - On resources - the test does not damage the filter element
- **Easy to perform test method, no special knowledge or skills required**
- **High security**
  - Clear detection of filter element defects (Go/No Go)
  - Proven test method
- **In-line testing ability**
- **Compact solution - you do not need a multi-part test set-up, just the FilterTester**

## APPLICATIONS

In all industries, suitable for all CPM sterile filters and most conventional sterile filter cartridges.

# HAFFMANS MK-3

## CPM FILTERTESTER

### TECHNICAL DATA

**Dimensions**

300 x 220 x 205 (LxWxH mm), excl. filter element connection

**Weight**

12 lbs/5.2 kg

**Operating Voltage**

wide range 80-240 V/50 - 60 Hz

**Connection point for test filter**

R-1" inner thread

**Power consumption**

approx. 60 W

**Maximum testing pressure**

1.0 barg/14.5 psig

### SCOPE OF SUPPLY

- FilterTester, type MK-3
- Power supply module
- Mains cable for power supply module
- Smoke liquid (Aerosol)
- Silicone grease (100 g)
- Instruction Manual

### OPTIONS

Filter element adapters for CPM filter elements and conventional filter cartridges, connection to be specified.

**HAFFMANS B.V.**

P.O. BOX 3150, 5902 RD VENLO, NETHERLANDS WWW.FOODANDBEVERAGE.PENTAIR.COM

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.