

The SCIOLOGEX SCI506 low-speed centrifuge is supplied with a fixed angle rotor which can hold up to 6 x 15mL/10mL/7mL/5mL tubes (adapters included). It is widely used for blood or urine separation in medical routine practice in hospitals, clinics or research institutes.

SCI506 Low-speed Centrifuge



Features

- Speed range 300-5000rpm
- Rotor speed can be set and displayed in RPM or G-force
- Two memory programs
- Two deceleration speeds setting to meet different requirements
- Easy-to-read display
- Automatic lid-lock release
- Maintenance-free brushless DC motor



Specifications

SCI506

| | |
|---------------------------|--|
| Speed Range | 300-5000rpm, increment:10rpm |
| Max. RCF | 2350xg, increment: 10g |
| Speed accuracy | ±20rpm |
| Rotor capacity | 6x15mL/10mL/7mL/1.5-5ml |
| Run Time | 30sec-99min, HD(continuous running) |
| Display | LCD |
| Programs Memory | 2 |
| Acceleration/Deceleration | 1 ↑ 2 ↓ |
| Safety Devices | Door interlock, Overspeed detector, Automatic internal diagnosis |
| Motor | Brushless DC motor |
| Power | Single-phase, 100V-240V,50Hz/60Hz, 70W |
| Dimension(WxDxH) | 300X240X180mm |
| Weight | 11lbs |

Advanced features

Speed/RCF switch; sound-alert function

Included adapters



A5P17

Cat. No.19500022

5ml adapter, Adapted to 13×75mm blood collection tube



A2P17

Cat. No.19500023

1.5/2ml Cryogenic Vials/ centrifuge tube adapter