



Water and oil baths with analogue control	pages	84 to 86
Sand baths	page	85
Circulation pump	page	85
Water and oil baths with digital control	pages	86 to 89
Histology paraffin bath	page	90
Bank of water and oil baths	page	91
Precise shaking baths	page	91 and 92
Microprocessor control		
Viscometer bath	page	92
Ultrasonic cleaning baths	page	93 to 95



Ultrasonic Cleaning Baths "Ultrasons",

"Ultrasons UB-1488", "Ultrasons-H", "Ultrasons-HD"and "Ultrasons-P"

FUNDAMENTAL THEORY

The principal of ultrasonic cleaning consists of the use of high frequency sound waves (40 kHz), produced by a generator through a transducer, which propagates them mechanically inside the tank, this produces a cavitation effect which leads to the formation of millions of low pressure microscopical bubbles which carry out molecular cleaning, eliminating impurities, polluting agents and dirt from the parts or material which must be cleaned.

Complex parts can be cleaned without disassembly since the cavitation penetrates wherever the cleaning solution is in contact with the surface.

The generator of these baths is completely transistorised and incorporated, working through the "Sweeping frequency" system, which ensures uniform cavitation at all points of the resonance tank.

COMMON FEATURES

Double bodied tank, made entirely of stainless steel.

Emptying drain, anti-parasite filter, adjustable timer and heating, model dependent.

APPLICATIONS

Laboratories in general: acceleration of chemical reactions, degassing of liquids, cell disruption, cleaning of sieves, pipettes, micro-pipettes, cuvettes, trays, viscometers, decomposition of radioactive substances, etc.

Dentistry: Cleaning of prosthesis, instruments, etc.

Optics: Cleaning of frames, lenses, and contact lenses, etc.

SUMMARY TABLE

Medicine: Cleaning of instruments in general, forceps, probes, scalpels etc. **Jewellery and Watch making:** Cleaning of all kind of watches and jewels. **Industry:** Cleaning of all electronic components, printed circuit boards, semiconductors, petrol injector sieves and filters, etc.





Ultrasonic bath, Automatic Lift and Dry "Ultrasons-UB-1488"

Selecta original model. Quick dry, without having to control the instrument



MODEL

INIUDEL						
Part No.	Capacity litres	Height / Width /Depth (usable) cm	Height / Width /Depth (exterior) cm	Generator power W	Power total W	Weight Kg
3001488	6	15 30 14	30 40 34	150	2150	12

Comes complete with basket.

FEATURES

Bath with automatic basket elevator that operates at the end of the time cleaning cycle.

Hot air drying by two-turbine air fans that switch on at the start of the elevation and finalise the complete operation. Waste drain at the front of the instrument. Removable support basket.



CONTROL PANEL

- 1. Cleaning time control: 0-15 minutes.
- 2. Push button drying time: 0-15 minutes.
- 3. Push button increase value.
- 4. Push button reduce value.
- 5. Push button stop / start.
- 6. Digital timer display.