



HQ11D Portable pH Meter with Gel pH Electrode, 1 m Cable

Product #: HQ11D53101000

USD Price: Contact Hach

Call for ship date

Designed for your pH applications, the Hach HQ11D portable pH meter is an advanced handheld digital meter that takes the guesswork out of measurements. The Hach HQD digital pH meter combines reliability, flexibility and ease of use. The HQD portable meters connect with a wide range of Intellical smart pH electrodes addressing different sample types and operating environment for water quality, environmental and treatment process purposes. The Intellical probe automatically recognize the testing parameter, store the calibration history, and method settings to minimize errors and setup time.

Intellical™ PHC101 is a digital combination pH electrode with built-in temperature sensor. PHC101 has low maintenance needs thanks to a non-refillable gel-filled single open reference junction. The laboratory version of this pH electrode is shockproof with its epoxy plastic body protecting down to the glass bulb sensing element. The PHC101 electrode is ideal for measuring pH in wastewater, drinking water and general aqueous applications. The PHC101 is not suitable for use with organic solvents or samples with pH less than 2.

Rugged pH meter for efficient field water testing

Single input channel for pH, Oxidation Reduction Potential (ORP/mV) and temperature - connect to any pH or ORP Intellical™ smart electrode, probe and sensor.

Intuitive user interface for simple operation, reliable and accurate results

Guided calibration and check standard routines reduce calibration errors while stabilization alerts and visual measurement lock ensure that you can trust the accuracy of the results. Calibration status indicator and custom calibration alerts ensure accurate results.

Trust your measurements - Intellical™ smart probes store all calibrations in the probe

Calibration history allows quick and easy change out of probes without re-calibrating. The HQD™ smart system records serial numbers, current calibration data, user ID, sample ID, time, and date automatically in the data log for complete Good Laboratory Practice (GLP) traceability.

Designed for demanding field operating conditions and ease of use

Rugged and waterproof meter design provides worry-free, reliable operation in field environments. All connections between the meter and the probe are secure. Connectors can be color-coded for quick identification. Information is clearly displayed on the one screen with back light for low light conditions. Display results can be enlarged.

Complete convenient kit

Package content includes everything you need to start testing. Details below

Specifications

AC Power Adapter and USB/DC Adapter:	Optional
Automatic Buffer Recognition:	Yes
Calibration Intervals/Alerts/Reminder:	Off, Selectable from 2 hours to 7 days
Compliance Certifications:	CE, WEEE
Contents:	Meter + Probe(s)

Custom Calibration Standards:	Yes
Data Export:	Download via USB connection to PC or flash memory device. Automatically transfer entire data log or as readings are taken.
Data Memory:	500 records/FIFO
Data Storage:	Automatic, GLP ISO compliant reading data stored with calibration details.
Digital (intelligent) electrode inputs:	1 channel
Display:	Detailed mode/Large mode
Display Lock Function:	Continuous / Auto-stabilization ("press to read") / At Interval
Display Type:	240 x 160 pixel LCD with backlight illumination
GLP Features:	Date; Time; Sample ID; Operator ID
Inputs:	1
Instrument:	Portable
IP Rating:	IP67
Languages:	English, French, German, Italian, Spanish, Danish, Dutch, Polish, Portuguese, Turkish, Swedish, Czech, Russian
Measurement Method:	Probe specific programmed method settings
Model:	HQ11D – pH/1 Channel
mV Measurement at Stable Reading:	Yes
mV Measurement Range:	-1500 - 1500 mV
mV Resolution:	0.1 mV
Operating Error Messages:	Clear text error messages displayed
Operating Humidity:	90 % relative humidity (non-condensing)
Operating Interface:	Soft Touch Keypad
Operating Temperature:	0 - +60 °C (32 - 140 °F)
ORP Electrode Calibration:	Predefined ORP standards (including Zobell's solution)
Parameter:	pH/Oxydo Reduction Potential (ORP)
PC Data Transfer Software:	HQd Series Meter Data Transfer Utility
pH Buffer Sets:	Color-coded: 4.01, 7.00, 10.01 pH; IUPAC: 1.679, 4.005, 7.000, 10.012, 12.45 DIN: 1.09, 4.65, 9.23 User-defined custom buffer sets
pH Electrode calibration:	1 - 3 Calibration points Calibration summary data logged and displayed
pH Measurement Range:	0 - 14 pH
pH Resolution:	Selectable: 0.001/0.01/0.1 pH
Printer:	Yes, Optional
Probe Type:	IntelliCAL Standard Laboratory or Rugged Field
Probes included:	PHC10101
Salinity Measurement Range:	0 - 42 (ppt) (‰)
Salinity Resolution:	0.01 (ppt) (‰)
TDS Measurement Range:	0.00 mg/L - 50.0 g/L NaCl
TDS Resolution:	0.01 mg/L up - 0.1 g/L upon measuring range

Temperature Compensation:	Automatic Temperature compensation for pH
Temperature Measurement:	°C or °F
Temperature Resolution:	0.1
Warranty:	3 years
Weight:	335 g (0.75 lb) without batteries; 430 g (0.95 lb) with

What's in the box?

Meter package includes HQ11D Portable Meter; 4 AA batteries, PHC101 Laboratory Gel pH Electrode, 1 m cable; quick-start guide and user manuals.