

Entris® II Laboratory Balances



Entris® II – Best Value in its Class for Basic Weighing Tasks

Every Sartorius balance offers quality, value and consistency

No matter what you're weighing, the new Entris® II is always the right choice. Offering unrivalled value at a budget price, this is the only balance in its class featuring isoCAL, LED touch technology and 12 built-in applications. Backed by almost 150 years of German engineering expertise, and available in 40 different models, you'll easily find an Entris® II balance that exactly meets your specific weighing needs.



Find out more
For more information, please visit
www.sartorius.com

Quality, Value and Consistency

For accurate weighing results you can trust time after time

Highest quality standards engineered in Germany

- Highly accurate results year in and year out
 - guaranteed via monolithic weigh cell technology invented by Sartorius*
- Fastest stabilization time in its class
 - using state-of-the-art weighing sensors
- Best repeatability
 - with rectangular weighing pan
- Overload protection
 - rugged design weighs up to a pre-set amount
- Guaranteed reliability
 - with the self-test "@start"
- Made in Germany

Easy clean for operational efficiency and durability

- High chemical resistance
 - ensured using parts made from hard-wearing polybutylene terephthalate (PBT), stainless steel and glass
- Prevents cross contamination
 - with wipe clean design and easy-to-remove parts

Effective draft shield

- Minimizes weighing errors caused by electrostatically charged samples
 - using specially coated glass parts



Innovations in this Weighing Class

For efficient, user-friendly operation

isoCAL (internal calibration and adjustment) for total assurance of accurate weighing results

- Optimal accuracy and operating convenience
 - using fully automated internal temperature and time-controlled calibration and adjustment feature, unique in this weighing class
- Assures (SOP) compliant operation
 - with self-notification if calibration is outside the normal range

Hybrid screen for excellent readability and use

- Combines intuitive, wear resistant LED and touch technology
 - provides an easy and clear structured user interface

Plug-and-play convenience

- Automatically detects Sartorius accessories (e.g. printer, second display)
- Real "PC-direct feature" for easy connection to a PC to transfer weighing data directly into spreadsheets or documents such as Microsoft® Excel or Word

Data output for dynamic weighing applications

- Configurable time interval for data output

Easily adapts to your ambient conditions

- With just one click on the home screen



* may differ for a few models



Find out more
For more information, please visit
www.sartorius.com

Universal Application

For future-proof assurance

The right model for each and every task

- Offering a range of 40 models (the largest portfolio in its class), starting from 60 g up to 8,200 g and a readability from 0.1 mg to 1 g—finding the right model to suit any weighing application is simple

12 built-in applications with GLP | GMP compliant printout | data output

- Weighing | Dosing
- Counting
- Percentage weighing
- Mixing | Net Total
- Components | Totalizing
- Animal weighing
- Calculation | Free Factor
- Density determination
- Statistics
- Peakhold
- Checkweighing
- Mass unit conversion
- and underfloor weighing feature for bigger samples

Weighing chamber (where applicable)

- Highest usable weighing chamber height for easy handling of even large containers
- Convenient access to weighing pan
- Easy-to-(re)move top and side sliding doors
- Draft shield can be removed completely

8 built-in languages for international operation

- English, German, French, Italian, Spanish, Portuguese, Russian, Polish

Modern, up-to-date connectivity methods

- Future-proof USB Type C interface
- Industry-proof RS232 9-pin interface
- Backwards compatibility (by using RS232 port)

Password protection for secure operation

- Protects the balance against unintentional changes



Entris® II Technical Specifications

Model	Weighing capacity	Readability	Repeatability, typical	Stabilization time, typical	Weighing pan size	Weighing chamber height*	Dimensions (W x D x H)	Calibration and adjustment	
	[g]	[mg]	[mg]	[s]	[mm]	[mm]	[mm]	Internal	External
Analytical balances									
BCE64i-1x	60	0.1	0.1	≤1,5	Ø 90	240	219x317x345	•	•
BCE64-1x	60	0.1	0.1	≤1,5	Ø 90	240	219x317x345	-	•
BCE124i-1x	120	0.1	0.1	≤1,5	Ø 90	240	219x317x345	•	•
BCE124-1x	120	0.1	0.1	≤1,5	Ø 90	240	219x317x345	-	•
BCE224i-1x	220	0.1	0.1	≤1,5	Ø 90	240	219x317x345	•	•
BCE224-1x	220	0.1	0.1	≤1,5	Ø 90	240	219x317x345	-	•
Precision balances									
BCE223i-1x	220	1	1	≤1,0	Ø 120	240	219x317x345	•	•
BCE223-1x	220	1	1	≤1,0	Ø 120	240	219x317x345	-	•
BCE323i-1x	320	1	1	≤1,0	Ø 120	240	219x317x345	•	•
BCE323-1x	320	1	1	≤1,0	Ø 120	240	219x317x345	-	•
BCE423i-1x	420	1	1	≤1,0	Ø 120	240	219x317x345	•	•
BCE423-1x	420	1	1	≤1,0	Ø 120	240	219x317x345	-	•
BCE623i-1x	620	1	1	≤1,0	Ø 120	240	219x317x345	•	•
BCE623-1x	620	1	1	≤1,0	Ø 120	240	219x317x345	-	•
BCE653i-1x	650	1	1	≤1,0	Ø 120	50	219x317x145	•	•
BCE653-1x	650	1	1	≤1,0	Ø 120	50	219x317x145	-	•
BCE622i-1x	620	10	10	≤0,9	182x182	-	219x317x94	•	•
BCE622-1x	620	10	10	≤0,9	182x182	-	219x317x94	-	•
BCE822i-1x	820	10	10	≤0,9	182x182	-	219x317x94	•	•
BCE822-1x	820	10	10	≤0,9	182x182	-	219x317x94	-	•
BCE1202i-1x	1,200	10	10	≤0,9	182x182	-	219x317x94	•	•
BCE1202-1x	1,200	10	10	≤0,9	182x182	-	219x317x94	-	•
BCE2202i-1x	2,200	10	10	≤0,9	182x182	-	219x317x94	•	•
BCE2202-1x	2,200	10	10	≤0,9	182x182	-	219x317x94	-	•
BCE3202i-1x	3,200	10	10	≤0,9	182x182	-	219x317x94	•	•
BCE3202-1x	3,200	10	10	≤0,9	182x182	-	219x317x94	-	•
BCE4202i-1x	4,200	10	10	≤0,9	182x182	-	219x317x94	•	•
BCE4202-1x	4,200	10	10	≤0,9	182x182	-	219x317x94	-	•
BCE6202i-1x	6,200	10	10	≤0,9	182x182	-	219x317x94	•	•
BCE6202-1x	6,200	10	10	≤0,9	182x182	-	219x317x94	-	•
BCE2201i-1x	2,200	100	100	≤0,9	182x182	-	219x317x94	•	•
BCE2201-1x	2,200	100	100	≤0,9	182x182	-	219x317x94	-	•
BCE5201i-1x	5,200	100	100	≤0,9	182x182	-	219x317x94	•	•
BCE5201-1x	5,200	100	100	≤0,9	182x182	-	219x317x94	-	•
BCE8201i-1x	8,200	100	100	≤0,9	182x182	-	219x317x94	•	•
BCE8201-1x	8,200	100	100	≤0,9	182x182	-	219x317x94	-	•
BCE6200i-1x	6,200	1,000	1,000	≤0,9	182x182	-	219x317x94	•	•
BCE6200-1x	6,200	1,000	1,000	≤0,9	182x182	-	219x317x94	-	•
BCE8200i-1x	8,200	1,000	1,000	≤0,9	182x182	-	219x317x94	•	•
BCE8200-1x	8,200	1,000	1,000	≤0,9	182x182	-	219x317x94	-	•

* upper edge of the weighing pan to the lower edge of the upper draft shield panel
x = term for country-specific models



Find out more
For more information, please visit
www.sartorius.com

Sales and Service Contacts

For further contacts, visit www.sartorius.com

Europe

Germany

Sartorius Lab Instruments
GmbH & Co. KG
Otto-Brenner-Strasse 20
37079 Goettingen
Phone +49.551.308.0

France & Suisse Romande

Sartorius France
2, rue Antoine Laurent de Lavoisier
ZA de la Gaudrée
91410 Dourdan
Phone +33.1.70.62.50.00

Austria

Sartorius Austria GmbH
Modecenterstrasse 22
1030 Vienna
Phone +43.1.7965760.0

Belgium

Sartorius Belgium N.V.
Rue Colonel Bourg 105
1030 Bruxelles
Phone +32.2.756.06.90

Finland & Baltics

Sartorius Biohit Liquid Handling Oy
Laippatie 1
00880 Helsinki
Phone +358.9.755.951

Hungary

Sartorius Hungária Kft.
Kagyó u. 5.
2092 Budakeszi
Phone +3623.457.227

Ireland

Sartorius Ireland Ltd.
Unit 41, The Business Centre
Stadium Business Park
Ballycoolin Road
Dublin 11
Phone +353.1.8089050

Italy

Sartorius Italy S.r.l.
Via Torino 3/5
20814 Varedo (MB)
Phone +39.0362.5557.11

Netherlands

Sartorius Netherlands B.V.
Phone +31.30.60.53.001
info.netherlands@sartorius.com

Poland

Sartorius Poland sp.z o.o.
ul. Wrzesinska 70
62-025 Kostrzyn
Phone +48.61.6473830

Russian Federation

LLC "Sartorius RUS"
Vasilyevsky Island
5th line 70, Lit. A
199178 St. Petersburg
Phone +7.812.327.53.27

Spain & Portugal

Sartorius Spain, S.A.
Avda. de la Industria, 32
Edificio PAYMA
28108 Alcobendas (Madrid)
Phone Spain +34.913.586.095
Phone Portugal +351.800.855.800

Switzerland

Sartorius Mechatronics Switzerland AG
Ringstrasse 24a
8317 Tagelswangen (ZH)
Phone +41.44.746.50.00

U.K.

Sartorius UK Ltd.
Longmead Business Centre
Blenheim Road, Epsom
Surrey KT19 9QQ
Phone +44.1372.737159

Ukraine

LLS "Sartorius RUS"
Post Box 440 "B"
01001 Kiev, Ukraine
Phone +380.44.411.4918

For more information, view our Sartorius catalog and price list or visit our website.

Americas

USA

Sartorius Corporation
565 Johnson Avenue
Bohemia, NY 11716
Phone +1.631.254.4249
Toll-free +1.800.635.2906

Argentina

Sartorius Argentina S.A.
Int. A. Ávalos 4251
B1605ECS Munro
Buenos Aires
Phone +54.11.4721.0505

Brazil

Sartorius do Brasil Ltda
Avenida Senador Vergueiro 2962
São Bernardo do Campo
CEP 09600-000 - SP- Brasil
Phone +55.11.4362.8900

Canada

Sartorius Canada Inc
1173 North Service Road West, D4
Oakville, ON L6M 2V9
Phone +1.905.569.7977
Toll-Free +1.800.668.4234

Mexico

Sartorius de México, S.A. de C.V.
Libramiento Norte de Tepotzotlan s/n,
Colonia Barrio Tlacateco,
Municipio de Tepotzotlan,
Estado de México,
C.P. 54605
Phone +52.55.5562.1102
leadsmex@sartorius.com

Asia | Pacific

Australia

Sartorius Australia Pty. Ltd.
Unit 5, 7-11 Rodeo Drive
Dandenong South Vic 3175
Phone +61.3.8762.1800

China

Sartorius (Shanghai) Trading Co., Ltd.
3rd Floor, North Wing, Tower 1
No. 4560 Jinke Road
Zhangjiang Hi-Tech Park
Pudong District
Shanghai 201210, P.R. China
Phone +86.21.6878.2300

Hong Kong

Sartorius Hong Kong Ltd.
Unit 1012, Lu Plaza
2 Wing Yip Street
Kwun Tong
Kowloon, Hong Kong
Phone +852.2774.2678

India

Sartorius Weighing India Pvt. Ltd.
#69/2-69/3, NH 48, Jakkasandra,
Nelamangala Tq
562 123 Bangalore, India
Phone +91.80.4350.5250

Japan

Sartorius Japan K.K.
4th Fl., Daiwa Shinagawa North Bldg.
8-11, Kita-Shinagawa 1-chome
Shinagawa-ku, Tokyo, 140-0001 Japan
Phone +81.3.3740.5408

Malaysia

Sartorius Malaysia Sdn. Bhd
Lot L3-E-3B, Enterprise 4
Technology Park Malaysia
Bukit Jalil
57000 Kuala Lumpur, Malaysia
Phone +60.3.8996.0622

Singapore

Sartorius Singapore Pte. Ltd
10 Science Park Rd
The Alpha #02-13/14
Singapore Science Park II
Singapore 117684
Phone +65.6872.3966

South Korea

Sartorius Korea Ltd.
8th Floor, Solid Space B/D,
PanGyoYeok-Ro 220, BunDang-Gu
SeongNam-Si, GyeongGi-Do, 463-400
Phone +82.31.622.5700

Thailand

Sartorius (Thailand) Co. Ltd.
129 Rama 9 Road,
Huaykwang
Bangkok 10310
Phone +66.2643.8361-6



www.sartorius.com