



## Water distiller "Aquasel"

DISTILLATION CAPACITY: 4 AND 6 LITRES/HOUR.

**Made from stainless steel and glass, easy disassembly for cleaning and storage.**

### COMMON FEATURES

Easy to use, suitable for continuous distilled water requirements. Boiler unit and heater element made of AISI 304 stainless steel, with lid and condenser made of borosilicate glass. The glassware pressure seal connection is an original Selecta design. Safety system cuts off power to the heater element if there is not enough water. Distilled water produced is pyrogen free.

MODELS	Part No.	Distillation capacity l/h	Water consumption l/h	Conductivity at 20 °C	Ø / Height (ext.) cm	Power W	Weight Kg
Aquasel 4	4903004	4	50 to 60	3 µs/cm	18 43	2400	2.5
Aquasel 6	4903006	6	120 to 130	3 µs/cm	23 68	4800	4

Supplied complete with silicon seals.



## Distillation still "L-3"

DISTILLATION CAPACITY: 3 LITRE PER HOUR.

### FEATURES

Made entirely of borosilicate glass, with protective case support, designed for functionality, that permits easy access to the quartz heater elements.

Functions: automatic with continuous water production. Produces distilled water of a high purity, free of pyrogens and metal ions.

Equipped with quartz heater elements and protection device using a safety thermostat that is activated in the case of low water pressure to the condenser or boiler unit. The unit automatically reactivates when the water pressure is restored.

Suitable for wall mounting.

### MODEL

Part No.	Distillation capacity l/h	Water consumption l/h	Conductivity at 20 °C	Height / Width / Depth (exterior) cm	Power W	Weight Kg
4903000	3	60	3 µs/cm	34.5 56 19	2200	4.5



## Water distiller, "AC-L4" and "AC-L8"

DISTILLATION CAPACITY: 3.5 AND 8 LITRES/HOUR.

### FEATURES

Tank and heating element made from stainless steel.

External case made from epoxy covered steel.

Easily dismantled for cleaning and service. All seals made from silicon.

In the case of over temperature or low water supply, a safety thermostat cuts power to the heater.

Water supply tube Ø 10 to 11 mm.

Distilled water tube connection Ø 12 mm.

Voltage: 230 V / 50/60 Hz

### CONTROL PANEL

Illuminated power switch.

Safety switch thermostat with rearm system.

MODELS	Part No.	Distillation capacity l/h	Water consumption l/h	Conductivity at 20 °C	Height / Width / Depth cm	Power W	Weight Kg
AC-L4	5903005	4	30	2,5 µs/cm	55 25 23	3000	12
AC-L8	5903008	8	70	2,5 µs/cm	61 26 26	6000	14



OPTIC  
ivymen<sup>®</sup>  
SYSTEM