

HETTICH PRODUCT PORTFOLIO



MANUAL CENTRIFUGE

- Independent of electricity
- Maintenance-free
- Two rotors to choose from (90° or 50°)
- Clamping device for easy table attachment



max. RPM	3,000 min ⁻¹
max. RCF	1,298
max. capacity	4 x 15 ml
weight (approx.)	0.9 kg
Cat. No.	1011

EBA 200 | 200 S

- IVDR-conform according to (EU) 2017/746
- Small centrifuge including 8-place angle rotor
- Noise level: 50 dB(A) in EBA 200
- Impuls key for short cycle mode



max. RPM	6,000 min ⁻¹ 8,000 min ⁻¹
max. RCF	3,461 6,153
max. capacity	8 x 15 ml
weight (approx.)	9 kg 11 kg
Cat. No.	1800 1802

EBA 270

- IVDR-conform according to (EU) 2017/746
- Small centrifuge including 6-place swing-out rotor
- Noise level: 51 dB(A)
- Impuls key for short cycle mode



max. RPM	4,000 min ⁻¹
max. RCF	2,254
max. capacity	6 x 15 ml
weight (approx.)	14 kg
Cat. No.	2300

EBA 280 | 280 S

- IVDR-conform according to (EU) 2017/746
- Small centrifuge with rotor quick-exchange system
- Choice of 6 rotors
- 9 program storage memories



max. RPM	6,000 min ⁻¹
max. RCF	4,146 5,071
max. capacity	6 x 50 ml
weight (approx.)	12 kg
Cat. No.	1101 1102

HAEMATOKRIT 200

- Hematocrit determination in 7 minutes
- IVD-conform according to 98/79/EC
- Compact, powerful centrifuge
- Noise Level: 56 dB(A) with rotor 2056



max. RPM	13,000 min ⁻¹
max. RCF	16,060
max. capacity	24 capillaries
weight (approx.)	10 kg
Cat. No.	1801

MIKRO 185

- Compact, powerful microliter centrifuge
- IVDR-conform according to (EU) 2017/746
- Choice of 4 rotors
- Noise Level: 54 dB(A) with rotor 1252-A



max. RPM	14,000 min ⁻¹
max. RCF	18,845
max. capacity	24 x 2 ml
weight (approx.)	11 kg
Cat. No.	1203

MIKRO 200 | 200 R

- IVDR-conform according to (EU) 2017/746
- Choice of 4 rotors
- 4 program storage memories
- Impuls key for short cycle mode



max. RPM	15,000 min ⁻¹
max. RCF	21,382
max. capacity	30 x 2 ml
weight (approx.)	11.5 kg 28 kg
Cat. No.	2400 2405

MIKRO 220 | 220 R

- IVDR-conform according to (EU) 2017/746
- Choice of 8 rotors
- 9 program storage memories
- Impuls key for short cycle mode



max. RPM	18,000 min ⁻¹
max. RCF	31,514
max. capacity	60 x 2 ml
weight (approx.)	21 kg 42 kg
Cat. No.	2200 2205

ROTOFIX 32 A

- IVDR-conform according to (EU) 2017/746
- Choice of 9 rotors
- Noise level: 52 dB(A) with rotor 1628
- Impuls key for short cycle mode



max. RPM	6,000 min ⁻¹
max. RCF	4,226
max. capacity	4 x 100 ml
weight (approx.)	23 kg
Cat. No.	1206

UNIVERSAL 320 | 320 R

- IVDR-conform according to (EU) 2017/746
- Choice of 18 rotors
- 9 individual acceleration and 10 deceleration stages
- Noise level: 48 dB(A) with rotor 1611



max. RPM	16,000 min ⁻¹
max. RCF	24,900
max. capacity	4 x 200 ml
weight (approx.)	31 kg 52 kg
Cat. No.	1401 1406

ROTINA 380 | 380 R

- IVDR-conform according to (EU) 2017/746
- Choice of 8 rotors
- 9 individual acceleration and 10 deceleration stages
- 98 program storage memories



max. RPM	15,000 min ⁻¹
max. RCF	24,400
max. capacity	4 x 290 ml
weight (approx.)	51 kg 81 kg
Cat. No.	1701 1706

ROTINA 420 | 420 R

- IVDR-conform according to (EU) 2017/746
- Choice of 5 rotors
- 9 individual acceleration and 10 deceleration stages
- 98 program storage memories



max. RPM	15,000 min ⁻¹
max. RCF	24,400
max. capacity	4 x 600 ml
weight (approx.)	75 kg 108 kg
Cat. No.	4701 4706

ROTANTA 460 | 460 R

- Medical device according to (EU) 2017/745
- Choice of 8 rotors
- 9 individual acceleration and 19 deceleration stages
- 98 program storage memories



max. RPM	15,000 min ⁻¹
max. RCF	24,400
max. capacity	4 x 750 ml
weight (approx.)	101 kg 141 kg
Cat. No.	5650 5660

ROTOFIX 46 | 46 H

- Robust and versatile industrial centrifuge
- ROTOFIX 46 H heatable up to +90 °C
- Choice of 4 rotors
- Noise Level: 38 dB(A) with rotor 4619



max. RPM	4,000 min ⁻¹ 2,000 min ⁻¹
max. RCF	3,095 984
max. capacity	4 x 290 ml 4 x 100 ml
weight (approx.)	60 kg
Cat. No.	4600 4600-50

ROTANTA 460 RC | 460 RF

- Medical device according to (EU) 2017/745
- Choice of 8 rotors
- 9 individual acceleration and 19 deceleration stages
- 98 program storage memories



max. RPM	15,000 min ⁻¹
max. RCF	24,400
max. capacity	4 x 750 ml
weight (approx.)	140 kg 164 kg
Cat. No.	5670 5675

ROTIXA 500 RS

- Medical device according to (EU) 2017/745
- Choice of 5 rotors
- 89 program storage memories
- 9 individual acceleration and 19 deceleration stages



max. RPM	11,500 min ⁻¹
max. RCF	18,038
max. capacity	4 x 1,000 ml
weight (approx.)	ca. 219 kg
Cat. No.	4950

ROTO SILENTA 630 RS

- Medical device according to (EU) 2017/745
- Choice of 3 rotors
- 89 program storage memories
- 9 individual acceleration and 19 deceleration stages



max. RPM	6,000 min ⁻¹
max. RCF	6,520
max. capacity	6 x 2,000 ml
weight (approx.)	ca. 355 kg
Cat. No.	5005

ROTOLAVIT II

- IVDR-conform according to (EU) 2017/746
- Automatic washing centrifuge for serological tests
- Choice of 2 rotors
- Simple operation due to intuitive touch screen



max. RPM	3,500 min ⁻¹
max. RCF	1,438
max. capacity	24 x 5 ml
weight (approx.)	24,5 kg
Cat. No.	1008-00

HETTCUBE 200 | 400 | 600

- Incubator with a temperature range of 1 K (°C) above ambient to + 65 °C
- Touchscreen with individual settings
- Constant and homogeneous temperature control through gentle air flow
- Maximum validated usable space on small footprint



dimensions (mm)	710 x 825 x 970 710 x 825 x 1425 710 x 825 x 1990
internal volume	150 l 310 l 520 l
validated volume	82 l 199 l 351 l
weight (approx.)	92 kg 117 kg 164 kg
Cat. No.	62000 64000 66000

HETTCUBE 200 R | 400 R | 600 R

- Refrigerated incubator with a temperature range of 0 °C to + 65 °C
- Touch screen with individual settings, weekly programming with holiday function and more security through various power failure scenarios
- Constant and homogeneous temperature control



dimensions (mm)	710 x 825 x 970 710 x 825 x 1425 710 x 825 x 1990
internal volume	150 l 310 l 520 l
validated volume	82 l 199 l 351 l
weight (approx.)	103 kg 128 kg 175 kg
Cat. No.	62005 64005 66005

Also available as general purpose model.

ZENTRIMIX 380 R

- Innovative dual centrifuge
- Efficient homogenizing, mixing and milling with only one device
- Can also be used as a cooled standard centrifuge



max. RPM	2,500 min ⁻¹
max. RCF	1,048
max. capacity	6 x 50 ml
weight (approx.)	81.5 kg
Cat. No.	3200

ACCESSORIES

- HettInfo II – Documentation system for blood banks
- Blood bank accessories
- Cyto accessories
- Incubator accessories
- Rolling cabinets



AUTOMATED CENTRIFUGES

- World market leader with over 25 years of experience in the field of automated centrifuges
- 4 models available in different sizes
- Extensive standard accessories



Developed and manufactured in Germany



Ø Product life of over 10 years



Spare parts and service for many years to come



Over 100 trained partners worldwide



All products are IVDR or MDR compliant