























۱.۸. مشخصات محصولات

جدول ۸-۱: مشخصات فنی پنل‌ها

| نوع لبه | استاندارد تولید | ضریب هدایت حرارتی λ W/(m.K) | چگالی حدافل (kg/m ³) | وزن تقریبی kg/m ² | ابعاد | | پنل | | | | | | | | | | |
|---|--------------------------------|--|---|---------------------------------|---------------|---|--|---|------|---|---------------------------|---|--|---|---|---|---|
| | | | | | ضخامت [mm] | طول و عرض [mm] | | | | | | | | | | | |
| <p>AK  طولی</p> <p>VK  عرضی</p> | EN520 ISIR14818 DIN18180 | ۰/۲۵ | ۷۷۰ | ۷/۳ | ۹/۵ |  | wRG (GKB) |  | | | | | | | | | |
| | | | ۷۸۰ | ۷/۸ | ۱۲/۵ | | MR (GKBI) |  | | | | | | | | | |
| | | | ۸۰۰ | ۱۲/۰۰ | ۱۵ | | FR (GKF) |  | | | | | | | | | |
| | | | ۸۱۰ | ۱۴/۶۰ | ۱۸ | | | | | | | | | | | | |
| | | | ۸۰۰ | ۱۰/۱۰ | ۱۲/۵ | | | | | | | | | | | | |
| | | | <p>HRAK  طولی</p> <p>VK  عرضی</p> | EN520 ISIR14818 DIN18180 | ۰/۲۷ | | ≥ 1000 | ۱۲/۸ | ۱۲/۵ |  | Diamant |  | | | | | |
| | | | | | | | ۷۶۰ | ۹/۳ | ۱۲/۵ | | |  | Cleaneo Random Plus 12/20/35R |  | | | |
| | | | | | | | ۷۶۰ | ۸/۴ | ۱۲/۵ | | | | | |  | Cleaneo Alternating Circular 12/20/35R |  |
| | | | | | | | ۷۶۰ | ۸/۳ | ۱۲/۵ | | | | | | | | |
| | | | <p>AK  طولی</p> <p>VK  عرضی</p> | EN14190 DIN18180 | ۰/۲۳ | | ۷۶۰ | ۸/۶ | ۱۲/۵ |  | Cleaneo Slotline B5 |  | | | | | |
| | | | | | | | <p>Essy Edge  طولی</p> <p>VK  عرضی</p> | ۰/۳۵ | ۷۵۰ | | | | ۱۱ | داخلي ۱۲/۵ |  | AQUAPANEL |  |
| | | | ۱۱۵۰ | ۱۶ | خارجي ۱۲/۵ | | | | | | | | | | | | |
| ۱۲۳۰ | ۱۰/۵ | اسکای لایت ۸ | | | | | | | | | | | | | | | |