
QuickSpecs

Overview

HPE ProLiant DL80 Generation9 (Gen9)

The HPE ProLiant DL80 Gen9 Server is designed with affordable storage, networking and processor scalability, and manageability in a 2U server for cost conscious service provider and SMBs. Apart from basic IT infrastructure workloads this server is ideal for running storage capacity intensive applications like cold storage, back-up due to compelling cost/GB that it offers.




Front View

- 1. Access Panel (Top Cover)
- 3. UID button/LED
- 5. NIC status LED
- 7. Serial label pull tab

- 2. USB 2.0 connector
- 4. Health LED
- 6. Power On/Standby button and system power LED
- 8. 8-bay LFF drive cage bay

Overview




Rear View

- 1. Slot 7 PCle3 x16 low-profile, standup
- 3. Slot 4 PCle3 x8 low-profile, riser (optional)
- 5. Slot 4 PCle3 x16 low-profile, standup
- 7. Slot 1 PCle3 x16 low-profile, standup
- 9. Slot 2 PCle3 x8 full-height half-length riser (optional)
- 11. Power supply status LED
- 13. Embedded 2x1GbE network adapter
- 15. Video connector

- 2. Slot 6 PCle3 x8 low-profile, standup
- 4. Slot 5 PCle3 x8 FlexibleLOM riser (optional)
- 6. Slot 3 PCle3 x8 low-profile, standup
- 8. Slot 1 PCle3 x16 full-height, full-length GPU riser (optional) or Slot 1 PCle3 x8 (8, 4, 1) full-height, half-length riser (optional)
- 10. Power supply power connection
- 12. Non-hot-plug power supply
- 14. UID LED
- 16. USB 3.0 connectors

Overview



Internal View

- 1. Fans shown with 6 Hot-swap fans
- 3. Internal USB 3.0 connector
- 5. PCle riser kits
- 7. PCIe 3.0 slots
- 9. 2 Processors, heatsink showing, with HPE Smart Socket Guide 10. HPE DDR4 SmartMemory DIMM slots. Shown fully
- 2. HPE Smart Storage Battery connector (optional)
- 4. Embedded HPE Smart Array B140i Controller
- 6. (Under) Non-Hot Plug HPE Power supply
- 8. MicroSD card slot
 - HPE DDR4 SmartMemory DIMM slots. Shown fully populated in 8 slots (4 per processor)

What's New

• Support for ClearOS – an easy to use OS with its own application marketplace

NOTE: For more information regarding Intel Xeon processors, please see the following http://www.intel.com/xeon.

Processor

One of the following depending on model

Model	CPU frequency	Cores	L3 Cache	Power	QPI	DDR4 Hz
E5-2660v3	2.6GHz	10	25MB	105W	9.6GT/s	2133
					-	
E5-2650v3	2.3GHz	10	25MB	105W	9.6GT/s	2133
E5-2650Lv3	1.8GHz	12	30MB	65W	9.6GT/s	2133
E5-2640v3	2.6GHz	8	20MB	90W	8.0GT/s	1866
E5-2630v3	2.4GHz	8	20MB	85W	8.0GT/s	1866
E5-2630Lv3	1.8GHz	8	20MB	55W	8.0GT/s	1866
E5-2623v3	3.0GHz	4	10MB	105W	8.0GT/s	1866
E5-2620v3	2.4GHz	6	15MB	85W	8.0GT/s	1866
E5-2609v3	1.9GHz	6	15MB	85W	6.4GT/s	1600
E5-2603v3	1.6GHz	6	15MB	85W	6.4GT/s	1600
E5-2660v4	2.0GHz	14	35MB	105W	9.6GT/s	2400
E5-2650v4	2.2GHz	12	30MB	105W	9.6GT/s	2400
E5-2650Lv4	1.7GHz	14	35MB	65W	9.6GT/s	2400
E5-2640v4	2.4GHz	10	25MB	90W	8.0GT/s	2133
E5-2630v4	2.2GHz	10	25MB	85W	8.0GT/s	2133
E5-2630Lv4	1.8GHz	10	25MB	55W	8.0GT/s	2133
E5-2623v4	2.6GHz	4	10MB	85W	8.0GT/s	2133
E5-2620v4	2.1GHz	8	20MB	85W	8.0GT/s	2133
E5-2609v4	1.7GHz	8	20MB	85W	6.4GT/s	1866
E5-2603v4	1.7GHz	6	15MB	85W	6.4GT/s	1866

Chipset

One of the following depending on model Intel® C610 Series Chipset

Intel® E5-2600v3 Processor Family Intel® E5-2600v4 Processor Family

NOTE: For more information regarding Intel® chipsets, please see the following URL:

http://www.intel.com/products/server/chipsets/

On System Management Chipset

HPE iLO (Firmware HPE iLO4 2.0 or later) 2GB NAND NOTE: Read and learn more in the iLO QuickSpecs.

Memory

One of the following depending on model

HPE SmartMemory and Standard Memory

DDR4 Registered (RDIMM) or Load Reduced (LRDIMM)

DIMM Slots Available (4 DIMM slots per processor, 4 channels per processor, 1 DIMMs per

channel)

Maximum Capacity

(LRDIMM)

256GB

(8 x 32GB LRDIMM @2400MHz)

Maximum Capacity

(RDIMM)

256GB (8 x 32GB LRDIMM @2400MHz)

Memory Protection Advanced ECC

Advanced ECC uses single device data correction to detect and correct single and

One of the	following
dependina	on model

all multibit error that occurs within a single DRAM chip.

Online Spare Memory online spare mode detects a rank that is degrading and switches

operation to the spare rank.

Mirroring mode Memory mirroring inter-socket stores a copy of memory with dynamic failover in

case of failure. Once a DIMM in a mirrored set is detected as failed, the mirror

failover uses its mirrored DIMM.

Expansion Slots							
Motherboard slots (Standard)	Expansion Slots #	Technology	Bus Width	Connector Width	Bus Number	Form Factor	Notes
	1	PCle 3.0	x16	x16		Low profile	CPU 1 slots
	3	PCIe 3.0	x8	x8		Low profile	CPU 1 slots
	4	PCIe 3.0	x16	x16		Low profile	CPU 1 slots
	6	PCle 3.0	x8	x8		Low profile	CPU 2 slots
	7	PCIe 3.0	x16	x16		Low profile	CPU 2 slots
	NOTE: Bus Wid	Ith data indicates	the number	of physical elect	rical lanes ru	nning to the cor	nector.
Primary Riser (Optional)	Expansion Slots #	Technology	Bus Width	Connector Width	Bus Number	Form Factor	Notes
	1	PCle 3.0	x8	x8		Full-height, half-length slot	CPU 1 slots
	2	PCle 3.0	x8	x8		Full-height, half-length slot	CPU 1 slots
Flexible LOM Riser (Optional)	Expansion Slots #	Technology	Bus Width	Connector Width	Bus Number	Form Factor	Notes
	4	PCIe 3.0	x8	x8		Low profile	CPU 1 slots
	5	PCle 3.0	x8	x8		Flexible LOM	CPU 1 slots
	NOTE: This rise	er is mandatory fo	r installing F	lexibleLOMs.			
GPU riser (Optional)	Expansion Slots #	Technology	Bus Width	Connector Width	Bus Number	Form Factor	Notes
	1	PCIe 3.0	x16	x16			Full-height, full-length slot
	NOTE: When po	opulating slots on	second rise	r, a second proce	essor must be	e installed.	
Storage Controller One of the following depending on model	supports RAID Base Models	s support for up to 0, 1 & 5. HPE H2 rovides support fo	o 10 SATA o	t Host Bus Adap	ransmission s		

Internal Storage Devices

One of the following depending on model

Optical Drive Via USB only
Hard Drives None ship standard

Hard Drive Bays 12 LFF drive bays total without Optical Bay

8 LFF drive bays total without Optical Bay

Redundant 4 fans

Standard Features

Maximum Internal Storage One of the following depending on model	Hot Plug LFF SAS Hot Plug LFF SATA Hot Plug LFF SATA SSD Non Hot Plug LFF SATA	CAPACITY 96.0TB 96.0TB 46.08TB 32TB	CONFIGURATION 12 x 8TB (with 12LFF drive cage) 12 x 8TB (with 12LFF drive cage) 12 x 3.84TB (with 12LFF drive cage) 8 x 4TB (with 8LFF drive cage)
Power Supply One of the following depending on model	HPE 550W FIO Power Sup HPE 900W AC 240V DC R Looking for high-efficiency	edundant Power	Supply at an entry-level price for your ProLiant Gen9 Essential

Looking for high-efficiency power solutions at an entry-level price for your ProLiant Gen9 Essential Server? HPE Entry-Level Power Supplies offer an optimized set of features with options for both redundant and non-redundant power configurations.

The HPE 550W FIO Power Supply offers Silver-certified 80 Plus power efficiency (up to 89%) with an optimized set of features for non-redundant power configurations.

The HPE 900W AC 240VDC Power Input Module with Power Backplane can be configured to support power redundancy in ProLiant servers that offer only a single power supply bay, providing additional protection against power loss. With an 80 Plus Gold power efficiency rating (up to 92%), this power option helps to reduce operating expenses while protecting against trapped power capacity in the data center. Hot-plug AC power input modules allow for better serviceability with fast and easy deployment and replacement.

System Fans		Non-redundant
One of the following	1P model	2 fans
depending on model	NOTE: Redundant and non-re	edundant fan counts varv with riser selection.

NOTE: Redundant and non-redundant fan counts vary with riser selection. 1P configurations either one of primary and secondary risers need 3 fans in non-redundant configuration.

	Non-redundant	Redundant
2P model	4 fans	5 fans

NOTE: Customers may separately purchase redundant fans with the 765516-B21 option kit. Additional fans (two) are also included in -B21 processor option kits when upgrading from one processor to two processors.

NOTE: All the riser option kits ship with necessary fan option kits.

Interfaces	Video	1 (Vaux Support)
	LOM Network Ports	2 x 1GbE ports

Micro SD Slot 1 Micro SD

NOTE: The SD slot is not a hot-pluggable device. Customers should not attempt to plug an SD card into the SD slot while the server is powered.

USB Up to 4 USB ports (standard):

Front: 1xUSB 2.0 std; (1xUSB2.0 optional upgrade with quick release ears)

Rear: 2xUSB 3.0 Internal: 1x USB 3.0

Operating Systems and Virtualization Software Support for ProLiant Servers **Microsoft Windows Server**

Red Hat Enterprise Linux (RHEL)

SUSE Linux Enterprise Server (SLES)

VMware ClearOS

NOTE: ClearOS allows you to build a fully functional server that is just right for you at no upfront cost. It is available via CTO preload, Intelligent Provisioning or via download. For more information on

ClearOS, please visit http://www.hpe.com/servers/clearos.

NOTE: For more information on Hewlett Packard Enterprise Certified and Supported ProLiant Servers for OS and Virtualization Software and latest listing of software drivers available for your server, please visit our Support Matrix at: http://www.hpe.com/info/ossupport and our driver download page.

Upgradeability

One of the following depending on model

Upgradeable to 2 processors (28 cores)

NOTE: Processor upgrade from E5-2600v3 to E5-2600v4 is supported. Please refer to DL80 Gen9 User Guide for more details.

Up to 8 DIMM slots

NOTE: To take advantage of DIMMs 5-8, a second processor must be installed.

FlexibleLOM slot for 1GbE or 10GbE or QDR/FDR InfiniBand Networking Options

NOTE: To take advantage of the additional 2 PCI slot upgrade, a second processor must be installed.

Redundant Power Supply

Redundant Fan

Industry Standard Compliance

ACPI 2.0b Compliant PCIe 3.0 Compliant

PXE Support WOL Support

Microsoft® Logo certifications

USB 3.0 Support ASHRAE A3

NOTE: Supports A3 extended ambient temperature.

NOTE: Refer to technical specifications section for more details.

Graphics

Integrated Matrox G200eH2 video standard

- 1280 x 1024 (32 bpp)
- 1920 x 1200 (16 bpp)

HPE Server UEFI/Legacy ROM

Unified Extensible Firmware Interface (UEFI) is an industry standard that provides better manageability and more secured configuration than the legacy ROM while interacting with your server at boot time. HPE ProLiant Gen9 platform defaults to UEFI and can be factory or field configured for Legacy BIOS Boot Mode.

NOTE: The UEFI System Utilities function is analogous to the HPE ROM-Based Setup Utility (RBSU) of legacy BIOS. For more information, please visit http://www.hpe.com/servers/uefi.

UEFI enables numerous new capabilities specific to HPE ProLiant servers such as:

- Secure Boot
- Operating system specific functionality
- Support for > 2.2 TB (using GPT) boot drives
- USB 3.0 Stack
- Embedded UEFI Shell
- Mass Configuration Deployment Tool using RESTful API for iLO 4
- PXE boot support for IPv6 networks
- Boot support for option cards that only support a UEFI option ROM

Network Stack configurations

NOTE: For UEFI Boot Mode, boot environment and OS image installations should be configured properly to support UEFI.

NOTE: UEFI FIO Setting (758959-B22) can be selected to configure the system in Legacy mode in the factory for your HPE ProLiant Gen9 Server.

Form Factor

One of the following depending on model 2U Rack form factor

All models ship with Easy Install rails (Cable management arm optional).

8 LFF Drive Bay Version:

3.44 (8.75cm) Height x 17.54" (44.55 cm) Width x 23.9" (60.70 cm) Length

12 LFF Drive Bay Version:

3.44 (8.75cm) Height x 17.54" (44.55 cm) Width x 23.9" (60.70 cm) Length

Embedded Management

HPE Integrated Lights-Out (HPE iLO)

Monitor your servers for ongoing management, service alerting, reporting and remote management with HPE iLO. Learn more at http://www.hpe.com/info/ilo.

UEFI Configure and boot your servers securely with industry standard Unified Extensible

Firmware Interface (UEFI). Learn more at http://www.hpe.com/servers/uefi.

RESTful API RESTful API for iLO 4 is Redfish 1.0 conformance for simplified server management

such as configuration and maintenance tasks based on modern industry

standards. Learn more at http://www.hpe.com/info/restfulapi.

Intelligent **Provisioning** Hassle free server and OS provisioning for 1 or few servers with Intelligent

Provisioning. Learn more at http://www.hpe.com/servers/intelligentprovisioning.

Embedded Remote Support The Hewlett Packard Enterprise embedded remote support, when used with Insight Online direct connect or HPE Insight Remote Support, allows HPE ProLiant servers to transmit hardware events directly to Hewlett Packard Enterprise or a Hewlett Packard Enterprise Authorized Partner for automated phone home support. Learn more at

http://www.hpe.com/info/insightonline/explore.

Server utilities

Smart Update

Optimize firmware and driver updates with Smart Update solutions including Smart Update Manager (SUM) and Service Pack for ProLiant (SPP). Learn more at

http://www.hpe.com/servers/smartupdatemanager

HPE Systems Insight Manager (HPE SIM)

HPE SIM allows you to monitor the health of your HPE ProLiant Servers and HPE Integrity Servers, and also provides you with basic support for non-HPE servers. HPE SIM also integrates with Smart Update Manager to provide quick and seamless

firmware updates. Learn more at http://www.hpe.com/servers/hpsim.

and Windows **PowerShell**

Scripting Tool Kit Provision 1 to many servers using your own scripts to discover and deploy them with Scripting Tool Kit (STK) for Windows and Linux or Scripting Tools for Windows PowerShell. Learn more at http://www.hpe.com/servers/proliant/stk or

http://www.hpe.com/servers/powershell.

Tool

RESTful Interface RESTful Interface tool is a scripting tool to provision using RESTful API for iLO 4 to discover and deploy servers at scale. Learn more at

http://www.hpe.com/info/resttool.

HPE iLO Mobile Application

Enables the ability to access, deploy, and manage your server anytime from anywhere from select smartphones and mobile devices. For additional information please visit:

http://www.hpe.com/info/ilo/mobileapp.

HPE Insight Online

HPE Insight Online, available at no additional cost as part of your Hewlett Packard Enterprise warranty or contractual support agreement with Hewlett Packard Enterprise, is a personalized dashboard for simplified tracking of IT operations and

support information from anywhere, anytime. Learn more at

http://www.hpe.com/info/insightonline/explore

Security

Power-on password
Serial interface control
Administrator's password

TPM 1.2 TPM 2.0

NOTE: TPM 2.0 works only in UEFI Mode.

UEFI

Warranty

This product is covered by a global limited warranty and supported by HPE Services and a worldwide network of HPE Authorized Channel Partners resellers. Hardware diagnostic support and repair is available for three years from date of purchase. Support for software and initial setup is available for 90 days from date of purchase. Enhancements to warranty services are available through HPE Pointnext operational services or customized service agreements. Hard drives have either a one year or three year warranty; refer to the specific hard drive QuickSpecs for details.

NOTE: Server Warranty includes 1-Year Parts, 1-Year Labor, 1-Year Onsite support with next business day response. Warranty repairs may be accomplished through the use of Customer Self Repair (CSR) parts. These parts fall into two categories: 1) Mandatory CSR parts are designed for easy replacement. A travel and labor charge will result when customers decline to replace a Mandatory CSR part; 2) Optional CSR parts are also designed for easy replacement but may involve added complexity. Customers may choose to have Hewlett Packard Enterprise replace Optional CSR parts at no charge. Additional information regarding worldwide limited warranty and technical support is available at:

http://h17007.www1.hpe.com/us/en/enterprise/servers/warranty/

Optional Features

Embedded Management

iLO Essentials

HPE iLO Essentials is the preferred license for small and medium business that offers full remote server management capabilities for small and medium business via the Integrated Remote Console (IRC), virtual media, and e-mail based alerts. Learn more about HPE iLO Essentials at http://www.hpe.com/servers/iLO/essentials.

iLO Scale-Out

HPE iLO Scale-Out is the preferred license built for web hosting, cloud service providers, and high performance computing data centers, managing massive scale out environments for the DL 100 and 10 series servers, not available for ML servers. This license offers sophisticated scripting tools that provides remote access through Text Console via SSH, Dynamic power capping, Email-based Alerting and proactive notifications. For more information, visit http://www.hpe.com/servers/iLO/scale-out.

iLO Advanced

HPE iLO Advanced licenses offer smart remote functionality without compromise, for all HPE ProLiant servers. The license includes the full integrated remote console, virtual keyboard, video, and mouse (KVM), multi-user collaboration, console record and replay, and GUI-based and scripted virtual media and virtual folders. You can also activate the enhanced security and power management functionality. Learn more about HPE iLO Advanced at http://www.hpe.com/servers/iloadvanced.

Server Management HPE Insight

HPE Insight Control

HPE Insight Control, lets you deploy, migrate, monitor, remote control, and optimize your IT infrastructure through a single, simple management console. For more information, see http://www.hpe.com/info/insightcontrol.

Rack and Power Infrastructure

HPE Rack and Power Infrastructure products and services create highly efficient and intelligent solutions for existing or new IT data centers. HPE Rack and Power infrastructure solutions – rack infrastructure, power protection and management, performance optimized data centers (PODs) – are the foundation you are looking for to help secure your long-term IT success. These products are designed to help you react to changes in the industry. They deliver efficient, easy-to-use capabilities to manage, monitor, deploy and provision infrastructure from entry to enterprise. As an industry leader, Hewlett Packard Enterprise is uniquely positioned to address the key concerns of power, cooling, cable management and system access. Learn more at **HPE Rack and Power Infrastructure**.

High Performance Clusters

HPE Cluster Platforms are specifically engineered, factory-integrated large-scale ProLiant clusters optimized for High Performance Computing, with a choice of servers, networks and software. Operating system options include specially priced offerings for Red Hat Enterprise Linux and SUSE Linux Enterprise Server, as well as Microsoft Windows HPEC Server. A Cluster Platform Configurator simplifies ordering. https://www.hpe.com/us/en/solutions/hpc-high-performance-computing/hpc-software.html.

HPC Interconnects

NOTE: High Performance Computing (HPC) interconnect technologies are available for this server under the HPE Cluster Platform product portfolio. These high-speed interconnects are fully supported by Hewlett Packard Enterprise when they are part of these configure to order clusters. Solutions can be defined with a lot of flexibility with the help of configuration tools. Please visit the following URL to configure HPEC Clusters with InfiniBand Interconnects: https://www.hpe.com/info/hpc/solutions.

Storage Software

Whether you need to solve a specific data protection, archiving, or storage command and control challenge, or deliver on strategic consolidation, compliance, or continuity initiatives, look no further than Hewlett Packard Enterprise storage software. Our storage software helps you reduce costs, simplify storage infrastructure, protect vital assets and respond faster to business opportunities. Storage software that gets the job done:

• Data Protection and Recovery Software

Optional Features

Whether you're a large enterprise or a smaller business, Hewlett Packard Enterprise data protection and recovery software will cost-effectively protect you against disaster and ensure business continuity.

• Data Archive and Migration Software

Hewlett Packard Enterprise storage software enables you to comply with data retention and retrieval requirements, improve application performance, and reduce costs by efficiently migrating infrequently accessed or less valuable data to lower cost storage.

• Storage Resource Management Software (SRM)

Hewlett Packard Enterprise storage resource management software reduces operational costs and provides the command and control foundation you need to efficiently manage and visualize your physical and virtual environments.

Data Replication Software

Hewlett Packard Enterprise offers array-based and host-based replication software for use in disaster recovery, testing, application development and reporting.

• Storage Device Management Software

Maximize your investment in Hewlett Packard Enterprise storage and networking with software that enables hardware-specific configuration, performance tuning and connectivity management.

HPE StoreVirtual VSA

With HPE StoreVirtual VSA you can use the power of virtualization to create a virtual array within your host server. Manage it as a single pool of shared storage capacity, and scale it to match your evolving needs. HPE ProLiant Gen9 servers include a 3-year limited license for HPE StoreVirtual VSA software with 1TB of capacity at no extra cost. Simply select to install HPE StoreVirtual VSA software during server setup within Intelligent Provisioning. More information, instructional videos, and free console management software are available at http://www.hpe.com/info/vsa1TB.

NOTE: For more information about Storage Software including QuickSpecs, please see:

https://www.hpe.com/us/en/storage/software-defined.html

ClearOS

HPE and ClearCenter will help you lower the cost of building on-premise solutions without sacrificing security and ease of use. HPE ProLiant servers with ClearOS give you a simple, secure, and affordable operating system with an intuitive web based graphical user interface that provides a cloud-like experience on- premise, and an Application Marketplace with over 100 apps and growing. Whether you're starting out or scaling, you decide what applications you need and pay as you grow.

One Config Simple (SCE)

SCE is a guided self-service tool to help sales and non-technical people provide customers with initial configurations in 3 to 5 minutes. You may then send the configuration on for configuration help, or use in your existing ordering processes. If you require "custom" rack configuration or configuration for products not available in SCE, please contact Hewlett Packard Enterprise Customer Business Center or an Authorized Partner for assistance. http://ocs.ext.hpe.com/.

Service and Support

HPE Support Services

HPE Technology Services delivers confidence, reduces risk and helps customers realize agility and stability. Connect to Hewlett Packard Enterprise to help prevent problems and solve issues faster. HPE Support Services enable you to choose the right service level, length of coverage and response time as you purchase your new server, giving you full entitlement to the support for need for your IT and business.

Connect your devices

Unlock all of the benefits of your technology investment by connecting your products to Hewlett Packard Enterprise. Achieve up to $77\%^1$ reduction in down time, near $100\%^2$ diagnostic accuracy and a single consolidated view of your environment. By connecting, you will receive 24x7monitoring, pre-failure alerts, automatic call logging, and automatic parts dispatch. HPE Proactive Care Service and HPE Datacenter Care Service customers will also benefit from proactive activities to help prevent issues and increase optimization. All of these benefits are already available to you with your server storage and networking products, securely connected to Hewlett Packard Enterprise support.

Recommended Support

Basic: HPE Foundation Care NBD, three-year Support Service

HPE Foundation Care Next Business Day connects you to Hewlett Packard Enterprise during business hours for assistance on resolving issues – This service features need based next business day hardware onsite response and software call back within two hours. In addition, Collaborative software support and provides troubleshooting assistance on industry leading software running on your HPE server. Simplify your support experience and make Hewlett Packard Enterprise your first call to help resolve hardware or software problems.

https://www.hpe.com/h20195/V2/GetDocument.aspx?docname=4AA4-8876ENW&cc=us&lc=en

Standard: HPE Foundation Care 24x7, three-year Support Service

HPE Foundation Care 24x7 gives you access to Hewlett Packard Enterprise 24 hours a day, seven days a week for assistance on resolving issues. This service includes need based Hardware onsite response within four hours. In addition, collaborative software support is included in this service that provides troubleshooting assistance on industry leading software running on your HPE server. Simplify your support experience and make Hewlett Packard Enterprise your first call to help resolve hardware or software problems.

https://www.hpe.com/h20195/V2/GetDocument.aspx?docname=4AA4-8876ENW&cc=us&lc=en

Optimized: HPE Proactive Care* with 24x7 coverage, three year Support Service

HPE Proactive Care gives customers an enhanced call experience. When your products are connected to Hewlett Packard Enterprise, Proactive Care helps prevent problems and maintains IT stability by utilizing personalized proactive reports with recommendations and advice. This service combines three years proactive reporting and advice with our 24x7 coverage, four hour hardware response time when there is a problem. This service also includes collaborative software support for Independent Software Vendors (ISVs), (Red Hat, VMWare, Microsoft, etc.) running on your HPE servers.

Parts and Materials

Hewlett Packard Enterprise will provide Hewlett Packard Enterprise-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product QuickSpecs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

The defective media retention service feature option applies only to Disk or eligible SSD/Flash Drives replaced by Hewlett Packard Enterprise due to malfunction.

Related Services

HPE Server Hardware Installation

Provides for the basic hardware installation of Hewlett Packard Enterprise branded servers, storage devices

Service and Support

and networking options to assist you in bringing your new hardware into operation in a timely and professional manner.

https://www.hpe.com/h20195/V2/GetPDF.aspx/5981-9356EN.pdf

HPE Installation and Startup Service

Provides for the installation and startup of Hewlett Packard Enterprise technology including BladeSystems, C-Class enclosure, HPE ProLiant c-Class and Integrity server blades, storage blades, SAN switch blades, HPE Virtual Connect modules (Ethernet and Fibre Channel), Ethernet network interconnects, and InfiniBand, as well as the installation of one supported operating system type (Windows® or Linux).

HPE Technology Services Support Credits

Offer flexible services and technical skills to meet your changing IT demands. With a menu of service that is tailored to suit your needs, you get additional resources and specialist skills to help you maintain peak performance of your IT. Offered as annual credits, you can plan your budgets while proactively responding to your dynamic business.

HPE Education Services

Keep your IT staff trained making sure they have the right skills to deliver on your business outcomes. Book on a class today and learn how to get the most from your technology investment.

http://www.hpe.com/ww/learn

HPE Support Center The HPE Support Center is a personalized online support portal with access to information, tools and experts to support Hewlett Packard Enterprise business products. Submit support cases online, chat with Hewlett Packard Enterprise experts, access support resources or collaborate with peers.

Learn more http://www.hpe.com/support/hpesc

The Hewlett Packard Enterprise Support Center Mobile App* allows you to resolve issues yourself or quickly connect to an agent for live support. Now, you can get access to personalized IT support anywhere, anytime.

HPE Insight Remote Support and HPE Support Center are available at no additional cost with a Hewlett Packard Enterprise warranty, HPE Support Service or Hewlett Packard Enterprise contractual support agreement.

*HPE Support Center Mobile App is subject to local availability.

For more information: http://www.hpe.com/services

Pre-configured Models

For the Standard Features shipped in the "Factory Integrated Models", please see the "Configuration Information - Factory Integrated Models" section.

- 1. Pre-configured models ship with the configurations below. Options can be selected from the Core or Additional options section of this QuickSpecs.
- 2. Hewlett Packard Enterprise does not allow factory integration of options into pre-configured models. Any additional options purchased will be shipped separately.
- 3. If you desire a custom configuration please see "Configuration Information Factory Integrated Models" section of this QuickSpecs.

NOTE: All Pre-configured Models come populated with some hard drive blanks installed. Should the customer need additional hard drive blanks, they can order more using HPE LFF Hard Drive Blank Kit (666986-B21).

NOTE: All pre-configured servers ship with a standard 6-foot IEC C-13/C-14 jumper cord (A0K02A). This jumper cord is also included with each standard AC power supply option kit. If a different power cord is required, please check the **ProLiant Power Cables** web page.

CAUTION: Hewlett Packard Enterprise recommends that a minimum of two people are required for all Rack Server installations. Please refer to your installation instructions for proper tools and number of people to use for any installation.

	Entry Models	Base Models		
[SKU Number]	830013-B21	833869-B21		
Model Name	HPE ProLiant DL80 Gen9 E5-2603v4 4GB-R B140i 4LFF Non-hot Plug 550W PS Entry Server	HPE ProLiant DL80 Gen9 E5-2609v4 8GB-R H240 8LFF 550W PS Base Server		
Processor	Intel® Xeon® E5-2603v4	Intel® Xeon® E5-2609v4		
Number of Processors	C)ne		
Memory	8GB (1x8GB Registered DIMMs STND, 2400 MHz) NOTE: Due to processor limitation, these DDR4 DIMMs will operate at 1833 MHz in this model.	8GB (1x8GB Registered DIMMs, 2400 MHz) NOTE: Due to processor limitation, these DDR4 DIMMs will operate at 1833 MHz in this model.		
Network Controller	HPE Embedded Dual Port 361i Adapter Network Interface			
Storage Controller	HPE Dynamic Smart Array B140i	HPE H240 Smart Host Bus Adapter		
Hard Drive	None ship standard			
Internal Storage	4 LFF HDD Bays (Non Hot Plug) 8 LFF HDD Bays			
Optical Drive Bay	Not Available			
Optical Drive	Optional via HPE Mobile USB DVDRW Drive (701498-B21)			
PCI-Express Slots	3 PCle 3.0 slots (Without risers)			
Power Supply	(1) HPE 550W	FIO Power Supply		
Fans	2 hot swap fans, non-redundant	4 hot plug fans, redundant		
Management	iLO Management (standard), Intelligent Provisioning (standard), iLO Essentials (optional), iLO Scale- out (optional only for DL), iLO Advanced (optional)			
Form Factor	Rack (2U), HPE Easy Install Rails			
Warranty	Server Warranty includes 1-Year Parts, 1-Year Labor, 1-Year Onsite support with next business day response			

Smart Buy Models

[SKU Number]	840616-S01
Model Name	HPE ProLiant DL80 Gen9 E5-2620v4 2.1GHz 8-core 8GB-R 8LFF 900W PS US Server/S-Buy
Processor	Intel® Xeon® E5-2620v4
Number of	One
Processors	
Memory	8GB (1x8GB Registered DIMMs, 2400 MHz)
	NOTE: Due to processor limitation, these DDR4 DIMMs will operate at 2133 MHz in this model.
Network Controller	HPE Embedded Dual Port 361i Adapter Network Interface
Storage Controller	HPE Smart Array P440/2G + Smart Storage Battery
Hard Drive	None ship standard
Internal Storage	8 LFF HDD Bays
Optical Drive Bay	Not Available
Optical Drive	Optional via HPE Mobile USB DVDRW Drive (701498-B21)
PCI-Express Slots	3 PCle 3.0 slots (Without risers)
Power Supply	(1) HPE 900W Redundant Capable Power Supply Kit
Fans	2 hot swap fans, non-redundant
Management	Standard: iLO Management
_	Optional: iLO Essentials, iLO Advanced, Insight Control
Form Factor	Rack (2U), HPE Easy Install Rails without Cable Management Arms
Warranty	1-Year Parts, 1-Year Labor, 1-Year Onsite support with next business day response

Configuration Information - Factory Integrated Models

This section lists some of the steps required to configure a Factory Integrated Model. To ensure only valid configurations are ordered, Hewlett Packard Enterprise recommends the use of an HPE approved configurator. Contact your local sales representative for information on configurable product offerings and requirements.

- 1. Factory Integrated Models must start with a CTO Server.
- 2. FIO indicates that this option is only available as a factory installable option.
- 3. All Factory Integrated Models will be populated with sufficient hard drive blanks based on the number of initial hard drives ordered with the server.
- 4. Some options may not be integrated at the factory. Contact your local sales representative for additional information.

Step 1: Base Configuration (choose one of the following configurable models)

CTO Server	HP ProLiant DL80 Gen9 Non-hot Plug 4LFF Configure-to-order Server	HP ProLiant DL80 Gen9 8LFF Configure-to-order Server	HP ProLiant DL80 Gen9 12LFF Configure-to-order Server	
SKU Number	778686-B21	778685-B21	787217-B21	
Processor	2 (optional) x HPE Smart Socket Guide			
DIMM Slots	8 DIMM slots for RDIMM, LRDIMM DDR4 Memory			
Storage Controller	HPE Dynamic Smart Array B140i			
PCle	5 Low Profile PCIe 3.0 slots			
Drive Cage	4LFF Non Hot Plug	8LFF Hot Plug	12LFF Hot Plug	
Network Controller	HPE Embedded Dual Port 361i Adapter Network Interface			
Fans	2 hot swap fans, non-redundant			
Management	iLO Management (standard), Intelligent Provisioning (standard)			
USB	1 front, 1 internal, 2 rear			

Step 2: Choose Required Options (only one of the following from each list unless otherwise noted)

HPE Processors E5-2600v4 series Processors

HPE DL80 Gen9 Intel® Xeon® E5-2660v4 (2.0GHz/14-core/35MB/105W) FIO Processor Kit	803079-L21
HPE DL80 Gen9 Intel® Xeon® E5-2650v4 (2.2GHz/12-core/30MB/105W) FIO Processor Kit	803081-L21
HPE DL80 Gen9 Intel® Xeon® E5-2640v4 (2.4GHz/10-core/25MB/90W) FIO Processor Kit	803083-L21
HPE DL80 Gen9 Intel® Xeon® E5-2630v4 (2.2GHz/10-core/25MB/85W) FIO Processor Kit	803085-L21
HPE DL80 Gen9 Intel® Xeon® E5-2620v4 (2.1GHz/8-core/20MB/85W) FIO Processor Kit	803087-L21
HPE DL80 Gen9 Intel® Xeon® E5-2623v4 (2.6GHz/4-core/10MB/85W) FIO Processor Kit	803089-L21
HPE DL80 Gen9 Intel® Xeon® E5-2609v4 (1.7GHz/8-core/20MB/85W) FIO Processor Kit	803091-L21
HPE DL80 Gen9 Intel® Xeon® E5-2603v4 (1.7GHz/6-core/15MB/85W) FIO Processor Kit	803093-L21
HPE DL80 Gen9 Intel® Xeon® E5-2630Lv4 (1.8GHz/10-core/25MB/55W) FIO Processor Kit	803097-L21
HPE DL80 Gen9 Intel® Xeon® E5-2650Lv4 (1.7GHz/14-core/35MB/65W) FIO Processor Kit	803095-L21

NOTE: If two processors are desired, select one xxxxxx-L21 and one corresponding xxxxxx-B21

NOTE: Up to two processors supported. Mixing different processor models is not supported.

NOTE: DDR speed is the maximum memory speed of the processor. Actual memory speed may depend on the quantity and type of DIMMs installed.

NOTE: When v4 Processor is selected, then only PC4-2400T Memory Kit can be selected.

NOTE: For the Intel® C600 Chipset E5-2600 Series, the letter preceding the model number indicates the Product Line (E3, E5, E7); 2600x v#, 2 = number of CPUs in a Node, 6 is socket/segment designation, <math>00 = Processor SKU, x = L for low power SKUs and v# (not yet designated) = version number.

Configuration Information - Factory Integrated Models

HPE Memory

NOTE: Select one or more memory from section below. A minimum of two memory kits are required if server is configured with two processors.

NOTE: LRDIMM and RDIMM are distinct memory technologies and cannot be mixed within a server. The majority of ProLiant Gen9 servers support LRDIMM and RDIMM.

NOTE: HPE memory from previous generation servers are not qualified or warranted with this HPE ProLiant Server. HPE SmartMemory is required to realize the memory performance improvements and enhanced functionality listed in this document for Gen9.

NOTE: If only one processor is installed, only half of the total DIMM slots are available. When populating with two processors all DIMM slots are available

NOTE: Kits described as LP include Low Power DIMMs. For more information on ProLiant Energy Efficient Features, see: http://www.hpe.com/go/proliant-energy-efficient

NOTE: Depending on the memory configuration and processor model, the memory speed may run at 2400MHz, 2133MHz, 1866MHz, 1600MHz or 1333MHz. Please see Memory Population Table or the Online Memory Configuration Tool at: http://www.hpe.com/go/ddr4config

Registered DIMMs (RDIMMs) for E5-2600v4 Series

HPE 8GB (1x8GB) Single Rank x8 DDR4-2400 CAS-17-17-17 Registered Memory Kit	805347-B21
HPE 16GB (1x16GB) Single Rank x4 DDR4-2400 CAS-17-17-17 Registered Memory Kit	805349-B21
HPE 16GB (1x8GB) Dual Rank x4 DDR4-2400 CAS-17-17-17 Registered Memory Kit	836220-B21
HPE 32GB (1x8GB) Dual Rank x4 DDR4-2400 CAS-17-17-17 Registered Memory Kit	805351-B21

Load Reduced DIMMs (LRDIMMs) for E5-2600v4 Series

HP 32GB (1x32GB) Dual Rank x4 DDR4-2400 CAS-17-17-17 Load Registered Memory Kit	805353-B21
HP 64GB (1x64GB) Quad Rank x4 DDR4-2400 CAS-17-17-17 Load Registered Memory Kit	805358-B21

HPE Standard Memory for E5-2600v4 Series

HPE 8GB (1x8GB) Single Rank x8 DDR4-2400 CAS-17-17-17 Registered Standard Memory 851353-B21 Kit

NOTE: HPE Standard Memory DIMMs have no SmartMemory features.

HPE Power Supplies

NOTE: Mixing of power supplies in the same server is not supported. All power supplies must be of the same input voltage, output rating, and efficiency rating. If non-matching power supplies are installed, you may receive an error message and/or experience operational issues with your server.

NOTE: Prior to selecting a power supply option, it is highly recommended that your review your server configuration in the HPE Power Advisor Tool to determine the right size power supply for your server configuration. The HPE Power Advisor is located at: http://www.hpe.com/go/hppoweradvisor.

HPE Entry-Level Power Supplies

HP 550W FIO Power Supply Kit	730941-B21
NOTE: The above power supply opton is 80Plus Silver-certified with an efficiency rating of	
up to 89%. Power specifications and technical content for all HP Server power supplies can	

be found at: http://www.hpe.com/go/proliant/powersupply

HPE 900W AC 240VDC Power Input FIO Module 828734-B21

NOTE: HP Server RPS FIO Backplane Kit (828735-B21) is required for this power supply.

NOTE: Up to two of these option kits can be installed in one system.

HPE 900W AC 240VDC Power Backplane FIO Kit 828735-B21

NOTE: One is required when one or two HPE 900W AC 240VDC Power Input FIO Modules (828734-B21) are ordered.

HPE Storage Controllers

NOTE: If not using the embedded B140i controller, must select one of the following HPE storage controllers below depending the CTO Server model selected in Step 1 above.

HPE Smart Array Controllers

HP Smart Array P440/4GB FBWC 12Gb 1-port Int FIO SAS Controller 761872-B21

NOTE: Includes the HP Smart Storage Battery.

HPE Riser Cards

Configuration Information - Factory Integrated Models

NOTE: May be selected if HP ProLiant DL80 Gen9 8LFF CTO Server (778685-B21) is selected in Step 1 above. HP Smart Array P840/4GB FBWC 12Gb 2-ports Int FIO SAS Controller 761874-B21 **NOTE:** Includes the HP Smart Storage Battery. NOTE: May be selected if HP ProLiant DL80 Gen9 12LFF CTO Server (787217-B21) is selected in Step 1 above. **HPE Smart Host Bus Adapters** HP H240 12Gb 2-ports Int FIO Smart Host Bus Adapter 761873-B21 NOTE: May be selected if HP ProLiant DL80 Gen9 8LFF CTO Server (778685-B21) or HP ProLiant DL80 Gen9 NHP 4LFF CTO Server (778686-B21) is selected in Step 1 above. **HPE Cable Options** HP DL60/80/120 Gen9 4LFF Cable FIO Kit 777331-B21 NOTE: If embedded B140i controller is used with the HP ProLiant DL80 Gen9 8LFF CTO Server (778685-B21) selected in Step 1 above, order two of 777331-B21 779619-B21 HP DL80 Gen9 LFF Smart Array P440/840 SAS Cable Kit NOTE: If HP ProLiant DL80 Gen9 8LFF CTO Server (778685-B21) selected in Step 1 above and HP Smart Array P440/4GB FBWC 12Gb 1-port Int FIO SAS Controller (761872-B21) is selected, order one 779619-B21 NOTE: If HP ProLiant DL80 Gen9 12LFF CTO Server (787217-B21) selected in Step 1 above and HP Smart Array P840/4GB FBWC 12Gb 2-ports Int FIO SAS Controller (761874-B21) is selected, order two 779619-B21 779622-B21 HP DL80 Gen9 Lff Smart Array H240 SAS Cable Kit NOTE: If HP ProLiant DL80 Gen9 8LFF CTO Server (778685-B21) selected in Step 1 above and HP H240 12Gb 2-ports Int FIO Smart Host Bus Adapter is selected, order one 779622-B21. HPE Security Kits NOTE: One Quick Release Ear FIO Kit or one Thumbscrew Ear FIO Kit is required HP DL80 Gen9 Quick Release Ear FIO Kit 778109-B21 HP DI 80 Gen9 Thumbscrew Far FIO Kit 787211-B21 NOTE: This part is not allowed with HP ProLiant DL80 Gen9 12LFF CTO Server (787217-B21) HP DL80 Gen9 FlexibleLOM Riser Kit 765514-B21 NOTE: This part is required if HP ProLiant DL80 Gen9 12LFF CTO Server (787217-B21) is selected in Step 1 above. Step 3: Choose Additional Factory Integratable Options (only one of the following from each list

unless otherwise noted)

BIOS Mode	HP Legacy FIO Mode Setting NOTE: If B140i is the only primary controller, then this option cannot be selected. NOTE: Selecting this option will change the default UEFI BIOS setting into Legacy BIOS setting.	758959-B22
Controller State	HP Mfg FIO Enable HBA Mode Setting NOTE: Can only be selected with H240 FIO Smart Host Bus Adapter. NOTE: If H240 is the primary controller then RAID is not allowed with this selection.	792962-B21
	HP AHCI-Enable FIO Setting NOTE: If B140i is the only primary controller then RAID is not allowed with this selection.	801845-B21
HPE Insight Software	HP Insight Control including 1yr 24x7 Support ProLiant ML/DL/BL-bundle Single Server FIO License	C6N36A
HPE Converged	HPE OneView with iLO Advanced	
Infrastructure	HP OneView for ProLiant DL Server incl 3yr 24x7 Supp FIO Bundle Physical 1 Svr Lic	E5Y43A

Page 18

Configuration Information - Factory Integrated Models

Management HPE OneView without iLO Advanced

Software HP OneView w/o iLO including 3yr 24x7 Support FIO 1 Server LTU P8B31A

Step 4: Choose Additional Options for Factory Integration from Core and Additional Options Sections below

CAUTION: Hewlett Packard Enterprise recommends that a minimum of two people are required for all Rack Server installations. Please refer to your installation instructions for proper tools and number of people to use for any installation.

788355-B21

HPE Unique

Core Options

NOTE: Some options may not be integrated at the factory. To ensure only valid configurations are ordered, Hewlett Packard Enterprise recommends the use of an HPE approved configurator. Contact your local sales representative for additional information.

HP DL80 Gen9 8LFF Non-hot Plug Enablement Kit

Options	HP DL80 Geny 8LFF Non-not Plug Enablement Kit	/88355-B21
Options	NOTE: Required to upgrade from 4LFF NHP to 8LFF NHP models.	7/5545 004
	HP DL80 Gen9 Full Height Half Length Riser Kit	765515-B21
	NOTE: Includes two FHHL PCIe 3.0 slots and one fan.	7/5540 504
	HP DL80 Gen9 GPU Enablement Kit	765518-B21
	NOTE: Includes 1 FHFL slot, one fan and power cable required to enable GPU support. Either one of FHHL or FlexibleLOM riser or GPU riser can be selected.	
	HP DL80 Gen9 FlexibleLOM Riser Kit	765514-B21
	NOTE: Includes one FlexibleLOM slot, one Low Profile slot and one fan.	/03314-DZI
HPE Processors	E5-2600v4 series Processors	
	HPE DL80 Gen9 Intel® Xeon® E5-2609v4 (1.7GHz/8-core/20MB/85W) Processor Kit	803091-B21
	HPE DL80 Gen9 Intel® Xeon® E5-2603v4 (1.7GHz/6-core/15MB/85W) Processor Kit	803093-B21
	HPE DL80 Gen9 Intel® Xeon® E5-2650Lv4 (1.7GHz/14-core/35MB/65W) Processor Kit	803095-B21
	HPE DL80 Gen9 Intel® Xeon® E5-2630Lv4 (1.8GHz/10-core/25MB/55W) Processor Kit	803097-B21
	HPE DL80 Gen9 Intel® Xeon® E5-2620v4 (2.1GHz/8-core/20MB/85W) Processor Kit	803087-B21
	HPE DL80 Gen9 Intel® Xeon® E5-2623v4 (2.6GHz/4-core/10MB/85W) Processor Kit	803089-B21
	HPE DL80 Gen9 Intel® Xeon® E5-2660v4 (2.0GHz/14-core/35MB/105W) Processor Kit	803079-B21
	HPE DL80 Gen9 Intel® Xeon® E5-2650v4 (2.2GHz/12-core/30MB/105W) Processor Kit	803081-B21
	HPE DL80 Gen9 Intel® Xeon® E5-2640v4 (2.4GHz/10-core/25MB/90W) Processor Kit	803083-B21
	HPE DL80 Gen9 Intel® Xeon® E5-2630v4 (2.2GHz/10-core/25MB/85W) Processor Kit	803085-B21
	E5-2600v3 series Processors	
	HP DL80 Gen9 Intel® Xeon® E5-2603v3 (1.6GHz/6-core/15MB/85W) Processor Kit	765521-B21
	HP DL80 Gen9 Intel® Xeon® E5-2609v3 (1.9GHz/6-core/15MB/85W) Processor Kit	765523-B21
	HP DL80 Gen9 Intel® Xeon® E5-2620v3 (2.4GHz/6-core/15MB/85W) Processor Kit	765525-B21
	HP DL80 Gen9 Intel® Xeon® E5-2630v3 (2.4GHz/8-core/20MB/85W) Processor Kit	765526-B21
	HP DL80 Gen9 Intel® Xeon® E5-2630Lv3 (1.8GHz/8-core/20MB/55W) Processor Kit	765530-B21
	HP DL80 Gen9 Intel® Xeon® E5-2640v3 (2.6GHz/8-core/20MB/90W) Processor Kit	765531-B21
	HP DL80 Gen9 Intel® Xeon® E5-2623v3 (3GHz/4-core/10MB/105W) Processor Kit	780100-B21
	HP DL80 Gen9 Intel® Xeon® E5-2650v3 (2.3GHz/10-core/25MB/105W) Processor Kit	765528-B21
	HP DL80 Gen9 Intel® Xeon® E5-2660v3 (2.6GHz/10-core/25MB/105W) Processor Kit	765529-B21
	HP DL80 Gen9 Intel® Xeon® E5-2650Lv3 (1.8GHz/12-core/30MB/65W) Processor Kit	765532-B21
	NOTE: Processor upgrade from E5-2600v3 to E5-2600v4 is supported. Please refer to DL80 Gen9 User Guide for more details.	
HPE Memory	Registered DIMMs (RDIMMs) for E5-2600v4 Series	
	HP 8GB (1x8GB) Single Rank x8 DDR4-2400 CAS-17-17-17 Registered Memory Kit	805347-B21
	HP 16GB (1x16GB) Single Rank x4 DDR4-2400 CAS-17-17-17 Registered Memory Kit	805349-B21
		Page 20

HP 32GB (1x32GB) Dual Rank x4 DDR4-2400 CAS-17-17 Registered Memory Kit NOTE: These DIMMs are supported only with E5-2600v4 processors. Registered DIMMs (RDIMMs) for E5-2600v3 Series)5351-B21
	26717-B21
	26718-B21
	59934-B21
· · · · · · · · · · · · · · · · · · ·	26719-B21
	28629-B21
NOTE: These DIMMs are supported only with E5-2600v3 processors.	10027 521
Load Reduced DIMMs (LRDIMMs) for E5-2600v4 Series	
)5353-B21
NOTE: These DIMMs are supported only with E5-2600v4 processors.	
Load Reduced DIMMs (LRDIMMs) for E5-2600v3 Series	
	26720-B21
HP 32GB (1x32GB) Quad Rank x4 DDR4-2133 CAS-15-15-15 Load Reduced Memory 72 Kit	26722-B21
NOTE: These DIMMs are supported only with E5-2600v3 processors.	
HPE Standard Memory for E5-2600v4 Series	
HPE 8GB (1x8GB) Single Rank x8 DDR4-2400 CAS-17-17-17 Registered Standard 85 Memory Kit	51353-B21
NOTE: These DIMMs are supported only with E5-2600v4 processors.	
HPE Standard Memory for E5-2600v3 Series	
HPE 4GB (1x4GB) Single Rank x8 DDR4-2133 CAS-15-15 Registered Standard 80 Memory Kit)3026-B21
HPE 8GB (1x8GB) Single Rank x4 DDR4-2133 CAS-15-15 Registered Standard 80 Memory Kit)3028-B21
NOTE: These DIMMs are supported only with E5-2600v3 processors.	
HPE Optical Drives HPE Mobile USB Non Leaded System DVD RW Drive 70)1498-B21
HPE Drives SATA Non-Hot Plug LFF (3.5-inch) Midline (MDL) Drives	
HPE 4TB SATA 6G Midline 7.2K LFF (3.5in) RW 1yr Wty HDD 80)1888-B21
HPE 2TB SATA 6G Midline 7.2K LFF (3.5in) RW 1yr Wty HDD)1884-B21
HPE 1TB SATA 6G Midline 7.2K LFF (3.5in) RW 1yr Wty HDD)1882-B21
SATA Hot Plug LFF (3.5-inch) Midline (MDL) Drives	
HPE 10TB SATA 6G Midline 7.2K LFF (3.5in) SC 1yr Wty Helium 512e Digitally Signed 85 Firmware HDD	57648-B21
HPE 8TB SATA 6G Midline 7.2K LFF (3.5in) SC 1yr Wty 512e Digitally Signed Firmware 81 HDD	L9203-B21
HPE 8TB SATA 6G Midline 7.2K LFF (3.5in) SC 1yr Wty Helium 512e Digitally Signed 86 Firmware HDD	51594-B21
HPE 6TB SATA 6G Midline 7.2K LFF (3.5in) SC 1yr Wty 512e HDD 86	51750-B21
HPE 6TB SATA 6G Midline 7.2K LFF (3.5in) SC 1yr Wty Digitally Signed Firmware HDD 84	+6510-B21
HPE 4TB SATA 6G Midline 7.2K LFF (3.5in) SC 1yr Wty Digitally Signed Firmware HDD 87	72491-B21 Page 21

6G SATA Hot Plug LFF (3.5-inch) Read Intensive Solid State Drives	
HPE 480GB SATA 6G Mixed Use LFF (3.5in) SCC 3yr Wty Digitally Signed Firmware SSD	875472-B21
SSD	
HPE 960GB SATA 6G Mixed Use LFF (3.5in) SCC 3yr Wty Digitally Signed Firmware	875476-B21
HPE 960GB SATA 6G Mixed Use LFF (3.5in) SCC 3yr Wty Digitally Signed Firmware SSD	877784-B21
HPE 1.6TB SATA 6G Mixed Use LFF (3.5in) SCC 3yr Wty SSD	804634-B21
HPE 1.92TB SATA 6G Mixed Use LFF (3.5in) SCC 3yr Wty Digitally Signed Firmware SSD	877790-B21
6G SATA Hot Plug LFF (3.5-inch) Mixed Use Solid State Drives	
HPE 400GB SATA 6G WI LFF SCC DS SSD	872357-B21
HPE 800GB SATA 6G WI LFF SCC DS SSD	872361-B21
HPE 1.6TB SATA 6G WI LFF SCC DS SSD	872365-B21
6G SATA Hot Plug LFF (3.5-inch) Write Intensive Solid State Drives	
SSD	
HPE 800GB SAS 12G Mixed Use LFF (3.5in) SCC 3yr Wty Digitally Signed Firmware	872378-B21
12G SAS Hot Plug LFF (3.5-inch) SC Mixed Use Solid State Drives	. 3 . 2 0 2 0 2 1
HPE 300GB SAS 12G Enterprise 15K LFF (3.5in) SCC 3yr Wty HDD	737374 B21 737261-B21
HPE 450GB SAS 12G Enterprise 15K LFF (3.5in) SCC 3yr Wty HDD	737394-B21
HPE 600GB SAS 12G Enterprise 15K LFF (3.5in) SC 3yr Wty HDD	765424-B21
SAS Hot Plug LFF (3.5-inch) Enterprise (ENT) Drives	0-00Z+ DZI
HPE 1TB SAS 12G Midline 7.2K LFF (3.5in) SC 1yr Wty Digitally Signed Firmware HDD	846524-B21
HPE 2TB SAS 12G Midline 7.2K LFF (3.5in) SC 1yr Wty HDD	818365-B21
HPE 2TB SAS 12G Midline 7.2K LFF (3.5in) SC 1yr Wty Digitally Signed Firmware HDD	872485-B21
HPE 3TB SAS 12G Midline 7.2K LFF (3.5in) SC 1yr Wty Digitally Signed Firmware HDD	846528-B21
HPE 4TB SAS 12G Midline 7.2K LFF (3.5in) SC 1yr Wty 512e HDD HPE 4TB SAS 12G Midline 7.2K LFF (3.5in) SC 1yr Wty HDD	818367-B21
HPE 4TB SAS 12G Midline 7.2K LFF (3.5in) SC 1yr Wty Digitally Signed Firmware HDD HPE 4TB SAS 12G Midline 7.2K LFF (3.5in) SC 1yr Wty 512e HDD	8/248/-B21 861756-B21
HPE 6TB SAS 12G Midline 7.2K LFF (3.5in) SC 1yr Wty Digitally Signed Firmware HDD HPE 4TB SAS 12G Midline 7.2K LFF (3.5in) SC 1yr Wty Digitally Signed Firmware HDD	846514-B21 872487-B21
HPE 6TB SAS 12G Midline 7.2K LFF (3.5in) SC 1yr Wty 512e HDD	861754-B21
HDD	04175/ 004
HPE 8TB SAS 12G Midline 7.2K LFF (3.5in) SC 1yr Wty 512e Digitally Signed Firmware	819201-B21
HPE 8TB SAS 12G Midline 7.2K LFF (3.5in) SC 1yr Wty Helium 512e Digitally Signed Firmware HDD	861590-B21
Firmware HDD	
HPE 10TB SAS 12G Midline 7.2K LFF (3.5in) SC 1yr Wty Helium 512e Digitally Signed	857644-B21
SAS Hot Plug LFF (3.5-inch) Midline (MDL) Drives	
HPE 1TB SATA 6G Midline 7.2K LFF (3.5in) SC 1yr Wty HDD	858594-B21
HPE 2TB SATA 6G Midline 7.2K LFF (3.5in) SC 1yr Wty HDD	858596-B21
6G SATA SC Hot Plug LFF 7.2K (3.5-inch) Standard Drives	
HPE 1TB SATA 6G Midline 7.2K LFF (3.5in) SC 1yr Wty HDD	861691-B21
HPE 2TB SATA 6G Midline 7.2K LFF (3.5in) SC 1yr Wty HDD	861676-B21
HPE 2TB SATA 6G Midline 7.2K LFF (3.5in) SC 1yr Wty Digitally Signed Firmware HDD	872489-B21
HPE 3TB SATA 6G Midline 7.2K LFF (3.5in) SC 1yr Wty Digitally Signed Firmware HDD	861693-B21
HPE 4TB SATA 6G Midline 7.2K LFF (3.5in) SC 1yr Wty HDD	861678-B21
HPE 4TB SATA 6G Midline 7.2K LFF (3.5in) SC 1yr Wty 512e HDD	861752-B21

	HPE 1.92TB SATA 6G Read Intensive LFF (3.5in) SCC 3yr Wty Digitally Signed Firmware SSD	877760-B21
	HPE 1.6TB SATA 6G Read Intensive LFF (3.5in) SCC 3yr Wty Digitally Signed Firmware SSD	869388-B21
	HPE 960GB SATA 6G Read Intensive LFF (3.5in) SCC 3yr Wty Digitally Signed Firmware SSD	877754-B21
	HPE 480GB SATA 6G Read Intensive LFF (3.5in) SCC 3yr Wty Digitally Signed Firmware SSD HPE 480GB SATA 6G Read Intensive LFF (3.5in) SCC 3yr Wty Digitally Signed Firmware SSD	877748-B21
		869380-B21
	6G SATA Hot Plug LFF (3.5-inch) MU-3 SCC SSD	
	HPE 960GB SATA 6G Mixed Use LFF (3.5in) SCC 3yr Wty Digitally Signed Firmware SSD	872350-B21
	HPE 480GB SATA 6G Mixed Use LFF (3.5in) SCC 3yr Wty Digitally Signed Firmware SSD	872346-B21
	Hard Drive Blank Kits	
	HPE Large Form Factor Hard Drive Blank Kit	666986-B21
	Hard Drive Kits	
	HP DL80 Gen9 8LFF Non-hot Plug Enablement Kit	788355-B21
	NOTE: Required to move from 4LFF NHPE model to 8 LFF NHPE model.	
HPE Networking	1 Gigabit Ethernet adapters	
	HPE Ethernet 1Gb 4-port 331T Adapter	647594-B21
	HPE Ethernet 1Gb 2-port 332T Adapter	615732-B21
	HPE Ethernet 1Gb 2-port 361T Adapter	652497-B21
	HPE Ethernet 1Gb 4-port 366T Adapter	811546-B21
	10 Gigabit Ethernet adapters	
	HPE Ethernet 10Gb 2-port 530SFP Adapter	652503-B21
	HPE Ethernet 10Gb 2-port 530T Adapter	656596-B21
	HPE Ethernet 10Gb 2-port 546SFP+ Adapter	779793-B21
	HPE Ethernet 10Gb 2-port 560SFP+ Adapter	665249-B21
	HPE Ethernet 10Gb 2-port 561T Adapter	716591-B21
	HPE Ethernet 10Gb 2-port 562SFP+ Adapter	727055-B21
	NOTE: A minimum of two Gigabytes (2 GB) of server memory is required per each adapter.	
	NOTE: Direct Attach Cable (DAC) for copper environments or fiber transceivers and cables for fiber-optic environments must be purchased separately. See cables/options below.	
	25 Gigabit Ethernet adapters	
	HPE Ethernet 4x25Gb 1-port 620QSFP28 Adapter	817762-B21
	FlexibleLOM Adapters	
	HPE Ethernet 1Gb 4-port 366FLR Adapter	665240-B21
	HPE FlexFabric 10Gb 2-port 533FLR-T Adapter	700759-B21
	HPE FlexFabric 10Gb 2-port 534FLR-SFP+ Adapter	700751-B21
	HPE FlexFabric 10Gb 4-port 536FLR-T Adapter	764302-B21
	HPE Ethernet 10Gb 2-port 546FLR-SFP+ Adapter	779799-B21
	HPE Ethernet 10Gb 2-port 560FLR-SFP+ Adapter	665243-B21

Core Options		
	HPE Ethernet 10Gb 2-port 561FLR-T Adapter HPE Ethernet 10Gb 2-port 562FLR-SFP+ Adapter NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://www.hpe.com/servers/ProLiantNICs .	700699-B21 727054-B21
HPE InfiniBand	HPE InfiniBand FDR/Ethernet 10Gb/40Gb 2-port 544+QSFP Adapter NOTE: Please see the HPE InfiniBand Options for HP ProLiant and Integrity Servers QuickSpecs for additional information.	764284-B21
HPE I/O Expansion Options	HP DL80 Gen9 FlexibleLOM Riser Kit NOTE: Includes one FlexibleLOM slot, one Low Profile slot and one fan.	765514-B21
	HP DL80 Gen9 Full Height Half Length Riser Kit NOTE: Includes two FLFH PCIe 3.0 slots and one fan.	765515-B21
	HP DL80 Gen9 GPU Enablement Kit NOTE: Includes 1 FHFL slot, one fan and power cable required to enable GPU support. Either one of FHHL or FlexibleLOM riser or GPU riser can be selected.	765518-B21
HPE Power Supplies	HPE Entry-Level Power Supplies	
	HPE 900W Standard AC 240VDC Power Input Module NOTE: This part number can only be bought standalone and is for field integration only.	775595-B21
	NOTE: RPS Backplane is mandatorily needed with this power input module. HPE 900W Standard AC 240VDC RPS Power Backplane	814835-B21
	NOTE: This part number can only be bought standalone and is for field integration only. NOTE: This RPS backplane is mandatorily needed with 900W RPS input module.	
	HPE 900W Standard AC 240VDC Redundant Power Supply Kit NOTE: This Redundant Power supply kit includes 2 power supply input module and 1	820792-B21
	backplane kit. NOTE: This part number is both factory installed option and field integrable option. NOTE: This Power supply supports both 100-240V AC and 240V DC.	
	NOTE: Supports Gold-level efficiency (92%) with a standard C14 inlet connector. No support for HPE Power Discovery Services. Only compatible with select HPE ProLiant Gen9 Essential servers.	
	NOTE: HPE 900W Gold (Redundant) AC 240VDC Power Input Module (775595-B21) must be used with Power Backplane (814835-B21).	
	NOTE: Each Redundant Power Supply Backplane can support up to two (2) power input modules. NOTE: Redundant AC Power Input Modules do not share power. Redundant AC Power Input Module #1 is the primary AC Power Input Module. Redundant AC Power Input Module #2 is the backup AC Power Input Module.	
	NOTE: Mixing of power supplies in the same server is not supported. All power supplies a same input voltage, output rating, and efficiency rating. If non-matching power supplies a	

same input voltage, output rating, and efficiency rating. If non-matching power supplies are installed, you may receive an error message and/or experience operational issues with your server.

NOTE: Prior to selecting a power supply option, it is highly recommended that you review your server

configuration. The HPE Power Advisor is located at: http://www.hpe.com/info/hppoweradvisor.

Options

NOTE: Includes two fans and is required to move from non-redundant to redundant fan configurations. Since each riser includes a fan as well, please refer to user-guide for exact fan requirements to enable fan redundancy.

NOTE: Some options may not be integrated at the factory. To ensure only valid configurations are ordered, Hewlett Packard Enterprise recommends the use of an HPE approved configurator. Contact your local sales representative for additional information.

HPE	Insight
Soft	ware

HPE Insight Control

HPE Insight Control including 1yr 24x7 Technical Support and Updates 1-server LTU

C6N27A

HPE Insight Control including 1yr 24x7 TSU E-LTU

C6N28ABE

HPE Insight Control Upgrade from iLO Advanced including 1yr 24x7 Support E-LTU

C6N38ABE

NOTE: Electronic and Flexible-Quantity licenses can be used to purchase multiple licenses with a single activation key.

NOTE: Customer will receive a license entitlement certificate. The license entitlement certificate must be redeemed online or via fax in order to obtain the license activation key(s). Includes one year of 24x7 HPE Software Technical Support and Update Service.

NOTE: Licenses ship without media. The HPE Insight Control Media Kit can be ordered separately, or can be downloaded at: https://www.hpe.com/info/insightmanagement.

NOTE: For additional license options please see the HPE Insight Control QuickSpecs.

HPE iLO Advanced including 1vr 24x7 Technical Support and Updates 1-server LTU

Embedded
Management

HPE iLO Advanced

The File of Navanice a melading Tyr 2 1x7 recimical support and opadies T server E10	312 103 BZ1
HPE iLO Advanced including 3yr 24x7 Tech Support and Updates 1-server LTU	BD505A
HPE iLO Advanced including 1yr 24x7 Technical Support and Updates E-LTU	E6U59ABE
HPE iLO Advanced including 3yr 24x7 Technical Support and Updates E-LTU	E6U64ABE
HPE iLO Essentials	
HPE iLO Essentials including 3yr 24x7 Technical Support and Updates E-LTU	E6U61ABE
HPE iLO Essentials including 3yr 24x7 Tech Support and Updates 1-server LTU	BD774A
HPE iLO Essentials including 1yr 24x7 Tech Support and Updates 1-server LTU	BD775A
HPE iLO Essentials including 1yr 24x7 Technical Support and Updates E-LTU	E6U62ABE
HPE iLO Scale-out	
HPE iLO Scale-Out 3yr 24x7 Tech Support and Updates Flexible Quantity LTU	BD776A
HPE iLO Scale-Out 1yr 24x7 Tech Support and Updates Flexible Quantity LTU	BD778A
HPE iLO Scale-Out including 3yr 24x7 Tech Support and Updates Flex Qty E-LTU	BD776AAE
HPE iLO Scale-Out including 3yr 24x7 Tech Support and Updates Tracking LTU	BD777A
HPE iLO Scale-Out including 1yr 24x7 Tech Support and Updates Flex Qty E-LTU	BD778AAE

HPE Converged Infrastructure Management Software

HPE OneView Advanced (with HPE iLO Advanced)

HPE OneView including 3yr 24x7 Support Physical 1-server LTU	E5Y34A
HPE OneView including 3yr 24x7 Support Flexible Quantity E-LTU	E5Y35AAE

HPE OneView Advanced (without HPE iLO Advanced)

,	
HPE OneView w/o iLO including 3yr 24x7 Support 1-server LTU	P8B24A
HPE OneView w/o iLO including 3yr 24x7 Support Flexible Quantity E-LTU	P8B26AAE
HPE OneView w/o iLO including 3yr 24x7 Support Track 1-server LTU	P8B25A
HPE OneView Physical Media Kit LTU	E5Y37A

NOTE: Full licenses of HPE OneView Advanced also provide the right-to-use HPE Insight Control without additional charge.

HPE iLO Scale-Out including 1yr 24x7 Tech Support and Updates Tracking LTU

NOTE: Server provisioning (via 'HPE Insight Control server provisioning') is licensed

BD779A

512485-B21

820834-B21

726825-B21

Additional Options

as part of HPE OneView Advanced and provides multi-server OS and driver provisioning. Media kit #BD883A can be ordered for a physical copy of this software (USB flash drive).

NOTE: Licenses ship without media. The HPE OneView Media Kit can be ordered separately, or can be downloaded at: http://www.hpe.com/info/hpeoneview. **NOTE:** Electronic and Flexible-Quantity licenses can be used to purchase multiple licenses with a single activation key.

HPE Security

HPE Trusted Platform Module 2.0 Kit	745823-B21
HPE Trusted Platform Module Option	488069-B21
HPE 2U Security Bezel Kit	666988-B21
NOTE: Quick Release Ear FIO kit (778109-B21) is required for installing security bezel.	

HPE Storage Controllers

SAS Controllers

HPE Smart Array Controllers

NOTE: Includes the HPE Smart Storage Battery.	
HPE Smart Array P840/4GB FBWC 12Gb 2-ports Int SAS Controller	726897-B21
HPE Smart Array P841/4GB FBWC 12Gb 4-ports Ext SAS Controller	726903-B21
HPE Smart Array P440/4GB FBWC 12Gb 1-port Int SAS Controller	726821-B21

HPE Smart Host Bus Adapters

HPE H240 12Gb 2-ports Int Smart Host Bus Adapter	726907-B21
HPE H241 12Gb 2-ports Ext Smart Host Bus Adapter	726911-B21

HPE Cable Options

HP DL80 Gen9 LFF Smart Array P440/P840 SAS Cable Kit 779619-B21

NOTE: One cable kit must be selected with P440 controller.

NOTE: Two of these cable kits must be selected with P840 controller.

HPE Smart Array P440/2GB FBWC 12Gb 1-port Int SAS Controller

HPE Smart Array P441/4GB FBWC 12Gb 2-ports Ext SAS Controller

HP DL80 Gen9 LFF Smart HBA H240 SAS Cable Kit 779622-B21

NOTE: Two cable Kits must be selected with H240.

NOTE: One of the above cables is required to be selected depending on the combination of server model and storage controller. Cable option kit descriptions include the right server model and storage controller names.

NOTE: NHP server model includes SATA cables required to connect drives to embedded B140i SATA controller.

Optional Software

HPE Smart Array SR SmartCache (Single Key/Single Server) LTU	D7S26A
HPE Smart Array SR SmartCache (Single Key/Multiple Servers) LTU	D7S27A
HPE Smart Array SR SmartCache (Single Key/Multiple Servers) E-LTU	D7S27AAE

NOTE: HPE SmartCache is supported when one of the supported Smart Array Controllers is installed in the server.

NOTE: HPE SmartCache comes standard (no licensing is required) if the HPE Smart Array P840 Controller is installed in the server.

HPE Smart Array SR Secure Encryption (Data at Rest Encryption/per Server Entitlement) E-LTU

Optional Upgrades

Q2F26AAE

HP 96W Smart Storage Battery with 145mm Cable for DL/ML/SL Servers

727258-B21

NOTE: This option is mandatorily required with HPE Smart Array controllers. One server can accommodate only 1 Smart Storage Battery that would suffice the requirement of all HPE Smart Array controllers.

HPE Tape Backup

NOTE: For the complete range of tape drives, autoloaders, libraries and media see:

http://www.hpe.com/storage/storeever. For hardware and software compatibility of HPE tape backup products see: http://www.hpe.com/storage/spock.

NOTE: For Internal drives to be connected to DL servers please make sure that you order rack mount kit as well.

Tape Drives

HPE StoreEver LTO-7 Ultrium 15000 External Tape Drive	BB874A
HPE StoreEver LTO-6 Ultrium 6250 External Tape Drive	EH970A
HPE StoreEver LTO-5 Ultrium 3000 SAS External Tape Drive	EH958B
HPE StoreEver LTO-4 Ultrium 1760 SAS External Tape Drive	EH920B
SAS Rack-Mount Tape Solutions	
HPE StoreEver MSL LTO-7 Ultrium 15000 SAS Drive Upgrade Kit	N7P37A
HPE StoreEver MSL LTO-7 Ultrium 15000 FC Drive Upgrade Kit	N7P36A
HPE StoreEver LTO-6 Ultrium 6250 Tape Drive in a 1U Rack Mount Kit	COL99A
HPE StoreEver MSL LTO-6 Ultrium 6250 SAS Drive Upgrade Kit	C0H27A
HPE StoreEver MSL LTO-6 Ultrium 6250 Fibre Channel Drive Upgrade Kit	C0H28A
HPE StoreEver LTO-5 Ultrium 3000 SAS Tape Drive in a 1U Rack Mount Kit	EJ014B
HPE StoreEver MSL LTO-5 Ultrium 3000 SAS Drive Upgrade Kit	BL540B
HPE StoreEver LTO-4 Ultrium 1760 SAS (1) in a 1U Rack Mount Kit	EH946C
HPE StoreEver 1U SAS Rack Mount Kit	AE459B
HPE DAT Autoloader	
HPE StoreEver 1/8 G2 LTO-7 Ultrium 15000 SAS Tape Autoloader	N7P35A
HPE StoreEver 1/8 G2 LTO-7 Ultrium 15000 FC Tape Autoloader	N7P34A
HPE StoreEver 1/8 G2 LTO-6 Ultrium 6250 Fibre Channel Tape Autoloader	COH19A
HPE StoreEver 1/8 G2 LTO-5 Ultrium 3000 SAS Tape Autoloader	BL536B
HPE MSL2024 Tape Library	
HPE StoreEver MSL2024 0-drive Tape Library	AK379A
HPE MSL4048 Tape Library	
HPE StoreEver MSL4048 0-drive Tape Library	AK381A
HPE StoreEver MSL6480	
HPE StoreEver MSL6480 Scaleable Expansion Module	QU626A
HPE StoreEver MSL6480 Scalable Base Module	QU625A

HPE Disk Backup

HPE RDX Removable Disk Backup System

TIFE ROX Removable bisk backup System	
HP RDX+ 1TB External Backup System	B7B69B
HP RDX+ 500GB External Backup System	B7B66B
HPE RDX 2TB USB3.0 External Disk Backup System	E7X53B
HPE RDX+ 3TB USB 3.0 External Disk Backup System	P9L72A
HPE RDX 3TB USB 3.0 Internal Disk Backup System	P9L71A
HPE RDX 4TB USB 3.0 External Disk Backup System	Q2R33A
HPE D3700 Enclosure	QW967A

	HPE D3600 Enclosure	QW968A
	HPE RDX+ External Docking System	C8S07B
	NOTE: For the complete range of RDX drives and media see:	
	https://www.hpe.com/us/en/product-catalog/storage/disk-based-backup- systems.html. For hardware and software compatibility of HPE disk backup products	
	see: http://www.hpe.com/storage/spock	
	NOTE: Please see the HPE RDX Removable Disk Backup System QuickSpecs for additional part numbers, technical specifications, and additional information.	
	HPE StoreOnce Backup systems	
	HPE StoreOnce 3100 8TB System	BB913A
	HPE StoreOnce 3540 24TB System	BB914A
	HPE StoreOnce 5100 48TB System	BB915A
	HPE StoreOnce 3520 12TB System	BB922A
HPE Storage	Emulex Fibre Channel HBAs	
Options	HPE 81E 8Gb 1-port PCIe Fibre Channel Host Bus Adapter	AJ762B
	HPE 82E 8Gb 2-port PCIe Fibre Channel Host Bus Adapter	AJ763B
	HPE StoreFabric SN1100E 16Gb Single Port Fibre Channel Host Bus Adapter	C8R38A
	HPE StoreFabric SN1100E 16Gb Dual Port Fibre Channel Host Bus Adapter	C8R39A
	QLogic Fibre Channel HBAs	
	HPE 81Q 8Gb 1-port PCIe Fibre Channel Host Bus Adapter	AK344A
	HPE 82Q 8Gb 2-port PCIe Fibre Channel Host Bus Adapter	AJ764A
	HPE StoreFabric SN1000Q 16GB 1-port PCIe Fibre Channel Host Bus Adapter	QW971A
	HPE StoreFabric SN1000Q 16GB 2-port PCIe Fibre Channel Host Bus Adapter	QW972A
	Converged Network Adapter	
	HPE StoreFabric CN1100R Dual Port Converged Network Adapter	QW990A
	HPE StoreFabric CN1100R 10GBASE-T Dual Port Converged Network Adapter	N3U52A
	HPE StoreFabric CN1200E 10Gb Converged Network Adapter	E7Y06A
	HPE StoreFabric CN1200E 10GBASE-T Dual Port Converged Network Adapter	N3U51A
HPE Data Center	HPE Advanced Series Racks	
Racks	HPE 48U 600mm x 1075mm Advanced Pallet Rack	H6J87A
	HPE 48U 600mm x 1075mm Advanced Shock Rack	H6J88A
	HPE 42U 600mm x 1075mm Advanced Pallet Rack	H6J65A
	HPE 42U 600mm x 1075mm Advanced Shock Rack	H6J66A
	HPE 42U 600mm x 1200mm Advanced Pallet Rack	H6J67A
	HPE 42U 600mm x 1200mm Advanced Shock Rack	H6J68A
	HPE 36U 600mm x 1075mm Advanced Pallet Rack	H6J77A
	HPE 36U 600mm x 1075mm Advanced Shock Rack	H6J78A
	HPE 22U 600mm x 1075mm Advanced Pallet Rack	H6J83A
	HPE 22U 600mm x 1075mm Advanced Shock Rack	H6J84A
	HPE 14U 600mm x 1075mm Advanced Shock Rack	H6J82A
	NOTE: Please see the HPE Advanced Series Racks QuickSpecs for information on	
	additional racks options and rack specifications.	

HPE Power
Distribution Units

(PDUs)

Additional Options

HPE Enterprise Series Racks	
HP 47U 600mm x 1075mm Enterprise Pallet Rack	BW911A
HP 47U 600mm x 1075mm Enterprise Shock Rack	BW911A
HP 47U 600mm x 1200mm Enterprise Pallet Rack	BW912A
HP 47U 600mm x 1200mm Enterprise Shock Rack	BW913A
HPE 42U 600mm x 1075mm Enterprise Pallet Rack	BW903A
HP 42U 600mm x 1075mm Enterprise Shock Rack	BW904A
HP 42U 600mm x 1200mm Enterprise Pallet Rack	BW907A
HP 42U 600mm x 1200mm Enterprise Shock Rack	BW908A
HP 42U 800mm x 1075mm Enterprise Pallet Rack	BW917A
HP 42U 800mm x 1075mm Enterprise Shock Rack	BW918A
NOTE: Please see the HPE Enterprise Series Racks QuickSpecs for information	31172071
on additional racks options and rack specifications.	
HPE Basic Power Distribution Units (PDU)	
HPE 800VA - 277V Input / 230V Output NA Rack Mount Transformer	H3X09A
NOTE: Please see the HPE Basic Power Distribution Units (PDU) QuickSpecs	
for information on additional options and product specifications.	
HPE Metered Power Distribution Units (PDU)	
HPE Metered 4.9kVA/L6-30P 24A/208V Outlets (12) C13/Horizontal NA/JP PDU	D9N44A
HPE Metered 3.6kVA/60320 C20 Detachable 16A/230V Outlets (16) C13/Vertical WW PDU	D9N45A
HPE Metered 4.9kVA/L6-30P 24A/208V Outlets (20) C13 (4) C19/Vertical NA/JP PDU	D9N47A
HPE Metered 3Ph 8.6kVA/L15-30P 24A/208V Outlets (18) C13 (3) C19/Vertical NA/JP PDU	D9N51A
HPE Metered 3Ph 8.6kVA/L21-30P 24A/120-208V Outlets (18) C13 (3) C19 (3) 5-20R/Vertical NA/JP PDU	D9N53A
HPE Metered 3Ph 14.4kVA/CS8365C 40A/208V Outlets (12) C13 (12) C19/Vertical NA/JP PDU	D9N58A
HPE Metered 3Ph 16.6kVA/60309 32A-30A 5-wire 24A/230V Outlets (30) C13 (3) C19/Vertical NA/JP PDU	D9N61A
HPE Metered 3Ph 16.6kVA/60309 32A-30A 5-wire 24A/230V Outlets (12) C13 (12) C19/Vertical NA/JP PDU	D9N62A
HPE Metered 3Ph 17.3kVA/60309 60A 4-wire 48A/208V Outlets (24) C13 (3) C19/Vertical NA/JP PDU	D9N54A
HPE Metered 3Ph 17.3kVA/60309 60A 4-wire 48A/208V Outlets (12) C13 (12) C19/Vertical NA/JP PDU	D9N59A
HPE Metered 3Ph 17.3kVA/60309 60A 4-wire 48A/208V Outlets (12) C13 (12) C19/Vertical NA/JP PDU	G9Z07A
HPE Metered 3Ph 19.9kVA/L22-30P 24A/277V Outlets (30) RF-203P-HP/Vertical NA PDU	D9N63A
HP Environmental Sensor for Remote Monitored and Managed PDUs	E2D53A
NOTE: Please see the HPE Metered Power Distribution Units (PDU) QuickSpecs	
for information on additional options and product specifications.	
HPE Intelligent Power Distribution Unit (PDU)	
HPE Intelligent Modular 4.9kVA/L6-30P 24A/208V Outlets (6) C19/Horizontal NA/JP	AF520A

DDII	
PDU HPE Intelligent Modular 8.3kVA/CS8265C 40A/208V Outlets (6) C19/Horizontal NA/JP	AF521A
PDU	AI JZIA
HPE Intelligent Modular 3Ph 8.6kVA/L15-30P 24A/208V Outlets (6) C19/Horizontal NA/JP PDU	AF522A
HPE Intelligent Modular 3Ph 17.3kVA/60309 60A 4-wire 48A/208V (6) C19/Horizontal NA/JP PDU	AF523A
HPE Intelligent Modular 3Ph 17.3kVA/60309 30A 5-wire 24A/240V (6) C19/Horizontal NA/JP PDU	AF901A
HPE Intelligent Modular 3Ph 17.3kVA/IEC 60309 60A 4-wire 48A/208V (12) C19/Horizontal NA/JP PDU	AF535A
HPE Intelligent Modular 4.9kVA/L6-30P 24A/208V Outlets (20) C13 (6) C19/Horizontal NA/JP PDU	AF531A
HPE Intelligent Modular 3Ph 8.6kVA/L15-30P 24A/208V Outlets (20) C13 (6) C19/Horizontal NA/JP PDU	AF532A
HPE Intelligent Modular 3Ph 14.4kVA/CS8365C 40A/208V Outlets (6) C19/Horizontal NA/JP PDU	AF533A
HPE 5xC13 Intelligent PDU Extension Bar G2 Kit	AF547A
HPE 5xC13 Outlets Power and UID LEDs Pair Standard Extension Bar	AF528A
NOTE: Please see the HPE Intelligent Power Distribution Unit (PDU) QuickSpecs for	
information on additional options and product specifications.	
HPE Metered and Switched Power Distribution Units (PDU)	1100/04
HPE Metered Switched 2.8kVA/L5-30P 24A/120V Outlets (24) 5-20R /Vertical NA/JP PDU	H8B48A
HPE Metered Switched 3.6kVA/60320 C20 Detachable 16A/230V Outlets (7) C13 (1) C19/Vertical WW PDU	H8B49A
HPE Metered Switched 4.9kVA/L6-30P 24A/208V Outlets (20) C13 (4) C19/Vertical NA/JP PDU	H8B50A
HPE Metered Switched 3Ph 8.6kVA/L15-30P 24A/208V Outlets (18) C13 (6) C19/Vertical NA/JP PDU	H8B52A
HPE Metered Switched 3Ph 8.6kVA/L21-30P 24A/208V Outlets (20)C13 (3)C19 (1)5-20R/Vertical NA/JP PDU	H8B53A
HPE Metered Switched 3Ph 14.4kVA/CS8365C 40A/208V Outlets (12) C13 (12) C19/Vertical NA/JP PDU	H8B55A
HPE Metered Switched 3Ph 17.3kVA/60309 4-wire 48A/208V Outlets (12) C13 (12) C19/Vertical NA/JP PDU	H8B56A
NOTE: Please see the HPE Metered and Switched Power Distribution Units (PDU)	
QuickSpecs for information on additional options and product specifications.	
NOTE: To learn more, please visit the HPE Uninterruptible Power Systems (UPS) web page.	
HPE Location Discovery Services	
HPE Location Discovery Services LCD8500 Kit	TL052A
NOTE: Please see the HPE Location Discovery Services QuickSpecs for information	

HPE Rack Mount Consoles, KVM Switches, and Keyboards

NOTE: Please see the <u>HPE Location Discovery Services QuickSpecs</u> for information on additional options and product specifications.

HPE Rack Mount Consoles

HP LCD8500 1U US Rackmount Console KitAF630AHP LCD8500 1U US TAA Rackmount Console KitAF645A

HPE Uninterruptible Power Systems

(UPS)

HP Ox1x8 63 KVM Console Switch HP Ox2x16 G3 KVM Console Switch HP TAA 0x2x16 G3 KVM Console Switch HP TAA 0x2x16 G3 KVM Console Switch HP TAA 0x2x16 G3 KVM Console Switch HP USB Remote Access Key for G3 KVM Console Switches HP KVM Console USB/Display Port Interface Adapter HP KVM Console USB B-pack Interface Adapter HP KVM Console USB Interface Adapter HP 0x2x16 KVM Server Console Switch G2 with Virtual Media CAC Software HP 0x2x32 KVM Server Console Switch G2 with Virtual Media CAC Software HP 0x2x32 KVM Server Console Switch G2 with Virtual Media CAC Software HP 1x4 USB/PS2 KVM Console Switch G2 with Virtual Media CAC Software HP 1x4 USB/PS2 KVM Console Switch G2 with Virtual Media CAC Software HP 1x4 USB/PS2 KVM IP Console Switch G2 with Virtual Media CAC Software HP 2x1Ex16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software HP USB Keyboard and Mouse HPE USB Keyboard and Mouse HPE USB Keyboard and Mouse HPE USB Keyboard Minuse Kit NOTE: Please see the HPE USB Keyboard Minuse Kit NOTE: Please see the HPE USB Keyboard Minuse Ruil Kit HP 2U Small Form Factor Easy Install Rail Kit HP 2U Small Form Factor Easy Install Rail Kit HP 2U Small Form Factor Easy Install Rail Kit HP 2U Small Form Factor Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit HP 2U Sam Ala Management Arm for
HP TAA 0x2x16 G3 KVM Console Switch HP USB Remote Access Key for G3 KVM Console Switches HP USB Remote Access Key for G3 KVM Console Switches HPE KVM Console USB/Display Port Interface Adapter AF6544 HPE KVM Console USB 8-pack Interface Adapter AF6586 HP KVM Console USB Interface Adapter HP 0x2x16 KVM Server Console Switch G2 with Virtual Media CAC Software HP 0x2x16 KVM Server Console Switch G2 with Virtual Media CAC Software HP 0x2x32 KVM Server Console Switch G2 with Virtual Media CAC Software HP KVM Console USB 2.0 Virtual Media CAC Interface Adapter HP 1x4 USB/PS2 KVM Console Switch HP 1x4 USB/PS2 KVM Console Switch HP 1x4 LXEx8 KVM IP Console Switch G2 with Virtual Media CAC Software HP 2x1Ex16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software HPE USB Keyboard and Mouse HPE USB Keyboard and Mouse HPE USB Keyboard Mouse Kit MOTE: Please see the HPE USB Keyboard and Mouse QuickSpecs for information on additional options and product specifications. Rail Kits HP 2U Cable Management Arm for Easy Install Rail Kit T33660-B23 HPE Other Options HPE Rack LED Light Kit BW9394 HPE Other Options HPE Rack LED Light Kit BW9394 HPE TirectFlow Three Phase UPS Power Unit (1U UPS) HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System G9Y754 HPE R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System AF4786 Input/Output Module Options for 1U UPS HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS IEC309 Input/Output Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output
HP USB Remote Access Key for G3 KVM Console Switches HPE KVM Console USB/Display Port Interface Adapter AF654/ HPE KVM Console USB 8-pack Interface Adapter AF655/ HP KVM Console USB Interface Adapter AF628/ HP KVM Console USB Interface Adapter AF628/ HP Ox2x16 KVM Server Console Switch G2 with Virtual Media CAC Software HP Ox2x32 KVM Server Console Switch G2 with Virtual Media CAC Software HP KVM Console USB 2.0 Virtual Media CAC Interface Adapter AF619/ HP XVM Console USB 2.0 Virtual Media CAC Interface Adapter AF629/ HP X44 USB/PS2 KVM Console Switch G2 with Virtual Media CAC Software HP KVM Console USB 2.0 Virtual Media CAC Interface Adapter AF629/ HP X44 USB/PS2 KVM Console Switch G2 with Virtual Media CAC Software AF620/ HP 2x1Ex16 KVM IP Console Switch G2 with Virtual Media CAC Software AF621/ HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software AF622/ NOTE: To learn more, please visit the HPE KVM Switches web page. HPE USB Keyboard and Mouse HPE USB Keyboard Amd Mouse HPE USB Keyboard Mouse Kit NOTE: Please see the HPE USB Keyboard and Mouse QuickSpecs for information on additional options and product specifications. Rail Kits HP 2U Small Form Factor Easy Install Rail Kit 733660-B23/ HPE Other Options HPE Rack LED Light Kit BW939/ HPE RAck LED Light Kit BW939/ HPE Riz000 DirectFlow - POD 1U Rackmount Uninterruptible Power System G9Y75/ Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output AF489/ Module HPE 30A 480 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output AF489/
HPE KVM Console USB/Display Port Interface Adapter HPE KVM Console USB 8-pack Interface Adapter HPE KVM Console USB Interface Adapter HP KVM Console USB Interface Adapter HP KVM Console USB Interface Adapter HP Ox2x16 KVM Server Console Switch G2 with Virtual Media CAC Software HP Ox2x32 KVM Server Console Switch G2 with Virtual Media CAC Software HP KVM Console USB 2.0 Virtual Media CAC Interface Adapter HP KVM Console USB 2.0 Virtual Media CAC Interface Adapter HP KVM Console USB 2.0 Virtual Media CAC Interface Adapter HP 1x4 USB/PS2 KVM Console Switch G2 with Virtual Media CAC Software HP 1x4 USB/PS2 KVM IP Console Switch G2 with Virtual Media CAC Software HP 2x1Ex16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software HPE USB Keyboard and Mouse HPE USB Keyboard and Mouse HPE USB Keyboard Amd Mouse HPE USB Keyboard Mouse Kit NOTE: Please see the HPE USB Keyboard and Mouse QuickSpecs for information on additional options and product specifications. Rail Kits HP 2U Small Form Factor Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit HPE Other Options HPE Rack LED Light Kit HPE Other Options HPE Rack LED Light Kit HPE DirectFlow Three Phase UPS Power Unit (1U UPS) HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System HPE R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System AF478/ Input/Output Module Options for 1U UPS HPE 30A 480 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output AF489/ Module HPE 30A 480 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output
HPE KVM Console USB 8-pack Interface Adapter HP KVM Console USB Interface Adapter HP Ox2x16 KVM Server Console Switch G2 with Virtual Media CAC Software HP 0x2x32 KVM Server Console Switch G2 with Virtual Media CAC Software HP KVM Console USB 2.0 Virtual Media CAC Interface Adapter HP KVM Console USB 2.0 Virtual Media CAC Interface Adapter HP 1x4 USB/PS2 KVM Console Switch HP 1x1 Ex8 KVM IP Console Switch G2 with Virtual Media CAC Software HP 2x1 Ex16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 2x1 Ex16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 2x1 Ex12x16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 2x1 Ex12x16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 4x1 Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software HP 5x1 Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software HP 5x1 Ex12x16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 5x1 Ex12x16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 5x1 Ex12x16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 5x1 Ex12x16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 5x1 Ex12x16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 5x1 Ex12x16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 5x1 Ex12x16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 5x1 Ex12x16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 5x1 Ex12x16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 5x1 Ex12x16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 5x1 Ex12x16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 5x1 Ex12x16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 5x1 Ex12x16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 5x1 Ex12x16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 5x1 Ex12x16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 5x1 Ex12x16 KVM IP Console Switch G2 with Virtual Media CAC Software
HP KVM Console USB Interface Adapter HP 0x2x16 KVM Server Console Switch G2 with Virtual Media CAC Software HP 0x2x32 KVM Server Console Switch G2 with Virtual Media CAC Software HP KVM Console USB 2.0 Virtual Media CAC Interface Adapter HP KVM Console USB 2.0 Virtual Media CAC Interface Adapter HP 1x4 USB/PS2 KVM Console Switch HP 1x1Ex8 KVM IP Console Switch G2 with Virtual Media CAC Software HP 2x1Ex16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 2x1Ex16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software HP USB Keyboard and Mouse HPE USB Keyboard and Mouse HPE USB Keyboard And Mouse HPE USB US Revboard/Mouse Kit NOTE: Please see the HPE USB Keyboard and Mouse QuickSpecs for information on additional options and product specifications. Rail Kits HP 2U Cable Management Arm for Easy Install Rail Kit T33660-B23 HPE Other Options HPE Rack LED Light Kit BW9394 HP KIT LCD 1.83m Latch Display Port Cable ### HPE DirectFlow Three Phase UPS ### Power Unit (1U UPS) HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System HPE R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS IEC309 Input/Output AF4894
HP 0x2x16 KVM Server Console Switch G2 with Virtual Media CAC Software HP 0x2x32 KVM Server Console Switch G2 with Virtual Media CAC Software HP KVM Console USB 2.0 Virtual Media CAC Interface Adapter HP 1x4 USB/PS2 KVM Console Switch HP 1x4 USB/PS2 KVM Console Switch HP 1x1Ex8 KVM IP Console Switch G2 with Virtual Media CAC Software HP 2x1Ex16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software HP USB Keyboard and Mouse HPE USB Keyboard And Mouse HPE USB Keyboard/Mouse Kit NOTE: Please see the HPE USB Keyboard and Mouse QuickSpecs for information on additional options and product specifications. Rail Kits HP 2U Small Form Factor Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit HPE Other Options HPE Rack LED Light Kit HPE Other Options HPE Rack LED Light Kit HPK It LCD 1.83m Latch Display Port Cable G7T294 HPE DirectFlow Three Phase UPS Power Unit (1U UPS) HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System G9Y754 Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R12000 DirectFlow UPS IEC309 Input/Output AF4896 HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output
HP 0x2x32 KVM Server Console Switch G2 with Virtual Media CAC Software HP KVM Console USB 2.0 Virtual Media CAC Interface Adapter HP 1x4 USB/PS2 KVM Console Switch HP 1x4 USB/PS2 KVM Console Switch HP 1x1Ex8 KVM IP Console Switch G2 with Virtual Media CAC Software HP 2x1Ex16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software HPE USB Keyboard and Mouse HPE USB Keyboard And Mouse HPE USB US Keyboard/Mouse Kit NOTE: Please see the HPE USB Keyboard and Mouse QuickSpecs for information on additional options and product specifications. Rail Kits HP 2U Small Form Factor Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit HPE Other Options HPE Rack LED Light Kit HPE Rack LED Light Kit HPE WSB USB WSB USB USB USB USB USB USB USB USB USB U
HP KVM Console USB 2.0 Virtual Media CAC Interface Adapter HP 1x4 USB/PS2 KVM Console Switch HP 1x1Ex8 KVM IP Console Switch G2 with Virtual Media CAC Software HP 2x1Ex16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software AF6224 NOTE: To learn more, please visit the HPE KVM Switches web page. HPE USB Keyboard and Mouse HPE USB US Keyboard/Mouse Kit NOTE: Please see the HPE USB Keyboard and Mouse QuickSpecs for information on additional options and product specifications. Rail Kits HP 2U Small Form Factor Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit HPE Other Options HPE Rack LED Light Kit BW9394 HPE MY LCD 1.83m Latch Display Port Cable HPE DirectFlow Three Phase UPS Power Unit (1U UPS) HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System AF4784 Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS L22-30 Input/Output AF4894 Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output AF4914
HP 1x4 USB/PS2 KVM Console Switch HP 1x1Ex8 KVM IP Console Switch G2 with Virtual Media CAC Software HP 2x1Ex16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software AF6224 NOTE: To learn more, please visit the HPE KVM Switches web page. HPE USB Keyboard and Mouse HPE USB US Keyboard/Mouse Kit NOTE: Please see the HPE USB Keyboard and Mouse QuickSpecs for information on additional options and product specifications. Rail Kits HP 2U Small Form Factor Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit HPE Other Options HPE Rack LED Light Kit HPE Other Options HPE Rack LED Light Kit HPE DirectFlow Three Phase UPS Power Unit (1U UPS) HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System G9Y754 HPE R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System AF4784 Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS L22-30 Input/Output AF4894 Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output
HP 1x1Ex8 KVM IP Console Switch G2 with Virtual Media CAC Software HP 2x1Ex16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software AF6224 NOTE: To learn more, please visit the HPE KVM Switches web page. HPE USB Keyboard and Mouse HPE USB US Keyboard/Mouse Kit NOTE: Please see the HPE USB Keyboard and Mouse QuickSpecs for information on additional options and product specifications. Rail Kits HP 2U Small Form Factor Easy Install Rail Kit TP 33660-B23 HPE Other Options HPE Rack LED Light Kit HPE Other Options HPE Rack LED Light Kit HPE DirectFlow Three Phase UPS Power Unit (1U UPS) HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System G9Y754 HPE R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System AF4784 Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output AF4894
HP 2x1Ex16 KVM IP Console Switch G2 with Virtual Media CAC Software HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software NOTE: To learn more, please visit the HPE KVM Switches web page. HPE USB Keyboard and Mouse HPE USB US Keyboard/Mouse Kit NOTE: Please see the HPE USB Keyboard and Mouse QuickSpecs for information on additional options and product specifications. Rail Kits HP 2U Small Form Factor Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit HPE Other Options HPE Rack LED Light Kit HPE Kit LCD 1.83m Latch Display Port Cable HPE DirectFlow Three Phase UPS Power Unit (1U UPS) HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System HPE R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output AF4894
HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software NOTE: To learn more, please visit the HPE KVM Switches web page. HPE USB Keyboard and Mouse HPE USB US Keyboard/Mouse Kit NOTE: Please see the HPE USB Keyboard and Mouse QuickSpecs for information on additional options and product specifications. Rail Kits HP 2U Small Form Factor Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit HPE Other Options HPE Rack LED Light Kit HP Kit LCD 1.83m Latch Display Port Cable HPE DirectFlow Three Phase UPS Power Unit (1U UPS) HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System HPE R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System AF4784 Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output AF4894
NOTE: To learn more, please visit the HPE KVM Switches web page. HPE USB Keyboard and Mouse HPE USB US Keyboard/Mouse Kit NOTE: Please see the HPE USB Keyboard and Mouse QuickSpecs for information on additional options and product specifications. Rail Kits HP 2U Small Form Factor Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit T733660-B23 HPE Other Options HPE Rack LED Light Kit BW9394 HP Kit LCD 1.83m Latch Display Port Cable G7T294 HPE DirectFlow Three Phase UPS Power Unit (1U UPS) HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System G9Y754 Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output AF4914
HPE USB Keyboard And Mouse HPE USB US Keyboard/Mouse Kit NOTE: Please see the HPE USB Keyboard and Mouse QuickSpecs for information on additional options and product specifications. Rail Kits HP 2U Small Form Factor Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit HPE Other Options HPE Rack LED Light Kit HP Kit LCD 1.83m Latch Display Port Cable HPE DirectFlow Three Phase UPS Power Unit (1U UPS) HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System G9Y754 Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output
HPE USB US Keyboard/Mouse Kit NOTE: Please see the HPE USB Keyboard and Mouse QuickSpecs for information on additional options and product specifications. Rail Kits HP 2U Small Form Factor Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit HPE Other Options HPE Rack LED Light Kit HP Kit LCD 1.83m Latch Display Port Cable HPE DirectFlow Three Phase UPS Power Unit (1U UPS) HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System HPE R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output AF4916
HPE USB US Keyboard/Mouse Kit NOTE: Please see the HPE USB Keyboard and Mouse QuickSpecs for information on additional options and product specifications. Rail Kits HP 2U Small Form Factor Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit HPE Other Options HPE Rack LED Light Kit HP Kit LCD 1.83m Latch Display Port Cable HPE DirectFlow Three Phase UPS Power Unit (1U UPS) HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System HPE R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output AF4916
NOTE: Please see the HPE USB Keyboard and Mouse QuickSpecs for information on additional options and product specifications. Rail Kits HP 2U Small Form Factor Easy Install Rail Kit 733660-B23 HPE Other Options HPE Other Options HPE Rack LED Light Kit BW9394 HP Kit LCD 1.83m Latch Display Port Cable G7T294 HPE DirectFlow Three Phase UPS Power Unit (1U UPS) HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System G9Y754 Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output AF4914
additional options and product specifications. Rail Kits HP 2U Small Form Factor Easy Install Rail Kit 733660-B23 HP 2U Cable Management Arm for Easy Install Rail Kit 733664-B23 HPE Other Options HPE Rack LED Light Kit BW939A HP Kit LCD 1.83m Latch Display Port Cable G7T29A HPE DirectFlow Three Phase UPS Power Unit (1U UPS) HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System G9Y75A HPE R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System AF478A Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R12000 DirectFlow UPS IEC309 Input/Output Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output AF491A
HP 2U Small Form Factor Easy Install Rail Kit HP 2U Cable Management Arm for Easy Install Rail Kit T33660-B21 HPE Other Options HPE Rack LED Light Kit HP Kit LCD 1.83m Latch Display Port Cable HPE DirectFlow Three Phase UPS Power Unit (1U UPS) HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System HPE R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output AF4914
HPE Other Options HPE Rack LED Light Kit HPE Nit LCD 1.83m Latch Display Port Cable HPE DirectFlow Three Phase UPS Power Unit (1U UPS) HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System HPE R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output AF4914
HPE Other Options HPE Rack LED Light Kit HP Kit LCD 1.83m Latch Display Port Cable HPE DirectFlow Three Phase UPS Power Unit (1U UPS) HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System HPE R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System AF478A Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output AF491A
HPE Rack LED Light Kit HP Kit LCD 1.83m Latch Display Port Cable HPE DirectFlow Three Phase UPS Power Unit (1U UPS) HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System HPE R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System HPE R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output AF491A
HP Kit LCD 1.83m Latch Display Port Cable HPE DirectFlow Three Phase UPS Power Unit (1U UPS) HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System HPE R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System AF478A Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output AF491A
Power Unit (1U UPS) HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System HPE R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System HPE R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System AF478A Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output AF491A
Power Unit (1U UPS) HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System HPE R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output AF491A
Power Unit (1U UPS) HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System HPE R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output AF491A
HPE R12000 DirectFlow - 1U Rackmount Uninterruptible Power System HPE R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output AF491A
HPE R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output AF491A
Input/Output Module Options for 1U UPS HPE 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output AF491A
HPE 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output AF491A
Module HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output AF491A
Module
HPE 30A 480 Volt Three Phase NA R12000 DirectFlow UPS IEC309 Input/Output AF492A Module
HPE 30A 400-415 Volt Three Phase NA R12000 DirectFlow UPS IEC309 Input/Output G9Y76A Module
Power Unit (2U UPS)
HPE R18000 DirectFlow - 2U Rackmount Uninterruptible Power System AF479A
THE NEODOO Direction 20 Nackinouth offinierraphible Fower System 74.777
Input/Output Module Options for 2U UPS

HPE USB and SD

Options


HPE 30A 400 Volt Three Phase NA R18000 DirectFlow UPS IEC309 Input/Output Module	D9Q02A
HPE 30A 400-415V Three Phase NA R18000 DirectFlow UPS 1:1 IEC309 Input/Output Module	AF484A
NOTE: All Input/Output Modules support dual output outlets except the AF484A.	
HPE DirectFlow UPS Management Card	AF493A
Battery Pack Options	
HPE DirectFlow UPS - 1U Rackmount Lithium-ion Battery Pack	AF480A
HPE DirectFlow UPS - 3U Rackmount VRLA Battery Pack	AF482A
HPE WW DirectFlow Secondary Battery Cable	AF497A
NOTE: Please see the <u>HPE DirectFlow Three Phase Uninterruptible Power System</u>	
QuickSpecs for information on additional options and product specifications.	
HPE Tower UPS	
HPE T750 G4 UPS Models	
HPE T750 G4 NA/JP Uninterruptible Power System	J2P85A
HPE T1000 G4 UPS Models	
HPE T1000 G4 NA/JP Uninterruptible Power System	J2P86A
HPE T1500 G4 UPS Models	
HPE T1500 G4 NA/JP Uninterruptible Power System	J2P87A
HPE Rack-mountable UPS	
HPE R/T2200 G4 UPS Models	
HPE R/T2200 G4 NA/JP Uninterruptible Power System	J2R00A
HPE R/T3000 G4 UPS Models	
HPE R/T3000 G4 Low Voltage NA/JP Uninterruptible Power System	J2R01A
HPE R/T3000 G4 High Voltage NA/JP Uninterruptible Power System	J2R02A
R1500 G4 Models	
HPE R1500 G4 NA Uninterruptible Power System	J2Q99A
R7000 Uninterruptible Power System (UPS)	
HPE R7000 4U 50A High Voltage NA/JP Uninterruptible Power System	AF462A
R5000 Uninterruptible Power System (UPS)	
HPE R5000 3U L630 High Voltage NA/JP Uninterruptible Power System	AF460A
NOTE: Please see the <u>HPE Line Interactive Single Phase UPS QuickSpecs</u> for	
information on additional options and product specifications.	
HPE UPS Options	
HPE R/T2200 G4 Extended Runtime Module	J2R09A
HPE R/T3000 G4 Extended Runtime Module	J2R10A
HPE 2U Rack/Tower UPS Shipping Kit	L4Q11A
NOTE: To learn more, please visit the HPE Uninterruptible Power Systems (UPS) web page.	
HPE Enterprise Mainstream Flash Media Kits for Memory Cards	
HPE 32GB microSD Mainstream Flash Media Kit	700139-B21
HPE 8GB microSD Enterprise Mainstream Flash Media Kit	726116-B21
HPE 8GB USB Enterprise Mainstream Flash Media Drive Key Kit	737953-B21
HPE Dual 8GB microSD Enterprise Midline USB Kit	741279-B21

HPE Support
Services

Installation & Start-up Services

•	
HPE Installation ML/DL Series 10 Service	J7WZ5E
HPE Startup ML/DL Series 10 Service	J7WZ7E
Foundation Care	
HPE 3 year Foundation Care Next business day DL80 Gen9 Service U	J7WG1E
HPE 3 year Foundation Care Next business day with DMR DL80 Gen9 Service U	J7WG2E
HPE 3 year Foundation Care Next business day with CDMR DL80 Gen9 Service U	J7WG3E
HPE 3 year Foundation Care 24x7 DL80 Gen9 Service U	J7WG4E
HPE 3 year Foundation Care 24x7 wDMR DL80 Gen9 Service	J7WG5E
HPE 3 year Foundation Care 24x7 wCDMR DL80 Gen9 Service	J7WG6E
Proactive Care	
HPE 3 year Proactive Care 24x7 DL80 Gen9 Service	J7WK1E
HPE 3 year Proactive Care 24x7 with DMR DL80 Gen9 Service	J7WK2E
HPE 3 year Proactive Care 24x7 with CDMR DL80 Gen9 Service	J7WK3E

Memory Population guidelines



General Memory Population Rules and Guidelines:

- . Install DIMMs only if the corresponding processor is installed.
- If only one processor is installed in a two processor system, only half of the DIMM slots are available.
- . To maximize performance, it is recommended to balance the total memory capacity between all installed processors and to load the channels similarly whenever possible.
- . When two processors are installed, balance the DIMMs across the two processors.
- . White DIMM slots denote the first slot to be populated in a channel.
- . Do not mix RDIMMs or LRDIMMs.
- . Quad rank RDIMMs are not supported in HPE ProLiant DL80 Gen9 servers.
- . DIMMs of different speeds may be mixed in any order; the server will select a common optimal speed.
- . The maximum memory speed is a function of the memory type, memory configuration, and processor model.
- . The maximum memory capacity is a function of the memory type and number of installed processors.
- To realize the performance memory capabilities listed in this document, HPE SmartMemory is required.

Intel Gen9 Supported Memory Bandwidth for HPE ProLiant Gen9 Intel® Xeon® E5-2600v4 Series Processor Family

Memory Bandwidth and Capacit	у				
[DIMM Type]		Load Reduced (LRDIMMs)			
HPE SKU P/N	805347-B21	805349-B21	836220-B21	805351-B21	805353-B21
DIMM Rank	Single Rank	Single Rank	Dual Rank	Dual Rank	Dual Rank
DIMM Capacity	8GB	16GB	16GB	32GB	32GB
Voltage	Std Voltage 1.2V	Std Voltage 1.2V	Std Voltage 1.2V	Std Voltage 1.2V	Std Voltage 1.2V
DRAM Depth [bit]	1G	2G	1G	2G	2G
DRAM Width [bit]	x8	x4	x4	x4	x4
DRAM Density	8Gb	8Gb	4Gb	8Gb	8Gb
CAS Latency	17-17-17	17-17-17	17-17-17	17-17-17	17-17-17
DIMM Native Speed (MT/s)	2400	2400	2400	2400	2400
SLOTS THAT CAN BE POPULAT	ΓED				
8 slot servers	8	8	8	8	8
MAXIMUM CAPACITY (GB)		ı	I		
	64	128	128	256	256
POPULATED DIMM SPEED (MT,	/s)	<u> </u>			
1 DIMM Per Channel	2400	2400	2400	2400	2400
2 DIMM Per Channel	n/a	n/a	n/a	n/a	n/a
3 DIMM Per Channel	n/a	n/a	n/a	n/a	n/a

NOTE: DL80 has 1 DIMM per channel and hence 2 DIMMs and 3 DIMMs per channel memory speeds are not applicable on DL80.

Intel Gen9 Supported Memory Bandwidth for HPE ProLiant Gen9 Intel® Xeon® E5-2600v3 Series Processor Family

Memory Bandwidth and Capacity							
[DIMM Type]		Registe	Load Reduce	d (LRDIMMs)			
HPE SKU P/N	726717-B21	726718-B21	759934-B21	726719-B21	728629-B21	726720-B21	726722-B21
DIMM Rank	Single Rank	Single Rank	Dual Rank	Dual Rank	Dual Rank	Dual Rank	Quad Rank
DIMM Capacity	4GB	8GB	8GB	16GB	32GB	16GB	32GB
Voltage	Std Voltage 1.2V						
DRAM Depth [bit]	512M	1G	512M	1G	1G	2G	2G

DRAM Width [bit]	x8	x4	x8	x4	x4	x4	x4
DRAM Density	4Gb	4Gb	4Gb	4Gb	4Gb	8Gb	8Gb
CAS Latency	15-15-15	15-15-15	15-15-15	15-15-15	15-15-15	15-15-15	15-15-15
DIMM Native Speed (MT/s)	2133	2133	2133	2133	2133	2133	2133
SLOTS THAT CAN BE POP	PULATED						
8 slot servers	8	8	8	8	8	8	8
MAXIMUM CAPACITY (GB)					•	
	32	64	64	128	256	128	256
POPULATED DIMM SPEED	(MT/s)					•	
1 DIMM Per Channel	2133	2133	2133	2133	2133	2133	2133
2 DIMM Per Channel	n/a						
3 DIMM Per Channel	n/a						

NOTE: DL80 has 1 DIMM per channel and hence 2 DIMMs and 3 DIMMs per channel memory speeds are not applicable on DL80.

DIMM slot and configuration diagram

DIMM slot and configuration diagrams

Basic memory slot & population diagram

- Population order; start with "A" first, "B" second, "C" third, etc.
- When one processor is installed, install DIMMs in sequential alphabetic order: A, B, C, D, E, F.
- When two processors are installed, install DIMMs in sequential alphabetic order: CPU1-A, CPU2-A,CPU1-B,CPU2-B,CPU1-C, CP2-C.

CPU #1 IS PROCESSOR ON LEFT - LOOKING FROM FRONT OF SERVER

		CPU 1		CPU 2	
	Slot #	Population order	Slot #	Population order	
Chnl 1	1	A1	1	A1	
		CPU 1		CPU 2	
	Slot #	Population order	Slot #	Population order	
Chnl 2	2	B2	2	B2	
		CPU 1		CPU 2	
	Slot #	Population order	Slot #	Population order	
Chnl 4	3	D3	3	D3	
		CPU 1		CPU 2	
	Slot #	Population order	Slot #	Population order	
Chnl 3	4	C4	4	C4	

Memory Speed by Processor Model

Processor Models	Supported Memory Speeds
E5-2603v3, E5-2609v3	1600MT/s
E5-2620v3, E5-2630v3, E5-2630Lv3, E5-2640v3, E5-2623v3	1866MT/s
E5-2650v3, E5-2660v3, E5-2650Lv3	2133MT/s
E5-2609v4, E5-2603v4	1866MT/s
E5-2630Lv4, E5-2620v4, E5-2623v4, E5-2640v4, E5-2630v4	2133MT/s
E5-2650Lv4, E5-2660v4, E5-2650v4	2400MT/s


Standard and Maximum Memory Capacity (Pre-configured Models)

Pre-Configured Models	Standard Memory	Optional Memory	Standard Memory Replaced with Optional Memory
E5-2609v4, E5-2609v3, E5-2603v4	8GB (1x8GB)	232GB (7x32GB, 1x8GB)	256GB (8x32GB)
E5-2603v3	4GB (1x4GB)	228GB (7x32GB, 1x4GB)	256GB (8x32GB)

DDR4 memory options part number decoder


NOTE: Capacity references are rounded to the common gigabyte (GB) values:

- 2GB = 2,048MB
- 4GB = 4,096MB
- 8GB = 8,192MB
- 16GB = 16,384MB
- 32GB = 32,768MB
- 64GB = 65,536MB




Storage

4-bay LFF non-hot-plug drive model




1-4 4 x LFF SATA Non-Hot Pluggable Hard Drive Bays

8-bay LFF non-hot plug drive model




1-8 8 x LFF SATA Non- Hot Pluggable Hard Drive Bays

8-bay LFF hot-plug drive model



1-8 8 x LFF SATA/SAS/SDD Hot Pluggable Hard Drive Bays

12-bay LFF hot-plug drive model



1-12 12 x LFF SATA/SAS/SDD Hot Pluggable Hard drive bays

System Unit	Dimensions (with bezel)	3.45 x 18.98 x 24.97 in	(8.75 x 44.55 x 60.7 cm)		
	Weight	Maximum:	47.6 lb (21.59 kg)		
	(approximate)	Minimum:	36.58 lb (16.59 kg)		
	Input Requirements	Rated Line Voltage	100 to 240 VAC		
	(for Standard 460W PSU, see	Rated Input Current	For 550W Power Supply:		
	power specifications tables for detail on 460W, 750W and		6.7 A (at 100 VAC)		
	1200W power supplies)		3.3 A (at 100 VAC)		
		Rated Input Frequency	47 to 63 Hz		
		Rated Input Power	For 550 W Power Supply:		
			< 670 W (at 100 VAC)		
			< 660 W (at 200 VAC)		
	BTU Rating	Maximum	For 550 W Power Supply:		
Power			2201 BTU/hr (at 100 VAC)		
			2153 BTU/hr (at 200 VAC)		
	Power Specifications	To review typical system power ratings use the Power Advisor which is available via the online tool located at: http://www.hpe.com/info/hppoweradvisor - Click on the system of			
			Gen9- Follow the instructions of the next screens.		
	Power Supply Output	Rated Steady-State	For 550 W Power Supply:		
	, .	Power	550 W (at 100 VAC)		
			550 W (at 200 VAC)		
		Maximum Peak Power	For 550 W Power Supply:		
			550 W (at 100 VAC)		
			550 W (at 200 VAC)		
	System Inlet Temperature	Standard Operating Support	10° to 35°C (50° to 95°F) at sea level with an altitude derating of 1.0°C per every 305 m (1.8°F per every 1000 ft) above sea level to a maximum of 3050 m (10,000 ft), no direct sustained sunlight. Maximum rate of change is 20°C/hr (36°F/hr). The upper limit and rate of change may be limited by the type and number of options installed. System performance during standard operating support may be reduced if operating with a fan fault or above 30°C (86°F).		
		Extended Ambient Operating Support	For approved hardware configurations, the supported system inlet range is extended to be:		

supported system inlet range is extended to be: 5° to 10°C (41° to 50°F) and 35° to 40°C (95° to 104°F) at sea level with an altitude derating of 1.0°C per every 175 m (1.8°F per every 574 ft) above 900 m (2953 ft) to a maximum of 3050 m

(10,000 ft). The approved hardware

configurations for this system are listed at the

URL:

http://www.hpe.com/servers/ashrae.

System performance may be reduced if operating

in the extended ambient operating range or with

a fan fault.

NOTE: Supports A3 extended ambient.

Non-operating -30° to 60°C (-22° to 140°F). Maximum rate of

change is 20°C/hr (36°F/hr).

Relative Humidity Operating Minimum to be the higher (more moisture) of -

12°C (10.4°F) dew point or 8% relative humidity. Maximum to be the lower (less moisture) of 24°C

(75.2°F) dew point or 90% relative humidity.

Non-operating 5% to 95% relative humidity (Rh), 38.7°C

(101.7°F) maximum wet bulb temperature, non-

condensing.

Altitude Operating 3048 m (10,000 ft). This value may be limited by

the type and number of options installed.

Maximum allowable altitude change rate is 457

m/min (1500 ft/min).

Non-operating 9144 m (30,000 ft). Maximum allowable altitude

change rate is 457.2 m/min (1500 ft/min).

Acoustic Noise Listed are the declared A-Weighted sound power levels (LWAd) and

declared average bystander position A-Weighted sound pressure levels (LpAm) when the product is operating in a 23°C ambient environment. Noise emissions were measured in accordance with ISO 7779 (ECMA 74)

and declared in accordance with ISO 9296 (ECMA 109).

Idle

LWAd Entry: 4.8 B

Base: 4.7 B

LpAm Entry: 34 dBA

Base: 33 dBA

Operating

LWAd Entry: 4.9 B

Base: 4.9 B

LpAm Entry: 34 dBA

Base: 36 dBA

NOTE: The listed sound levels apply to standard shipping configurations.

Additional options may result in increased sound levels.

Emissions Classification

(non-condensing)

(EMC)

FCC Rating Class A

Normative Standards CISPR 22; EN55022; EN55024; FCC CFR 47, Pt

15; ICES-003; CNS14336-1; CNS13438; GB4943; GB9254; EN 61000-3-2; EN 61000-3-

3; EN 60950-1; IEC 60950-1

NOTE: Product conformance to cited product specifications is based on sample (type) testing, evaluation, or assessment. This product or family of products is eligible to bear the appropriate compliance logos and statements.

NOTE: The listed sound levels apply to standard shipping configurations. Additional options may result in increased sound levels.

Array B140i Controller

PCI link rate 4Gb/s Storage protocol support SATA

SAS/SATA peak data

transfer rate

Number of SAS/SATA links 10 links

6Gb/s

SAS/SATA connectivity

2x4 connectors; 2x1 connectors

Expander support

Drives supported (max)

Up to 10 Internal Drives

RAID support

0, 1, 10, 5 SATA

Software management

HPE SSA, SMH, SIM

Warranty

Server warranty

HPE Secure Encryption

license

Not Supported

HPE SmartCache License

HPE Smart Storage

Administrator

Not Supported

Supported

HPE Embedded Dual Network Interface Port 361i Adapter

Compatibility

10Base-T/100Base-TX/1000Base-TX

IEEE 802.3 10Base-T

IEEE 802.3ab 1000Base-T IFFF 802 3u 100Base-TX IEEE 1588, IEEE 802.1AS

IEEE 802.3az - Energy Efficient Ethernet (EEE) PCI Express v 2.0, 5.0 GT/s, two lanes (x2)

Data Transfer Method

Controller

Intel I350 Powerville

Network Transfer Rate

10Base-T (Half-Duplex) 10 Mb/s per port, 40 Mb/s combined 20 Mb/s per port, 80 Mb/s combined 10Base-T (Full-Duplex) 100Base-TX (Half-100 Mb/s per port, 400 Mb/s combined

Duplex)

100Base-TX (Full-Duplex) 200 Mb/s per port, 800 Mb/s combined 1000Base-TX (Half and 1000 Mb/s per port, 4000 Mb/s combined

Full-Duplex)

Connector Two RJ-45

Cable Support 10 Base-T Categories 3, 4 or 5 UTP; up to 328 ft (100 m)

> 10/100/1000 Base-TX Category 5 or higher UTP; up to 328 ft (100 m)

Environmentfriendly Products and Approach

Recycling

End-of-life Management and Hewlett Packard Enterprise offers end-of-life product return, trade-in, and recycling programs, in many geographic areas, for our products. Products returned to Hewlett Packard Enterprise will be recycled, recovered or disposed of in a responsible manner.

http://www.hpe.com/recycle

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard Enterprise web site. These instructions may be used by recyclers and other WEEE treatment facilities as well as Hewlett Packard

Enterprise OEM customers who integrate and re-sell Hewlett Packard Enterprise equipment.

http://www.hpe.com/recycle

Summary of Changes

Date	Version History	Action	Description of Change
25-Sep-2017	From Version 24 to 25	Added	Added new SSD offering.
			Added new Storage options.
		Changed	Core Options and Additional Options were revised.
		Removed	Obsolete SKUs were removed from the QuickSpecs.
11-Jul-2017	From Version 23 to 24	Changed	Operating Systems and Virtualization Software
			Support for ProLiant Servers section was revised.
5-Jun-2017	From Version 22 to 23	Added	Added new Solid State Drive option.
8-May-2017	From Version 21 to 22	Added	Added support for ClearOS.
		Changed	Operating Systems and Virtualization Software Support for ProLiant Servers and HPE Drives were revised.
		Removed	Obsolete SKUs were removed from the QuickSpecs.
27-Mar-2017	From Version 20 to 21	Added	Added new Hard Drives.
17-Feb-2017	From Version 19 to 20	Changed	HPE Storage Options section was revised.
13-Feb-2017	From Version 18 to 19	Added	Added new HDD and SSD offering to the HPE Drives section.
		Changed	HPE Converged Infrastructure Management Software and HPE Drives were revised.
		Removed	SKUs 778640-B21 and 778641-B21 were
			removed from the Pre-configured Models section.
			Obsolete SKUs were removed from the HPE Processors section.
28-Nov-2016	From Version 17 to 18	Added	Added new Hard Drives offering.
		Removed	Obsolete SKUs were removed from the QuickSpecs.
28-Oct-2016	From Version 16 to 17	Removed	Obsolete Hard Drives were removed from the QuickSpecs.
26-Sep-2016	From Version 15 to 16	Added	Added new 10TB SATA Hot Plug LFF drives offering and new 900W AC/ 240VDC power supply.
		Changed	HPE Power Supplies section was revised.
		Removed	Obsolete SKUs were removed from the QuickSpecs.
17-Jun-2016	From Version 14 to 15	Added	Power supply information was added to the Configuration Information - Factory Integrated Models section.
6-Jun-2016	From Version 13 to 14	Added	Added new HDD offering to the HPE Drives section.
		Changed	New options added to the HPE Disk Backup and HPE Storage Options.
8-Apr-2016	From Version 12 to 13	Changed	HPE Processors section was revised.
31-Mar-2016	From Version 11 to 12	Added	Added new HPE Smart Memory 2400 MHz memory, Intel Xeon E5-2600v4 processor support, new HPE Trusted Platform Module (TPM) 2.0, new 900W AC/ 240VDC power supply, new SATA Hot Plug Standard drives.
		Changed	Power Supply, Upgradeability, Embedded Management, Service and Support, Pre-configured Models, HPE Security, and Memory sections were


Summary of Changes

			revised.
		Removed	Obsolete SKUs were removed from the QuickSpecs.
16-Feb-2016	From Version 10 to 11	Added	New HDD offering was added to HPE Drives.
		Changed	HPE Power Supplies, HPE Computation and Graphics Accelerators, HPE Data Center Racks, and HPE Power Distribution Units (PDUs) were revised.
		Removed	Obsolete SKUs were removed from the QuickSpecs.
17-Dec-2015	From Version 9 to 10	Added	Smart Buy models were added to the NA version.
1-Dec-2015	From Version 8 to 9	Added	New options added to HPE Disk Backup, HPE Disk Storage Systems, and HPE Power Distribution Units (PDUs).
		Changed	On System Management Chipset, Maximum Internal Storage, Embedded Management, and Server utilities were revised.
			Product images were updated.
		Removed	Obsolete SKUs were removed from QuickSpecs.
28-Sep-2015	From Version 7 to 8	Added	Added new 6Gb SATA Solid State Drives.
			Added new HPE OneView management software.
		Removed	Obsolete SKUs were removed from the QuickSpecs.
17-Aug-2015	From Version 6 to 7	Added	New Solid State Drives offering was added to Core Options.
		Changed	Maximum Internal Storage was revised.
		Removed	Obsolete SKUs were removed from QuickSpecs.
10-Jun-2015	From Version 5 to 6	Added	Added new HPE Drives: HPE 8TB 12G SAS 7.2K rpm LFF (3.5-inch) SC 512e Helium 1yr Warranty Hard Drive HPE 6TB 12G SAS 7.2K rpm LFF (3.5-inch) SC 512e Helium 1yr Warranty Hard Drive HPE 8TB 6G SATA 7.2K rpm LFF (3.5-inch) SC 512e Helium 1yr Warranty Hard Drive
			HPE 6TB 6G SATA 7.2K rpm LFF (3.5-inch) SC 512e Helium 1yr Warranty Hard Drive
1-Jun-2015	From Version 4 to 5	Added	New Hard Drives were added to Core Options.
I Juli 2013	TOTT VEISION 4 TO 3	Added	Added new HPE Power Supplies options.
			Added new HPE OneView LTUs to HPE Converged Infrastructure Management Software.
			New RDX+ backup external backup options added to HPE Disk Backup.
		Changed	Core Options and Additional Options were revised.
		Removed	Obsolete SKUs were removed from QuickSpecs.
24-Apr-2015	From Version 3 to 4	Added	Added 813534-B21 and 813535-B21 to HPE Power Supplies.

Summary of Changes

			Optional Software added to HPE Storage Controllers.
		Changed	HPE Memory, HPE Disk Storage Systems, HPE USB and SD Options, HPE Storage Controllers, and HPE Disk Storage Systems were updated.
9-Feb-2015	From Version 1 to 2	Added	Added HP Insight Software.
			Added new G4 UPS models.
		Changed	HPE Memory, HPE Tape Backup, HPE Disk Backup, HPE Rack Mount Consoles, KVM Switches, and Keyboards, and HPE Uninterruptible Power Systems (UPS) sections were revised.





Sign up for updates

© Copyright 2017 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Intel® and Xeon® are registered trademarks of Intel Corporation in the U.S. and other countries.

Microsoft®, Windows®, and Windows Server® are U.S. registered trademarks of the Microsoft group of companies.

For hard drives, 1GB = 1 billion bytes. Actual formatted capacity is less

c04447834 - 15089 - North America - V25 - 25-September-2017

