

Product datasheet

Specifications



Residual current circuit breaker (RCCB), Acti9 iID K, 2P, 40A, AC type, 300mA

A9R75240

Main

| | |
|-------------------------------------|---|
| Range | Acti9 |
| Product name | Acti9 iID K |
| Product or component type | Residual current circuit breaker (RCCB) |
| Device short name | iID K |
| Poles description | 2P |
| Neutral position | Left |
| [In] rated current | 40 A |
| Network type | AC |
| Earth-leakage sensitivity | 300 mA |
| Earth-leakage protection time delay | Instantaneous |
| Earth-leakage protection class | Type AC |
| Quality labels | VDE |

Complementary

| | |
|---|--|
| Device location in system | Outgoer |
| Network frequency | 50/60 Hz |
| [Ue] rated operational voltage | 220...240 V AC 50/60 Hz |
| Residual current tripping technology | Voltage independent |
| Rated breaking and making capacity | Idm 500 A Im 500 A |
| Rated conditional short-circuit current | GL63: Inc 4.5 kA K60: Inc 6 kA C60: Inc 6 kA |
| [Ui] rated insulation voltage | 440 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 4 kV |
| Surge current | 250 A |
| Contact position indicator | No |
| Control type | Toggle |
| Mounting mode | Clip-on |

| | |
|------------------------------------|---|
| Mounting support | DIN rail |
| 9 mm pitches | 4 |
| Height | 85 mm |
| Width | 36 mm |
| Depth | 69 mm |
| Net weight | 0.21 kg |
| Colour | White |
| Mechanical durability | 5000 cycles |
| Electrical durability | AC-1: 2000 cycles |
| Locking options description | Padlocking device |
| Connections - terminals | Tunnel type terminals top or bottom 1...35 mm ² rigid Tunnel type terminals top or bottom 1...25 mm ² flexible Tunnel type terminals top or bottom 1...25 mm ² flexible with ferrule |
| Wire stripping length | 16 mm for top or bottom connection |
| Tightening torque | 3.5 N.m top or bottom |

Environment

| | |
|--|--|
| Standards | EN/IEC 61008-1 EN/IEC 61008-2-1 |
| IP degree of protection | IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529 |
| Pollution degree | 2 |
| Electromagnetic compatibility | 8/20 µs impulse withstand, 200 A conforming to EN/IEC 61008-1 |
| Ambient air temperature for operation | -5...60 °C |
| Ambient air temperature for storage | -40...85 °C |

Packing Units

| | |
|-------------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 8.500 cm |
| Package 1 Width | 4.000 cm |
| Package 1 Length | 10.000 cm |
| Package 1 Weight | 201.000 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 6 |
| Package 2 Height | 10.500 cm |
| Package 2 Width | 9.000 cm |
| Package 2 Length | 25.500 cm |
| Package 2 Weight | 1.302 kg |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 54 |
| Package 3 Height | 30.000 cm |
| Package 3 Width | 30.000 cm |
| Package 3 Length | 40.000 cm |

| | |
|------------------|-----------|
| Package 3 Weight | 12.404 kg |
|------------------|-----------|

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Halogen content performance | Halogen free plastic parts & cables product |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Recommended replacement(s)