

sales@awaretech.com

STAT FAX® 2200

Programmable Open System

ELISA Microplate - Digital Dry Bath



realties

- Holds two 96-well microplates.
- Digitally controlled 8-speed mixer with orbital mixing from 575 to 1500 rpm.
- Temperature adjustable from ambient to 40°C with resolution of 0.1°C
- Digital timer controls mixing or can be operated independently, solely as a timer.
- Compact and easy to operate
- Outer tinted cover provides further insulation and protection from light.

Options & Accessories

Available with either 120V AC or 230V AC adapter.

37°C temperature calibration plate.



STAT FAX® 2200

ELISA Microplate - Digital Dry Bath

Temperature range Ambient to 40° C

Resolution 0.1° C

Uniformity with coverBetter than +/- .4° C

Mechanism Enclosed, warm aluminum bed with air circulation

MIXER

Speeds 8 gradual steps from 575 to 1500 RPM,

OptionsContinuous or pulseMechanismRotating counter weight

Timer

Certifications

Dimensions and weight

Vessel

Modes Set time, view time remaining, audible signal (stop

mixing but maintains temperature control after time out)

Resolution 1 second

Range 1 second to 99 minutes, 59 seconds

Electronic
Display Four 7 segment red LEDs.

Keyboard 16-key, domed membrane switch, enunciating

Power requirements 12 V AC, 2 amps. Adapters available for 120 V or 230 V

power with US or Euro plugs

NRTL Listed, CE Mark

Holds 2 standard microwell plates or strip trays

Approx. 11" x 12.5" x 5.75", 7.2 lbs Approx. 43 cm x 37 cm x 18 cm, 3.3 kg



ISO 13485:2016







Awareness Technology, Inc. USA & International tel: +1 772 283 6540 fax: +1 772 283 8020

Awareness Technology, Inc. Europe tel: +43 (0) 2236 892465 fax: +43 (0) 2236 892464

Awareness Technology, Inc. Asia & Africa tel: +971 (06) 557 80 58 fax: +971 (06) 557 80 59





No 5, Shekarabi Alley, Naz Street, Zafar district, Shariati Ave, Tehran, Iran