



# **TECHNICAL DATA SHEET**

#### **PRODUCT CODE**

OG0-800/03

### **PRODUCT NAME**

Flexo Varnish (Lacquer) for Offset

#### **DESCRIPTION**

• OG0-800/03 is an epoxy acrylate based overprint varnish used in offset applications on many substrates like paper, cardboard and some plastic based substates (PVC, OPP, PP, PE, ..) etc.

#### **APPLICATIONS**

- OG0-800/03 is used only in flexo printing application
- Procedure is the same as any other UV coating material.
- OG0-800/03 can cure very rapidly under UV radiation.
- Coated sheets can be stacked immediately after curing no blocking will occur.

### **PHYSICAL PROPERTIES**

- OG0-800/03 is %100 solid after curing.
- Viscosity is about 800 seconds @ DIN CUP No:4 (25 oC).
- Viscosity can be modified according to customer's demand.
- Flexo UV varnish is clear and has a very light yellow color in its packaging. Due to the performance chemicals, it can be slightly turbid but it doesn't effect the clearness or glossiness of cured film.
- Odorless.

### **FILM PROPERTIES**

- Creates brilliant, high glossy finish.
- Clear and flexible coating.
- High slip properties.
- High anti-blocking properties.
- High speed curing at conventional UV curing systems

#### **STORAGE STABILITY**

 Minimum 6 months at 25 C in sealed closed and nontransparent container. Keep the product away from sunlight

#### **HEALTH AND SAFETY**

• OG0-800/03 is formulated and manufactured with the raw materials from ISO 9001 proved suppliers.



### **PACKAGING**

- 20 kg buckets
- 20 kg jerrycan
- 200 kg drums

- 5 Kg buckets
- 1000 Kg IBC

### **KEY DATA**

Visual	Clear Liquid	
Viscosity (25 °C) DIN Cup 4 (second)	800±5	mPa.s
Density (25 °C)	1,05 ~ 1,15	gr/cm³
Curing Properties (With medium pressure Hg Lamb)	1-4 micron film can be cured under 30- 50 mj/cm2 UV radiation	

## **COMPOSITION INFORMATION ON INGREDIENTS**

	Oligomers (Acrylate Based)	60-80 %
	Reactive Diluents (Acrylate Based)	40- 20 %
	Photoinitiators	2- 10 %
	Performance Additives	0-4 %

Esa Kompozit Ve Teknolojik Çözümler Mühendislik Sanayi Ticaret A.Ş.

Gebze Dilovası Osb Mahallesi D-4015 Sok. No:6/1 Gebze / KOCAELİ Tel No : (0 262) 724 95 14 / 4 Hat

Fax No: (0 262) 724 95 18