

Datasheet

Art.No. 76.353.4035.1

Hood BAS GOT GG 40HM32 50 A1

revos BASIC 500V size 16H hood with threaded collar M32, lateral cable entry, high design, single locking lever



Art.No.	76.353.4035.1
EAN	4015573625013
Order unit	1 pieces

Approvals

Technical data

General

Housing material	Aluminium
Colour	Grey
Surface	With powder coating
Degree of protection (IP)	Other
UV resistant	Yes
Inflammability class of insulation material acc. with UL94	Other
Operating temperature range min.	-40 °C
Operating temperature range max.	120 °C

Model

DIN-size	16H
Model	male
Locking mechanism	Single locking lever
Cable entry	Sideways
Type of cable	Thread
With cable screw gland	No
Thread size M	32
Hinged lid	No
EMC-version	No

Classification

ECLASS 8.1	27440202: Housing for industrial connectors
ETIM 6.0	: EC000437
ETIM 5.0	EC000437: Housing for industrial connectors
ETIM 4.0	EC000437: Housing for industrial connectors
ETIM 3.0	EC000437: Housing for industry plug connectors

Drawings

60	M40	Kabelverschraubung (KV), IP65
76.353.4035.5	BAS 60T 66 16HM32 A5	∮Cable gland (CG), IP65
60	M40	KV mit Zugentlastung, IP54
76.353.4035.4	BAS 60T 66 16HM32 A4	∮CG with strain relief, IP54
60	M40	KV mit Zugentlastung und Knickschutz, IP54
76.353.4035.3	BAS 60T 66 16HM32 A3	∮CG with strain relief and bend support, IP54
60	M40	Zwischenstützen
76.353.4035.2	BAS 60T 66 16HM32 A2	∮Bushing
60	M40	Gewindebohrung
76.353.4035.1	BAS 60T 66 16HM32 A1	∮Thread hole
60	M40	Kabelverschraubung (KV), IP54
76.353.4035.0	BAS 60T 66 16HM32 A0	∮Cable gland (CG), IP54

Varianten/ Variants

Bestellnummer / Order number: 76.353.4035.0

Varianten / Variants: 0, 2, 3, 4, 5

Wieland Electric Logo

GEHÄUSEOBerteile IL
 Baugröße 16H-Kabelbohrung 1x M25/M32/M40 seitlich
 hood size 16H-cable outlet 1x M25/M32/M40 side

76.353.4035.0 3x M25/M32/M40