

Datasheet

Art.No. 70.320.4828.0

Bottom BAS GUT GK 48 50 A

revos BASIC 500V size 48 open-bottom base, single locking lever



| | |
|------------|---------------|
| Art.No. | 70.320.4828.0 |
| EAN | 4015573220157 |
| Order unit | 1 pieces |

Approvals



Technical data

General

| | |
|--|---------------------|
| Housing material | Aluminium |
| Colour | Grey |
| Surface | With powder coating |
| Degree of protection (IP) | IP54 |
| UV resistant | Yes |
| Inflammability class of insulation material acc. with UL94 | Other |
| Operating temperature range min. | -40 °C |
| Operating temperature range max. | 120 °C |

Model

| | |
|------------------------|----------------------------------|
| DIN-size | 48 |
| Model | Equipment mounted (feed-through) |
| Locking mechanism | Single locking lever |
| Cable entry | None |
| Type of cable | None |
| With cable screw gland | No |
| Hinged lid | No |
| EMC-version | No |

Classification

| | |
|------------|---|
| ECLASS 8.1 | 27440202: Housing for industrial connectors |
| ETIM 6.0 | : EC000437 |
| ETIM 5.0 | EC000437: Housing for industrial connectors |

| | |
|----------|--|
| ETIM 4.0 | EC000437: Housing for industrial connectors |
| ETIM 3.0 | EC000437: Housing for industry plug connectors |

Drawings

