

Datasheet

Art.No. 71.353.1635.1

Hood BAS GOT GG 16 M32 A1

revos BASIC 500V size 16 hood with threaded collar M32, lateral cable entry, single locking lever



Art.No.	71.353.1635.1
EAN	4015573651654
Order unit	1 pieces

Approvals



Technical data

General

Housing material	Aluminium
Colour	Grey
Surface	With powder coating
Degree of protection (IP)	Other
UV resistant	Yes
Inflammability class of insulation material acc. with UL94	Other
Operating temperature range min.	-40 °C
Operating temperature range max.	120 °C

Model

DIN-size	16
Model	male
Locking mechanism	Single locking lever
Cable entry	Sideways
Type of cable	Thread
With cable screw gland	No
Thread size M	32
Hinged lid	No
EMC-version	No

Classification

ECLASS 8.1	27440202: Housing for industrial connectors
ETIM 6.0	: EC000437

ETIM 5.0	EC000437: Housing for industrial connectors
ETIM 4.0	EC000437: Housing for industrial connectors
ETIM 3.0	EC000437: Housing for industry plug connectors

Drawings

Varianten/ Variants

.0

.2

.3

.4

.5

71.350.1635.5	BAS 60T 66 16 M25	M32 A5	Kabelverschraubung (KV), IP65 /Cable gland (CG), IP65
71.350.1635.4	BAS 60T 66 16 M25 A4	M32 A4	KV mit Zugentlastung, IP54 /CG with strain relief, IP54
71.350.1635.3	BAS 60T 66 16 M25	M32 A3	KV mit Zugentlastung und Knockschutz, IP54 /CG with strain relief and knock support, IP54
71.350.1635.2	BAS 60T 66 16 M25 A2 <th>M32 A2</th> <th>Zwischensulfetzen /Bushing</th>	M32 A2	Zwischensulfetzen /Bushing
71.350.1635.1	BAS 60T 66 16 M25 A1 <th>M32 A1</th> <th>Seiteneinführung /Thread hole</th>	M32 A1	Seiteneinführung /Thread hole
71.350.1635.0	BAS 60T 66 16 M25 <th>M32 A0</th> <th>Kabelverschraubung (KV), IP54 /Cable gland (CG), IP54</th>	M32 A0	Kabelverschraubung (KV), IP54 /Cable gland (CG), IP54

Bestellnummer / Order number

Typ / Type

Varianten / Variants

Weitere Daten siehe KATALOG oder eKatalog.
Additional data see CATALOG or eCatalog.

www.wieland-electric.com
eshop.wieland-electric.com

GEHÄUSEOBerteil

Basgröße 16-Kabelabgang seitlich-M25-M32
Hood size 16-cable outlet side-M25-M32