



Datasheet

Art.No. 76.322.0736.0

Bottom MIN GUT GC 7 M20 25 Z0

revos MINI size 3 closed-bottom base with cable gland M20 single locking lever, metal housing $% \left({{\left[{{{\rm{NN}}} \right]}_{\rm{A}}}_{\rm{A}}} \right)$



| Art.No. | 76.322.0736.0 |
|------------|---------------|
| EAN | 4015573651210 |
| Order unit | 10 pieces |

Approvals

Technical data

General

| Housing material | Cast zinc |
|--|---------------------|
| Colour | Grey |
| Surface | With powder coating |
| Degree of protection (IP) | IP54 |
| UV resistant | Yes |
| Inflammability class of insulation material acc. with UL94 | Other |
| Operating temperature range min. | -40 °C |
| Operating temperature range max. | 120 °C |

Model

| DIN-size | 3 |
|------------------------|-------------------------|
| Model | Surface mounting (base) |
| Locking mechanism | Single locking lever |
| Cable entry | Below |
| Type of cable | Gland nut |
| With cable screw gland | Yes |
| Thread size M | 20 |
| Hinged lid | No |
| EMC-version | No |





Classification

| ECLASS 8.1 | 27440202: Housing for industrial connectors |
|------------|--|
| ETIM 6.0 | : EC000437 |
| ETIM 5.0 | EC000437: Housing for industrial connectors |
| ETIM 4.0 | EC000437: Housing for industrial connectors |
| ETIM 3.0 | EC000437: Housing for industry plug connectors |





Drawings

