

Datasheet

Art.No. 71.320.2428.0

Bottom BAS GUT GK 24 A

revos BASIC 500V size 24 open-bottom base, single locking lever



Art.No.	71.320.2428.0
EAN	4015573225176
Order unit	1 pieces

Approvals



Technical data

General

Housing material	Aluminium
Colour	Grey
Surface	With powder coating
Degree of protection (IP)	IP54
UV resistant	Yes
Inflammability class of insulation material acc. with UL94	Other
Operating temperature range min.	-40 °C
Operating temperature range max.	120 °C

Model

DIN-size	24
Model	Equipment mounted (feed-through)
Locking mechanism	Single locking lever
Cable entry	None
Type of cable	None
With cable screw gland	No
Hinged lid	No
EMC-version	No

Classification

ECLASS 8.1	27440202: Housing for industrial connectors
ETIM 6.0	: EC000437
ETIM 5.0	EC000437: Housing for industrial connectors

ETIM 4.0	EC000437: Housing for industrial connectors
ETIM 3.0	EC000437: Housing for industry plug connectors

Drawings

71.320.2428.0 BAS 6UT GK 24 A

Bestellnummer / Order number: 71.320.2428.0
 Typ / Type: BAS

Weitere Daten, siehe KATALOG oder eKatalog. / Additional data see CATALOG or eCatalog: www.wieland-electric.com
shop.wieland-electric.com

Bohrbild / Cut out

Dimensions: 140 (length), 28 (width), 112 (height), 130 (height), 35 (width), 32 (width), 43.4 (height), 66.4 (height), R4.6 (radius)

GEHAUSEUNTERTEIL
 Größe 24-eiten
 Open housing size 24

Wieland
 Industrietechnik
 Industrietechnik

71.320.2428.0 13K

GEHAUSEUNTERTEIL

Größe 24-eiten

Open housing size 24