

Datasheet

Art.No. 71.354.1635.1

Hood BAS GOT GI 16 M32 A1

revos BASIC 500V size 16 hood with threaded collar M32, top cable entry, single locking lever



Art.No.	71.354.1635.1
EAN	4015573651432
Order unit	1 pieces

Approvals



Technical data

General

Housing material	Aluminium
Colour	Grey
Surface	With powder coating
Degree of protection (IP)	Other
UV resistant	Yes
Inflammability class of insulation material acc. with UL94	Other
Operating temperature range min.	-40 °C
Operating temperature range max.	120 °C

Model

DIN-size	16
Model	male
Locking mechanism	Single locking lever
Cable entry	Above
Type of cable	Thread
With cable screw gland	No
Thread size M	32
Hinged lid	No
EMC-version	No

Classification

ECLASS 8.1	27440202: Housing for industrial connectors
ETIM 6.0	: EC000437

ETIM 5.0	EC000437: Housing for industrial connectors
ETIM 4.0	EC000437: Housing for industrial connectors
ETIM 3.0	EC000437: Housing for industry plug connectors

Drawings

Varianten/ Variants

71.352.1635.5	BAS 60T 61 16 M22 A5	Kabe lverschraubung (KV), IP65 /Cable gland (CB), IP65
71.352.1635.4	BAS 60T 61 16 M25 A4	KV mit Zugentlastung, IP54 /Cable gland with strain relief, IP54
71.352.1635.3	BAS 60T 61 16 M25 A3	KV mit Zugentlastung und Kabe lschutzhülse, IP54 /KV with strain relief and cable gland, IP54
71.352.1635.2	BAS 60T 61 16 M25 A2	Zwischenstück aus /Bushing
71.352.1635.1	BAS 60T 61 16 M25 A1	Gez. Nefelbohrung /Thread hole
71.352.1635.0	BAS 60T 61 16 M25 A0	Kabe lverschraubung (KV), IP54 /Cable gland (CB), IP54
Bestellnummer / Order number Typ / Type Varianten / Variants		

Weitere Daten, siehe KATALOG oder eKatalog.
Additional data, see CATALOG or eCatalog.
www.wieland-electric.com
eshop.wieland-electric.com

GEHAUSEOBerteil
 Gehäuse 16-kabelig, oben M25/M32
 Hood size 16-cable outlet top M25/M32