

Datasheet

Art.No. 71.350.1635.1

Hood BAS GOT GG 16 M25 A1

revos BASIC 500V size 16 hood with threaded collar M25, lateral cable entry, single locking lever



Art.No.	71.350.1635.1
EAN	4015573622012
Order unit	1 pieces

Approvals



Technical data

General

Housing material	Aluminium
Colour	Grey
Surface	With powder coating
Degree of protection (IP)	Other
UV resistant	Yes
Inflammability class of insulation material acc. with UL94	Other
Operating temperature range min.	-40 °C
Operating temperature range max.	120 °C

Model

DIN-size	16
Model	male
Locking mechanism	Single locking lever
Cable entry	Sideways
Type of cable	Thread
With cable screw gland	No
Thread size M	25
Hinged lid	No
EMC-version	No

Classification

ECLASS 8.1	27440202: Housing for industrial connectors
ETIM 6.0	: EC000437

ETIM 5.0	EC000437: Housing for industrial connectors
ETIM 4.0	EC000437: Housing for industrial connectors
ETIM 3.0	EC000437: Housing for industry plug connectors

Drawings

Varianten/ Variants

71.350.1635.5	BAS 60T 66 16 M25 A5	M32 A5	Kabelverschraubung(KV), IP65
71.350.1635.4	BAS 60T 66 16 M25 A4	M32 A4	KV mit Zugentlastung, IP54
71.350.1635.3	BAS 60T 66 16 M25 A3	M32 A3	KV mit Zugentlastung und Kriechschutz, IP54
71.350.1635.2	BAS 60T 66 16 M25 A2	M32 A2	Zwischenspalzen
71.350.1635.1	BAS 60T 66 16 M25 A1	M32 A1	Gewindebohrung
71.350.1635.0	BAS 60T 66 16 M25 A0	M32 A0	Kabelverschraubung(KV), IP54
Bestellnummer / Order number		Typ / Type	Varianten / Variants

Weitere Daten, siehe KATALOG oder eKatalog - Additional data, see CATALOG or eCatalog. www.wieland-electric.com
shop.wieland-electric.com

Produktionsart / Production type		Material / Material		Oberflächenbeschichtung / Surface coating		Anwendung / Application	
/	/	/	/	/	/	/	/
/	/	/	/	/	/	/	/
/	/	/	/	/	/	/	/
/	/	/	/	/	/	/	/
/	/	/	/	/	/	/	/

GEHAUSEOBERTEIL
Baugröße: 16-Kabelabgang 5x111x8-M32
Hood size: 16-cable outlet size-M32