


Datasheet

Art.No. 70.810.1056.0

Male insert BAS STCK 10 50 PC



Art.No.	70.810.1056.0
EAN	4015573861947
Order unit	5 pieces

Drawings

Verpackung/packaging: 5 Stück im Karton / 5 pieces in the cardboard

gezeichnet/drawn: 70.810.3256.0

X (im 180° gedreht/around 180° turned)

Technische Daten
Technical Data

Bemessungsspannung rated voltage	500V
Bemessungsstrom rated current	16A
Bemessungsstoßspannung rated peak voltage	6kV
Verschmutzungsgrad degree of pollution	3
Isoliermaterial insulating material	Polycarbonat
Brennbarkeitsklasse flammability rating	UL 94 V-0
Temperaturbereich temperature range	-40°C - +125°C

Teile - Nr. part no.	Typ type	A	B	Polz. pole
70.810.1056.0	BAS STACK 10 50 PC	44	51	10
70.810.1856.0	BAS STACK 18 50 PC	57	64	18
70.810.3256.0	BAS STACK 32 50 PC	77,5	84	32
70.810.4656.0	BAS STACK 46 50 PC	104	111	46

Zubehör - Steckkontakte
Accessories - plug contact

Bestell-Nr.	Ømm²	AWG
05.543.70MM.0	0,5	20 AWG
05.543.71MM.0	0,75-1	18 AWG
05.543.72MM.0	1,5	16 AWG
05.543.73MM.0	2,5	14 AWG

MM Oberfläche
Surface

01	vergoldet/gold plated
02	versilbert/silver plated

Wieland
Industrie-Technologie

STECKEREINSATZ
für Crimpkontakte 500V 16A
male insert for crimp contacts