



Datasheet

Art.No. 71.353.2435.1

Hood BAS GOT GG 24 M32 A1

revos BASIC size 24 hood with threaded collar M32, lateral cable entry, single locking lever $\,$



| Art.No. | 71.353.2435.1 |
|------------|---------------|
| EAN | 4015573651692 |
| Order unit | 1 pieces |

Approvals



Technical data

General

| Housing material | Aluminium |
|--|---------------------|
| Colour | Grey |
| Surface | With powder coating |
| Degree of protection (IP) | Other |
| UV resistant | Yes |
| Inflammability class of insulation material acc. with UL94 | Other |
| Operating temperature range min. | -40 °C |
| Operating temperature range max. | 120 °C |

Model

| DIN-size | 24 |
|------------------------|----------------------|
| Model | male |
| Locking mechanism | Single locking lever |
| Cable entry | Sideways |
| Type of cable | Thread |
| With cable screw gland | No |
| Thread size M | 32 |
| Thread size PG | |
| Hinged lid | No |
| EMC-version | No |

Classification





| ETIM 6.0 | : EC000437 |
|----------|--|
| ETIM 5.0 | EC000437: Housing for industrial connectors |
| ETIM 4.0 | EC000437: Housing for industrial connectors |
| ETIM 3.0 | EC000437: Housing for industry plug connectors |