

## Datasheet

Art.No. 70.300.1040.0

Female insert BAS BUS 10 2,5 50

revos BASIC 500V 10 pole + ground, female insert 500V/16A with wire protection, Sn screw connection



Art.No.	70.300.1040.0
EAN	4015573219601
Order unit	10 pieces

## Approvals



## Technical data

### General

Model	Female insert
Inflammability class of insulation material acc. with UL94	V0
Colour	Grey
Mating cycles	200
Pollution degree	3
Modular version	No
Operating temperature range min.	-40 °C
Operating temperature range max.	120 °C

### Connection Data

Connection type	Screw connection
Number of poles	10
Plus switching contacts	0
Number of pole for rated current 2	0
Number of pole for rated current 3	0
Total number of poles (without ground contact)	10
With wire protection	Yes
Min. conductor diameter rigid (solid/stranded)	0.5 mm <sup>2</sup>
Max. conductor diameter rigid (solid/stranded)	2.5 mm <sup>2</sup>
Protective contact	Yes

### Technical Data UL/CSA

Rated voltage according to UL/CSA	600 V
-----------------------------------	-------

Rated current according UL	16 A
Rated current according CSA	16 A
Min. conductor cross section flexible wire	0.5 mm <sup>2</sup>
Max. conductor cross section flexible wire	2.5 mm <sup>2</sup>
Conductor cross section flexible AWG wire	22-14 AWG

**Model**

With housing	No
--------------	----

**Contacts**

Contact material	Copper alloy
Surface	Tin-plated
Contact resistance	≤ 1.5 mOhm
Wire strip length	7 mm

**Screws head design/recomm. Torque**

Mounting screws	H1/0.5-0.7 Nm
Clamping screws	H1/0.5-0.7 Nm
Ground conductor screws	H2/1.2-1.6 Nm

**Technical Data DIN EN 61984**

Nominal voltage	500 V
Rated voltage face/ground	500 V
Nominal current	16 A
Rated impulse voltage	6 kV


**Classification**

ECLASS 8.1	27440205: Contact insert for industrial connectors
ETIM 5.0	EC000438: Contact insert for industrial connectors
ETIM 4.0	EC000438: Contact insert for industrial connectors
ETIM 3.0	EC000438: Contact insert for heavy duty connectors


Drawings

**Kodieransichten Ausführung 6-/16-/24-polig**  
Coding view execution 6-/16-/24-pole


6-polig/6-pole  
70.300.064.0.0




16-polig/16-pole  
70.300.164.0.0






24-polig/24-pole  
70.300.244.0.0



10-polig/10-pole  
70.300.104.0.0



Farbe: kieselgrau  
colour: pebble gray

ⓑ Weitere Daten siehe Katalog  
further data see catalog

Teile-Nr. part no.	Typ type	Polzahl pole	L	I
70.300.064.0.0	BAS BUS 6 2,5 50	6x	49,8	44
70.300.104.0.0	BAS BUS 10 2,5 50	10x	62,8	57
70.300.164.0.0	BAS BUS 16 2,5 50	16x	83,3	77,5
70.300.244.0.0	BAS BUS 24 2,5 50	24x	109,8	104

Referencing Size 60 14405 ① Terminal system Size 60 14405 ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪ ⑫ ⑬ ⑭ ⑮ ⑯ ⑰ ⑱ ⑲ ⑳ ㉑ ㉒ ㉓ ㉔ ㉕ ㉖ ㉗ ㉘ ㉙ ㉚ ㉛ ㉜ ㉝ ㉞ ㉟ ㊱ ㊲ ㊳ ㊴ ㊵ ㊶ ㊷ ㊸ ㊹ ㊺ ㊻ ㊼ ㊽ ㊾ ㊿

① - Dimensions with insulation thickness  
② - Dimensions with insulation thickness  
③ - Dimensions with insulation thickness  
④ - Dimensions with insulation thickness  
⑤ - Dimensions with insulation thickness  
⑥ - Dimensions with insulation thickness  
⑦ - Dimensions with insulation thickness  
⑧ - Dimensions with insulation thickness  
⑨ - Dimensions with insulation thickness  
⑩ - Dimensions with insulation thickness  
⑪ - Dimensions with insulation thickness  
⑫ - Dimensions with insulation thickness  
⑬ - Dimensions with insulation thickness  
⑭ - Dimensions with insulation thickness  
⑮ - Dimensions with insulation thickness  
⑯ - Dimensions with insulation thickness  
⑰ - Dimensions with insulation thickness  
⑱ - Dimensions with insulation thickness  
⑲ - Dimensions with insulation thickness  
⑳ - Dimensions with insulation thickness  
㉑ - Dimensions with insulation thickness  
㉒ - Dimensions with insulation thickness  
㉓ - Dimensions with insulation thickness  
㉔ - Dimensions with insulation thickness  
㉕ - Dimensions with insulation thickness  
㉖ - Dimensions with insulation thickness  
㉗ - Dimensions with insulation thickness  
㉘ - Dimensions with insulation thickness  
㉙ - Dimensions with insulation thickness  
㉚ - Dimensions with insulation thickness  
㉛ - Dimensions with insulation thickness  
㉜ - Dimensions with insulation thickness  
㉝ - Dimensions with insulation thickness  
㉞ - Dimensions with insulation thickness  
㉟ - Dimensions with insulation thickness  
㊱ - Dimensions with insulation thickness  
㊲ - Dimensions with insulation thickness  
㊳ - Dimensions with insulation thickness  
㊴ - Dimensions with insulation thickness  
㊵ - Dimensions with insulation thickness  
㊶ - Dimensions with insulation thickness  
㊷ - Dimensions with insulation thickness  
㊸ - Dimensions with insulation thickness  
㊹ - Dimensions with insulation thickness  
㊺ - Dimensions with insulation thickness  
㊻ - Dimensions with insulation thickness  
㊼ - Dimensions with insulation thickness  
㊽ - Dimensions with insulation thickness  
㊾ - Dimensions with insulation thickness  
㊿ - Dimensions with insulation thickness

Material / Material: 70.300.064.0.001K

Ordering for / Bestellen für: T 70.300.064.0.001K

Scale: 1:1

**BUCHSEINENSATZ**  
2,5 qmm 500V 16A Schraubanschluss u. Drahtschutz  
male insert screw connection and wire protection

**wieland**  
www.wieland-electric.com

Referencing Size 60 14405 ① Terminal system Size 60 14405 ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪ ⑫ ⑬ ⑭ ⑮ ⑯ ⑰ ⑱ ⑲ ⑳ ㉑ ㉒ ㉓ ㉔ ㉕ ㉖ ㉗ ㉘ ㉙ ㉚ ㉛ ㉜ ㉝ ㉞ ㉟ ㊱ ㊲ ㊳ ㊴ ㊵ ㊶ ㊷ ㊸ ㊹ ㊺ ㊻ ㊼ ㊽ ㊾ ㊿

① - Dimensions with insulation thickness  
② - Dimensions with insulation thickness  
③ - Dimensions with insulation thickness  
④ - Dimensions with insulation thickness  
⑤ - Dimensions with insulation thickness  
⑥ - Dimensions with insulation thickness  
⑦ - Dimensions with insulation thickness  
⑧ - Dimensions with insulation thickness  
⑨ - Dimensions with insulation thickness  
⑩ - Dimensions with insulation thickness  
⑪ - Dimensions with insulation thickness  
⑫ - Dimensions with insulation thickness  
⑬ - Dimensions with insulation thickness  
⑭ - Dimensions with insulation thickness  
⑮ - Dimensions with insulation thickness  
⑯ - Dimensions with insulation thickness  
⑰ - Dimensions with insulation thickness  
⑱ - Dimensions with insulation thickness  
⑲ - Dimensions with insulation thickness  
⑳ - Dimensions with insulation thickness  
㉑ - Dimensions with insulation thickness  
㉒ - Dimensions with insulation thickness  
㉓ - Dimensions with insulation thickness  
㉔ - Dimensions with insulation thickness  
㉕ - Dimensions with insulation thickness  
㉖ - Dimensions with insulation thickness  
㉗ - Dimensions with insulation thickness  
㉘ - Dimensions with insulation thickness  
㉙ - Dimensions with insulation thickness  
㉚ - Dimensions with insulation thickness  
㉛ - Dimensions with insulation thickness  
㉜ - Dimensions with insulation thickness  
㉝ - Dimensions with insulation thickness  
㉞ - Dimensions with insulation thickness  
㉟ - Dimensions with insulation thickness  
㊱ - Dimensions with insulation thickness  
㊲ - Dimensions with insulation thickness  
㊳ - Dimensions with insulation thickness  
㊴ - Dimensions with insulation thickness  
㊵ - Dimensions with insulation thickness  
㊶ - Dimensions with insulation thickness  
㊷ - Dimensions with insulation thickness  
㊸ - Dimensions with insulation thickness  
㊹ - Dimensions with insulation thickness  
㊺ - Dimensions with insulation thickness  
㊻ - Dimensions with insulation thickness  
㊼ - Dimensions with insulation thickness  
㊽ - Dimensions with insulation thickness  
㊾ - Dimensions with insulation thickness  
㊿ - Dimensions with insulation thickness