

سیستم های طراحی مهندسی چند منظوره لیزر



oceTDS600 مناسب برای سرعت و توان بالا در کنار تداوم کیفیت

Specifications

Plotter

Printing technology
Electrophotography With Organic Photoconductor

Media Width
Roll Feed : 11.5" - 36" (297 - 914 mm)

Media Type
Plain, Transparent, Recycle, Film, Vellums

Speed (A0)
0:15 For All Print Modes

Toner Useable
oce B5 Toner

Print Resolution (Max.)
Up to 400 x 400 dpi

Warm Up Time
None Instant On

Dimensions (WxDxH)
1400x753x1470 mm

Weight
Approx. 250 Kg. (2 Rolls, 1 Sheet)

Amin3 building ■ Mohtasham Kashani St.
Esfahan ■ Iran
☎ : +98 31 36258137 & 39
☎ : +98 31 36246610

Controller

Platform
Windows XP Embedded

HDD Capacity
2x80 GB

Memory
512 MB

Interface
Ethernet 100/10 Mbits/s With RJ45

File Formats
HPGL, HPGL2, Calcomp 906/907/951, HPRTL, TIFF 6.0, CALS1, NIRS, C4, ASCII, Optional Adobe, PostScript, PDF

Applications
Oce Remote Application
Oce Scan Logic

Scan Tenology
Oce Color Image Logic Intelligent Image

اصفهان ■ خیابان محتشم کاشانی (دقیقی) ■ بین فرعی ۳۱ و ۳۳
ساختمان امین ۳ ■ طبقه ۲ ■ واحد شماره ۸
☎ : +98 31 36258137 & 39
☎ : +98 31 36246610

Scanner

Scanning technology
CCD, Image Logic Technology

Resolution (Max.)
600 x 600 dpi

Copy And Scan Mode
Lines & Text, Grays & Lines, Dark Original
Blueprint, Transparent And Photo, Printed Matter

Scan Modes (Option)
Color
15 mm Tickness Original in TC4-TX Model

Scan & Copy Speed (A0)
B&W 0:15
Grayscale 0:15

Multi Copy Mode
1-999 Copies Custom Zoom 25-400% (Adjustable 1% & 0.1%)

Dimensions (WxDxH)
1314x583x1353 mm

Weight
Approx. 89 Kg.