




Type	Upright
Volume total	966 litre
Usable volume 2/4 compartments	908/893 litre
Storage capacity 2" boxes	770
External dimensions	1340/1285 x 973 x 1992 mm
Internal dimensions	1035 x 731,5/697 x 1276 mm
Compartments/inner doors/platforms	4/2/3 in height adjustable
Main door	With lock and keys
Inner doors	Stainless steel, insulated
Material internal/external	Stainless Steel/Epoxy Coated steel
Placed on	Heavy duty castors, in front with brakes
Insulation	Polyurethane
Cooling	Two (2) cascade connected compressors
Refrigerants	First stage: R455A/Second stage: R170
Condenser	Air-cooled
Temperature adjustments	-50°C till -86°C (other range; on request)
Controller	Web-based
Display	7" Touchscreen in main door at eye level
Temperature history	On display with scroll function
Data storage	At least 12 months
Temperature sensors	PT1000
Backup battery	Alarming and monitoring during power failure
Alarming	Optical and acoustic, but also possible via E-Mail
Communication	Telephone dialling activation system Potential (Voltage) free contact RJ45 (Ethernet) connection USB connection
Software	I-freeze
CO <sub>2</sub> -backup system	Partially prepared
Transit/vacuum release	Ø 26 mm/vacuum release situated in transit
Cable entry ports	Two (2)
Compressor room	Well-arranged layout and very easy filter exchange
Requirements	220/240 VAC, 50 Hz, fuse 16 Amp. slow
Power and current rating	1590 VA/1375 W/7,0 Amp.
Energy consumption	15 kWh/24h
Heat exchange	0,6 kW/h
Noise level	57 dBA
Net weight	425 kg
CE certified	EN61010-1:2010, EN60601-1-2:2007



**OPTIONS**

- Hybride Cooling System
- Water cooling
- CO<sub>2</sub>-backup system
- LN<sub>2</sub>-backup system
- Extended backup system
- Temperature chart recorder
- Voltage stabilizer
- Transformer
- IQ/OQ/PQ
- Electronic lock main door
- Padlock on main door
- Left hinged door(s)
- 3, 4, 5 or 6 compartments/inner doors
- Inner doors lockable by key
- Levelling feet
- Alarming by texting and/or phone
- Sliding shelves with hinged front
- Drawers in Aluminium or Stainless Steel
- Racking systems in Aluminum or Stainless Steel
- Cryo Boxes
- Cryo Gloves



**DRAWER RACKING SYSTEM\*1**



Model #	Comp.	# Racks	# Boxes per rack	Total boxes 133x133	Total plates 128x85	Max. height box
DSA-7338-136G	4	28	56		1568	33 mm
DSA-5505-136G	4	14	25	770*2	1232	50 mm
DSA-6505-136G		14	30			
DSA-11525-136G	2	14	55	770	1232	52 mm
DSA-5535-136G	4	28	25	700	1120	53 mm
DSA-7845-136G	2	14	35	490		84 mm
DSA-3915-136G	4	28	15	420		91 mm
DSA-21285-136G	4	28	10	280		128 mm

\*1 other dimensions on request. \*2 only on request.

**SIDE ACCESS RACKS**

Model #	Comp.	# Racks	# Boxes per rack	Total boxes 133x133	Maximum height box
HR-5-6-45	4	28	30	840	45 mm
HR-5-5-53	4	28	25	700	53 mm
HR-5-3-76	4	28	15	420	76 mm
HR-5-FLEX	4	28	25/15	700/420	55/95 mm

Laurent Janssensstraat 105  
5048 AR Tilburg  
The Netherlands  
T +31 13 750 15 55  
F +31 13 463 86 35  
info@snijderslabs.com  
www.snijderslabs.com