

## Waterbath

### Model WNB 22



### Standard equipment

#### Control

- microprocessor PID-temperature controller with integrated autodiagnostic system with fault indicator
- solid state switching unit
- one Pt100 sensor class A in 4-wire-circuit
- integrated digital timer from 1 min. to 99,59 hours for:  
ON continuous operation  
WAIT (delayed on for continuous and limited timed operation)  
HOLD
- digital display (LED) of set and actual temperature (0,1 °C resolution) and of (remaining) programme time
- LEDs for indication of programme status

#### Overtemperature protection (double)

- in case of overtemperature due to failure, the heating is switched off at approx. 10 °C above the set temperature (fixed value)
- mechanical temperature limiter TB protection class 1 switching the heating off at approx. 30 °C above max. temperature of the bath

#### Textured Stainless Steel Casing

- l x w x h: 578 x 436 x 296 mm
- material 1.4301 (ASTM 304), corrosion resistant

#### Interior - Heating Concept

- l x w x h: 350 x 290 x 220 mm, 22 l
- easy-to-clean interior, made of stainless steel, reinforced by deep drawn ribbing, material no. 1.4301 (ASTM 304), laser-welded
- corrosion-proof large-area heating on three sides

#### Temperature Range

- min. 5 °C above ambient up to +95 °C with additional boiling mode (+100 °C)

#### Voltage / Power Rating

- 230 V (+/- 10%), 50/60 Hz
- approx. 2.000 W (during heating)

#### Packing Data

- net weight approx. 16 kg
- gross weight carton approx. 20 kg
- dimensions approx.:  
carton w x h x d: 67 x 53 x 46 cm
- the appliances must be transported upright

#### Customs Tariff Number

- 8419 8998

#### Country of Origin

- Federal Republic of Germany

#### WEEE-Reg.-No.

- DE 66812464

#### Accessories

- Flat stainless steel cover with openings and concentric ring sets (6 openings / 87 mm diameter) L0
- Gable stainless steel cover mounted for condensate drainage L1
- Water level control (for WNB, WNE, WPE) L3