



نوع پمپ		نوع الکتروموتور 3 ~ 400 V(380-415)	جریان (آمپر) A	توان P2		قطر لوله چاه (اینچ)		میزان آبدهی Q m³/h	n = 2900 rpm, 50 Hz (دور در دقیقه)											DM حداکثر قطر مجموعه mm	L طول مجموعه mm	L1 طول پمپ mm	W وزن مجموعه kg	W وزن پمپ kg
RP 293-1	B - RP 293-1 NB - RP 293-1			KW	HP	in φ	in φ		20	25	28	30	35	40	45	50	55	60						
RP 293-1/12	NB-RP-293-1/12	9I 453/2	93	45.5	62	10	4	240	237	235	233	230	224	215	202	184	164	215	2760	1290	298	106		
RP 293-1/13	NB-RP-293-1/13	9I 523/2	107	52	70	10	4	258	255	253	252	249	243	234	220	200	178	215	2930	1350	316	111		
RP 293-1/14	NB-RP-293-1/14	9I 523/2	107	52	70	10	4	279	275	273	271	268	263	253	238	215	192	215	2990	1410	321	116		
RP 293-1/15	NB-RP-293-1/15	9I 553/2	114	55	75	10	4	296	293	292	290	287	282	272	256	231	206	215	3050	1470	335	121		
RP 293-1/16	NB-RP-293-1/16	9I 603/2	122	60	80	10	5	315	312	311	309	306	301	292	274	247	219	215	3240	1530	356	126		
RP 293-1/17	NB-RP-293-1/17	9I 673/2	137	67	90	10	5	334	331	329	328	325	319	310	292	263	233	215	3300	1590	370	131		
RP 293-1/18	NB-RP-293-1/18	9I 673/2	137	67	90	10	5	353	350	349	347	344	338	329	310	278	245	215	3370	1660	376	137		
RP 293-1/19	NB-RP-293-1/19	9I 733/2	154	73.5	100	10	5	372	369	368	366	363	357	348	328	294	259	215	3520	1720	399	142		
RP 293-1/20	NB-RP-293-1/20	9I 733/2	154	73.5	100	10	5	391	388	387	386	382	376	367	346	311	274	215	3580	1780	404	147		
RP 293-1/21	NB-RP-293-1/21	9I 833/2	166	83	110	10	5	412	408	406	405	400	394	384	364	327	285	215	3820	1840	434	152		
RP 293-1/22	NB-RP-293-1/22	9I 833/2	166	83	110	10	5	429	427	425	424	419	412	401	382	343	298	215	3880	1900	439	157		
RP 293-1/23	NB-RP-293-1/23	9I 923/2	188	92	125	10	5	449	446	444	443	438	430	418	399	359	313	215	3940	1960	453	162		
RP 293-1/24	NB-RP-293-1/24	9I 923/2	188	92	125	10	5	469	465	463	462	456	448	437	417	375	326	215	4000	2020	458	167		
RP 293-1/25	NB-RP-293/25	9I 923/2	188	92	125	10	5	490	485	482	481	475	466	454	434	392	341	215	4060	2080	463	172		
RP 293-1/26	NB-RP-293-1/26	9I 923/2	188	92	125	12	5	508	504	501	499	494	484	471	450	407	355	215	4120	2140	471	180		
RP 293-1/27	NB-RP-293-1/27	12I 1003/2	214	100	135	12	5	528	524	521	518	513	502	488	466	422	369	235	4170	2200	485	185		
RP 293-1/28	NB-RP-293-1/28	12I 1003/2	214	100	135	12	5	546	542	539	537	531	520	505	484	437	383	235	4230	2260	490	190		
RP 293-1/29	NB-RP-293-1/29	12I 1003/2	214	100	135	12	5	565	561	558	556	549	538	522	500	452	397	235	4290	2320	495	195		
RP 293-1/30	NB-RP-293-1/30	12I 1003/2	214	100	135	12	5	583	580	578	575	568	556	539	515	467	411	235	4350	2380	500	200		
RP 293-1/31	NB-RP-293-1/31	12I 1103/2	235	110	150	12	5	602	599	597	595	588	574	557	532	482	425	235	4450	2440	525	205		
RP 293-1/32	NB-RP-293-1/32	12I 1103/2	235	110	150	12	5	621	618	617	614	608	593	574	549	497	439	235	4510	2500	530	210		
RP 293-1/33	NB-RP-293-1/33	12I 1103/2	235	110	150	12	5	640	637	636	633	627	612	592	563	512	453	235	4570	2560	535	215		
RP 293-1/34	NB-RP-293-1/34	12I 1103/2	235	110	150	12	5	660	657	655	653	644	627	606	574	527	467	235	4630	2620	540	220		
								η% راندمان	65	71	73	74	75	74.5	73	70	66	61						
								NPSH (m)*	2.5	2.7	2.8	3	3.2	3.6	4	4.5	5	5.5						