

نوع پمپ R.P M.S.V 125	توان P		جریان (آمپر) A	قطر فلنج mm		میزان آبدهی Q m3/h l/s	n ≈ 2900 rpm , 50 HZ							
	KW	HP		مکش	رانش		H (m)	5	7	9	10	11	12	14
								1.4	1.9	2.5	2.8	2	3.3	3.9
R.P M.S.V-125/5	2.2	3	4.6				48	45.7	42.5	41	38.5	35.4	24.5	
R.P M.S.V-125/6	2.2	3	4.6				58	55	51.2	49.2	46.5	42.5	29	
R.P M.S.V-125/7	3	4	6				66.5	64	59.7	57	53.7	48.7	33.5	
R.P M.S.V-125/8	3	4	6				76	73	68	64.8	60.6	55	38	
R.P M.S.V-125/9	3	4	6				85	81.5	75.5	71.5	66.2	60	42.5	
R.P M.S.V-125/10	4	5.5	8.4	65	65	H (m)	94	90.2	83.6	79	73.1	66.3	47	
R.P M.S.V-125/11	4	5.5	8.4				104	99.5	91.9	86.8	80.2	72.6	51.5	
R.P M.S.V-125/12	5.5	7.5	10.5	113	105		100	94.6	87.3	78.9	56			
R.P M.S.V-125/13	5.5	7.5	10.5	123	118		109	102	94.4	85.2	60.5			
R.P M.S.V-125/14	5.5	7.5	10.5	132	127		117	110	101	91.3	65			
R.P M.S.V-125/15	5.5	7.5	10.5	141	136		125	118	108	97.6	71			
R.P M.S.V-125/16	5.5	7.5	10.5	150	144		133	125	115	104	75.5			

