

R.P M.S.V 130

نوع پمپ R.P M.S.V 130	توان P		جریان (آمپر)		قطر فلنج mm		میزان آبدهی Q m3/h l/s	n ≈ 2900 rpm , 50 HZ						
	KW	HP	380 V A	220 V A	مکش	رانش		6	12	18	24	30	36	39
								1.7	3.4	5	6.7	8.3	10	10.8
R.P M.S.V-130/1	1.1	1.5	2.6	6.9				13.3	12	9.9	7.7	5.4	3	1.6
R.P M.S.V-130/2	2.2	3	4.6	12.4				25	23.6	21.2	18	14	8.2	5.1
R.P M.S.V-130/3	3	4	6	*				36.4	33.8	30.9	27	21.5	14	10
R.P M.S.V-130/4	4	5.5	8.4	*				47	44.5	41	36	29	20	14.6
R.P M.S.V-130/5	5.5	7.5	10.5	*				61	58.6	54.7	48.7	39.3	27.5	20
R.P M.S.V-130/6	5.5	7.5	10.5	*	65	65	H (m)	64	61.8	57.8	51.8	42.5	29.8	22
R.P M.S.V-130/7	7.5	10	14.2	*				77.3	76	72.4	64	51.8	37.3	28
R.P M.S.V-130/8	11	15	21	*				86	84	79.8	72	59.5	42.2	32
R.P M.S.V-130/9	11	15	21	*				102	99.8	93	82.5	69	49	37
R.P M.S.V-130/10	11	15	21	*				113	109	101	90.4	75.5	54	41
R.P M.S.V-130/11	11	15	21	*				121	118	113	102	86	61.5	46

