

## CSB-10/10T/10A (WHITE)



- One way full range
- 3" polypropylene coated shield transducer
- 0.5" (13mm) voice coil diameter
- High impact polypropylene weather resistant enclosure
- Optional metal rotatable mounting brackets

<b>MODEL</b>	<b>CSB-10</b>
System Type	Passive Speaker Cabinet
Speaker	3" (77x77mm) Paper cone speaker 0.5" (13mm ) voice coil diameter
SPL at 1m/1w	85dB ( $\pm$ 3dB)
Frequency Response (-10dB)	160Hz-20kHz
Impedance	6 $\Omega$
Power rating	10W (RMS)
Connector	Wiring Terminal
External Controls	-
Power supply	-
Dimensions (WxDxH)	115x107x175mm (4.5"x4.2"x6.9")
Weight	0.52 kg (1.13 lbs)

<b>MODEL</b>	<b>CSB-10T</b>
System Type	Speaker Cabinet with transformer
Speaker	3" (77x77mm) Paper cone speaker 0.5" (13mm ) voice coil diameter
SPL at 1m/1w	85dB (±3dB)
Frequency Response (-10dB)	160Hz-20kHz
Impedance	70V 500Ω/1KΩ/2KΩ/4KΩ 100V 1KΩ/2KΩ/4KΩ
Power rating	70V 10W/5W/2.5W/1.25W 100V 10W/5W/2.5W
Connector	Wiring Terminal
External Controls	Power selective Switch
Power supply	-
Dimensions (W×D×H)	115x107x175mm (4.5"x4.2"x6.9")
Weight	0.9kg (1.98 lbs)

<b>MODEL</b>	<b>CSB-10A</b>
System Type	Active Speaker Cabinet
Speaker	3" (77x77mm) Paper cone speaker 0.5" (13mm ) voice coil diameter
SPL at 1m/1w	85dB (±3dB)
Frequency Response (-10dB)	160Hz-20kHz
Impedance	4Ω
Power rating	10W (RMS)
Connector	Input-RCA and φ6.3 Balanced/ Output-lick φ6.3 Jack
External Controls	Volume control/Power Switch
Power supply	220V-240V/50Hz 110V-220V/60Hz
Dimensions (W×D×H)	115x107x175mm (4.5"x4.2"x6.9")
Weight	1.06 kg (2.34 lbs)